

Current Transformer (7.2kV)



- 옥내용 (For Indoor)
- 권선형 (Winding Type)
- 일반 계기 및 보호 계전기용 (For Metering & Protection)
- Epoxy Mold로 절연특성 강화
(Insulation : Epoxy Vacuum Molding)


■ For Metering

Type	WH9A or WH9DA	
Standard	KS C 1706	IEC 61869-2
Max. Voltage	7.2 kV	
Insulation Level	7.2 / 22 / 60 kV (6A)	7.2 / 20 / 60 kV
Short time Current Max, kA	40 kA / 1 sec.	
Rated Primary Current	800 A or 800 / 400 A 이하	
Rated Secondary Current	5 or 1 A	
Rated Burden	15 ~ 40 VA	
Accuracy Class	1.0	
Rated Continuous Thermal Current	1.0 In	1.2 In
Frequency	60 Hz (Others on request)	
Weight	≒ 30 kg	

■ For Protection

Type	WH9RA or WH9DRA	
Standard	JEC 1201	IEC 61869-2
Max. Voltage	6.9 kV	7.2 kV
Insulation Level	6.9 / 22 / 60 kV	7.2 / 20 / 60 kV
Short time Current Max, kA	40 kA / 1 sec.	
Rated Primary Current	800A or 800 / 400A 이하	
Rated Secondary Current	5 or 1 A	
Rated Burden	15 ~ 40 VA	
Accuracy Class	1P	5P, 10P
Over Current Factor	n > 10 or 20	n > 10 or 20
Rated Continuous Thermal Current	1.0 In	1.2 In
Frequency	60 Hz (Others on request)	
Weight	≒ 30 kg	

■ Dimension & Drawing



Specification

Service	Type	Short time Current	Current Ratio (A)	KS C 1706		JEC 1201			IEC 61869-2			
				Class	Burden	Class	Burden	n >	Class	Burden	n >	
Metering	WH9A (1 Core Single Ratio)	75 In	400 ~ 500 / 5	0.5	15	—	—	—	0.5	15	—	
		150 In	200 ~ 250 / 5									
		300 In	100 ~ 120 / 5									
		8 kA	10 ~ 25 / 5									
		12.5 kA	15 ~ 30 / 5	1.0	40							
		25 kA	25 ~ 75 / 5									
		31.5 kA	40 ~ 800 / 5									
		40 kA	50 ~ 800 / 5									
	WH9DA (1 Core Double Ratio)	75 In	400,200 ~ 500,250 / 5	0.5	15	—	—	—	0.5	15	—	
		150 In	200,100 ~ 240,120 / 5									
		300 In	10,5 ~ 120,60 / 5									
		8 kA	20,10 ~ 50,25 / 5									
		12.5 kA	30,15 ~ 60,30 / 5	1.0	40							
		25 kA	50,25 ~ 60,30 / 5									
		31.5 kA	80,40 ~ 800,400 / 5									
		40 kA	100,50 ~ 800,400 / 5									
Protection	WH9RA (1 Core Single Ratio)	75 In	400 ~ 500 / 5	—	—	1P	15	10	5P	15	10	
		150 In	200 ~ 250 / 5									
		300 In	5 ~ 120 / 5									
		8 kA	10 ~ 25 / 5									
		12.5 kA	15 ~ 30 / 5						10P			
		25 kA	25 ~ 75 / 5									
		31.5 kA	40 ~ 800 / 5									
		40 kA	50 ~ 800 / 5									
		75 In	400 ~ 500 / 5	—	—	1P	15	20	5P	15	20	
		150 In	200 ~ 250 / 5									
		300 In	5 ~ 120 / 5									
		8 kA	15 ~ 25 / 5									
		12.5 kA	20 ~ 30 / 5				40	10	10P	30		
		25 kA	40 ~ 75 / 5									
		31.5 kA	60 ~ 800 / 5									
		40 kA	75 ~ 800 / 5									
	WH9RA (1 Core Single Ratio)	75 In	400 ~ 500 / 5	—	—	1P	40	20	5P	30	20	
		150 In	5 ~ 250 / 5									
		300 In	5 ~ 120 / 5									
		8 kA	30 ~ 50 / 5									
		12.5 kA	40 ~ 60 / 5						10P			
		25 kA	75 ~ 150 / 5									
		31.5 kA	120 ~ 800 / 5									
		40 kA	150 ~ 800 / 5									

Current Transformer (7.2kV)

■ Specification

Service	Type	Short time Current	Current Ratio (A)	KS C 1706		JEC 1201			IEC 61869-2		
				Class	Burden	Class	Burden	n >	Class	Burden	n >
Protection	WH9DRA (1 Core Double Ratio)	75 In	400,200 ~ 500,250 / 5	—	—	1P	40	10/5	5P	30	10/5
		150 In	200,100 ~ 240,120 / 5								
		300 In	10,5 ~ 120,60 / 5								
		8 kA	30,15 ~ 50,25 / 5								
		12,5 kA	40,20 ~ 60,30 / 5								
		25 kA	80,40 ~ 60,30 / 5								
		31,5 kA	100,50 ~ 800,400 / 5								
		40 kA	150,75 ~ 800,400 / 5								
		40 In	10,5 ~ 800,400 / 5					20/10	10P	30	20/10
		75 In	400,200 ~ 500,250 / 5								
		150 In	10,5 ~ 120,60 / 5								
		300 In	10,5 ~ 120,60 / 5								
		8 kA	30,15 ~ 100,50 / 5								
		12,5 kA	40,20 ~ 120,60 / 5								
		25 kA	80,40 ~ 150,75 / 5								
		31,5 kA	150,75 ~ 800,400 / 5								
		40 kA	150,75 ~ 800,400 / 5								
Metering & Protection	2WH9RA (2 Core Single Ratio)	40 In	5 ~ 800 / 5 / 5	—	—	1P	15/15	10	1,0/5P 1,0/10P	15/15	10
		75 In	5 ~ 500 / 5 / 5								
		150 In	5 ~ 250 / 5 / 5								
		300 In	5 ~ 120 / 5 / 5								
		8 kA	15 ~ 800 / 5 / 5								
		12,5 kA	20 ~ 800 / 5 / 5								
		25 kA	40 ~ 800 / 5 / 5								
		31,5 kA	50 ~ 800 / 5 / 5								
		40 kA	60 ~ 800 / 5 / 5								
		40 In	5 ~ 800 / 5 / 5	—	—	1P	15/15	20	1,0/5P 1,0/10P	15/15	20
		75 In	5 ~ 500 / 5 / 5								
		150 In	5 ~ 250 / 5 / 5								
		300 In	5 ~ 120 / 5 / 5								
		8 kA	25 ~ 800 / 5 / 5								
		12,5 kA	30 ~ 800 / 5 / 5								
		25 kA	50 ~ 800 / 5 / 5								
		31,5 kA	80 ~ 800 / 5 / 5								
		40 kA	100 ~ 800 / 5 / 5								
		40 In	5 ~ 800 / 5 / 5	—	—	1P	40/40	20	1,0/5P 1,0/10P	30/30	20
		75 In	5 ~ 500 / 5 / 5								
		150 In	5 ~ 250 / 5 / 5								
		8 kA	50 ~ 800 / 5 / 5								
		12,5 kA	60 ~ 800 / 5 / 5								
		25 kA	120 ~ 800 / 5 / 5								
		31,5 kA	150 ~ 800 / 5 / 5								
		40 kA	200 ~ 800 / 5 / 5								

Specification

Service	Type	Short time Current	Current Ratio (A)	KS C 1706		JEC 1201			IEC 61869-2		
				Class	Burden	Class	Burden	n >	Class	Burden	n >
Metering & Protection	2WH9DRA (2 Core Double Ratio)	40In	10,5 ~ 800,400 / 5 / 5	-	-	1P	15/15	10/5	1.0/5P 1.0/10P	15/15	10/5
		75 In	10,5 ~ 500,250 / 5 / 5								
		150 In	10,5 ~ 240,120 / 5 / 5								
		300 In	10,5 ~ 120,60 / 5 / 5								
		8 kA	30,15 ~ 800,400 / 5 / 5								
		12,5 kA	40,20 ~ 800,400 / 5 / 5								
		25 kA	60,30 ~ 800,400 / 5 / 5								
		31,5 kA	120,60 ~ 800,400 / 5 / 5								
		40 kA	120,60 ~ 800,400 / 5 / 5								
		40 In	10,5 ~ 800,400 / 5 / 5	-	-	1P	15/15	20/10	1.0/5P 1.0/10P	15/15	20/10
		75 In	10,5 ~ 500,250 / 5 / 5								
		150 In	10,5 ~ 240,120 / 5 / 5								
		300 In	10,5 ~ 120,60 / 5 / 5								
		8 kA	30,15 ~ 800,400 / 5 / 5								
		12,5 kA	60,30 ~ 800,400 / 5 / 5								
		25 kA	100,50 ~ 800,400 / 5 / 5								
		31,5 kA	200,100 ~ 800,400 / 5 / 5								
		40 kA	200,100 ~ 800,400 / 5 / 5								
		40 In	10,5 ~ 800,400 / 5 / 5	-	-	1P	40/40	20/10	1.0/5P 1.0/10P	30/30	20/10
		75 In	10,5 ~ 500,250 / 5 / 5								
		150 In	10,5 ~ 240,120 / 5 / 5								
		8 kA	40,20 ~ 800,400 / 5 / 5								
		12,5 kA	80,40 ~ 800,400 / 5 / 5								
		25 kA	150,75 ~ 800,400 / 5 / 5								
		31,5 kA	300,150 ~ 800,400 / 5 / 5								
		40 kA	300,150 ~ 800,400 / 5 / 5								

※ IEEE C 57.13 규격에 의한 제품의 생산이 가능하며, 계급, 부담, 과전류 정수 등의 사양변경에 따라 다양한 생산도 가능합니다.

Can manufacture the products based on IEEE C 57.13 standards, and also Can manufacture the various products by change of specification, such as the Accuracy class, Burden and Over-current factor.

※ 단시간 과전류값은 2차측에 정격 부담의 25% 부담을 접속한 상태에서의 보증치 입니다.

Short time current being subject to 25% rated burden connection at secondary side for all ratios.