


Voltage Transformer (12kV)



- 옥내용
For Indoor
- 단상 비접지형
Single Phase,
Line to Line Voltage Transformer
- 일반 계기 및 보호계전기 용
For Metering & Protection
- Epoxy Mold로 절연특성 강화
Insulation : Epoxy Vacuum Molding.

Dimension & Drawing



Specification

Standard	KS C 1706	JEC 1201	IEC 61869-3
Max. Voltage	11.5 kV	11.5 kV	12 kV
Primary Voltage	11000 or 11400 V		
Secondary Voltage	110 V		
Insulation Level	11.5 / 28 / 75 kV (10B)	11.5 / 28 / 75 kV	12 / 28 / 75 kV
Over Voltage Factor	1.1Vn Continuous		1.2Vn Continuous
Frequency	60 Hz (Others on request)		

※ 상기의 정격 1차, 2차 전압은 표준형이며, 그 외의 전압비의 제품도 생산 가능합니다.

Above rated primary and secondary voltage is standard type, and besides, can be manufacture the another voltage ratio products.

※ VT FUSE는 별매품입니다.

If user wants to change the fuse, can be make an extra cost.

Rated Output

Accuracy Class			Type & Rated Output Burden
KS C 1706	JEC 1201	IEC 61869-3	LV36
0.5	—	0.5	100
1.0	1P	1.0	200
3.0	3P	3.0	500
Weight			≒ 29.0 kg