



△						
△						
△						
△						
△	FOR APPROVAL					
△	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED	

DESIGN DATA

CODE	N/A
UNIT	mm
KIND OF FLUID	-
PRESS.	10(Max.) Kg/Cm ²
TEMP. (SENSOR)	-20 ~ 60 °C
TEMP. (ELECTRONICS)	-20 ~ 60 °C
CONTACT RATING	250V AC, 10A
POWER SUPPLY	-
ENCLOSURE	EXPUSION PROOF / Ex d IIC T6,IP65
SP.GR	0.7(Min.)
OUTPUT	1SPDT
WISCOSITY	1Pa.s/10P Less
MOISTURE	Max 80%RH
TAG NO.	-

NOTES

REVISION

6	FLOAT	316SS	1		
5	SHAFT	316SS	1		
4	SUPPORT	304SS	1		
3	FLANGE	304SS	1		
2	HOUSING	AC2B	1		
1	COVER	AC2B	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-

TITLE
Magnetic Float Type Level Switch
SHM-100-A-1-A-1-B-1
ASSEMBLY DRAWING

MANUFACTURER

Seojin Instech Co., Ltd.

SCALE	1:1	EXP CODE	0000	Work Order No.	-	REV	1
N/S	DATE NO.	SJ-MO11-DWG-AP003					