

DESIGN DATA			
CODE	N/A		
UNIT	mm		
KIND OF FLUID	-		
PRESS.	DESIGN	10(Max.)	Kg/Cm ²
	OPERATING	-	Kg/Cm ²
TEMP.	DESIGN	-20 ~ 60	°C
(SENSOR)	OPERATING	-	°C
TEMP.	DESIGN	-20 ~ 60	°C
(ELECTRONICS)	OPERATING	-	°C
CONTACT RATING	250V AC, 10A		
POWER SUPPLY	-		
ENCLOSURE	WEATHER PROOF		
SP.GR	0.7(Min.)		
OUTPUT	1SPDT		
VISCOSITY	1Pa.s/10P Less		
MOISTURE	Max 80%RH		

NOTES

REVISION

NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK
7	FLANGE	304SS	2	1" ANSI 150# RF	
6	PIPE	A105	2	SCH.20 1"	
5	FLOAT	316SS	1		
4	SHAFT	316SS	1		
3	CHAMBER	A106B	1		
2	FLANGE	304SS	2	3" ANSI 150# RF	
1	TERMINAL BOX	AC2B	1		

BILL OF MATERIAL


CUSTOMER

PROJECT

TITLE


Magnetic Float Type Level Switch
SHM-100-B-1-A-1-A-1
ASSEMBLY DRAWING

MANUFACTURER



Seojin Instech Co., Ltd.

REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED
△					
△					
△					
△					
△					

SCALE			REV.
N/S	DWG. NO.	ERP CODE 0000	Work Order No. -
D	SU-M011-DWG-AP008		