

△						
△						
△						
△						
△	FOR APPROVAL					
REV	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED	

DESIGN DATA

CODE	N/A
UNIT	mm
KIND OF FLUID	-
PRESS.	10(Max.) kg/Cm <sup>2</sup>
TEMP. (SENSOR)	-20 ~ 60 °C
TEMP. (ELECTRONICS)	-20 ~ 60 °C
CONTACT RATING	250V AC, 10A
POWER SUPPLY	-
ENCLOSURE	WEATHER PROOF
SP.GR	0.7(Min.)
OUTPUT	1SPDT
VISCOSITY	1Pa.s/10P Less
MOISTURE	Max 80%RH
TAG NO.	-

NOTES

REVISION


NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK
6	FLOAT	316SS	1		
5	SHAFT	316SS	1		
4	SUPPORT	316SS	1		
3	FLANGE	316SS	1		
2	HOUSING	AC2B	1		
1	COVER	AC2B	1		

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-

TITLE	Magnetic Float Type Level Switch SHM-100-B-1-A-1-B-1 ASSEMBLY DRAWING
-------	---

MANUFACTURER

**Seoul Instech Co., Ltd.**

SCALE: N/S

DATE: SU-MO11-DWG-AP004

REV: 1