

*L : MAKER STANDARD

— Ordering Information —

1. Model : A050
2. Union Type : A
3. Material
☐D : 316SS ☐F : 316LSS ☐Z : Other_____
4. Gauge Connection Size
☐0 : 1/4" ☐1 : 3/8"
☐2 : 1/2" ☐9 : Other_____
5. Gauge Connection Type
☐A : PF(F) ☐B : PT(F) ☐C : NPT(F) ☐Z : Other_____
6. Process Connection Size
☐B : 1/4" ☐C : 3/8" ☐D : 1/2" ☐Z : Other_____
7. Process Connection Type
☐G : PF(M) ☐H : PT(M)
☐J : NPT(M) ☐Z : Other_____
8. Unused character
☐A0000 : None

— Standard Specifications —

9. Max. Working Pressure Up To 160 MPa, at 20°C


SAMPLE CODE
A050 A D 1 A C G A0000

2					
1					
NO	REASON	DATE	REVIEWED BY	CHECKED BY	APPROVED BY
REVISION					

This drawing and the specifications are the intellectual property of WISE CONTROL INC. therefore, without a prior written consent from WISE CONTROL INC., it is strictly prohibited to reproduce the drawing or manufacture the identical products according to its specifications provided here.

Unless otherwise specified
 Decimal dimensions ± 5
 Angle dimensions $\pm 1^\circ$
 Dimensions are in milli meter

THIRD ANGLE PROJECTION



	SIGNATURE	DATE
PREPARED BY	K.S.LEE	18.06.01
REVIEWED BY	J.S.PARK	18.06.01
APPROVED BY	D.M.CHO	18.06.01
REV. NO.	0	

WISE[®]
WISE Control Inc.

DRAWING TITLE :		
PULSATION DAMPNER		
DWG NO.		
A050A-S.T.D		
SCALE : N/S	W.T.	SHEET OF