

Bushing Type Current Transformer (BCT)



- Standard : IEEE C 57.13
- Type : **BC440**
- Application : For Metering & Protection
- Frequency : 60 Hz (Others on request)
- Insulation Level : 0.6 BIL 10kV full wave
- Continuous Thermal Current Rating Factor :
1.33 at 30°C Amb. 1.0 at 55°C Amb.
- Insulation : Epoxy Vacuum Molding
- Shield Winding

■ Specification

Current Ratio (A)	Protection Class	Metering Class	Weight (kg)
1000 / 5	C100	0.3 B-0.9	≈ 60
1200 / 5	C100	0.3 B-0.9	
1500 / 5	C200	0.3 B-1.8	
2000 / 5	C200	0.3 B-1.8	
2500 / 5	C200	0.3 B-1.8	
3000 / 5	C400	0.3 B-1.8	
4000 / 5	C400	0.3 B-1.8	
5000 / 5	C800	0.3 B-1.8	
6000 / 5	C800	0.3 B-1.8	
7500 / 5	C800	0.3 B-1.8	
10000 / 5	C800	0.3 B-1.8	
12000 / 5	C800	0.3 B-1.8	
15000 / 5	C800	0.3 B-1.8	

■ Dimension & Drawing

