



WIRING DIAGRAM

ELECTRIC RATING (RESISTIVE)	
MAX.CONTACT RATING	50W / 70VA
MAX.SWITCHING CURRENT	0.5A
MAX.SWITCHING VOITAGE	350VDC 300VAC

DESIGN DATA

CODE	N/A
UNIT	mm
KIND OF FLUID	-
PRESS.	DESIGN - Kg/Cm ²
	OPERATING - Kg/Cm ²
TEMP. (SENSOR)	DESIGN -20 ~ 80 °C
	OPERATING - °C
TEMP. (ELECTRONICS)	DESIGN -20 ~ 60 °C
	OPERATING - °C
SP.GR.	MORE THAN 0.74
VISCOSITY	10 P / 1 Pa.s
ENCLOSURE	WEATHER PROOF
FLANGE SIZE	JIS 10K 80A 6T FF FLANGE
FLOAT TYPE	φ49x50L

TAG NO.	L	L1	L2	L3	L4

NOTES

1. () Dimensions are reference dimensions.

REVISION

7	COULPING	316SS	1		
6	FLOAT	316SS	2		
5	FLOAT STOPPER	304SS	4		
4	STEM	304SS	1	φ13.8	
3	FLANGE	304SS	1		
2	HOUSING	ADC12	1		
1	COVER	ADC12	1		

NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-
TITLE	FLOAT TYPE LEVEL SWITCH ST-2S-B-1-A-1-A-1-B-3 ASSEMBLY DRAWING
MANUFACTURER	SeoJin Instech Co., Ltd.

SCALE	N/S	ERP CODE	-	Work Order No.	-	REV.	
DWG NO.	SJ-M003-DWG-AP007						