

DESIGN DATA

CODE	N/A		
UNIT	mm		
KIND OF FLUID	-		
PRESS.	DESIGN	Max. 10	Kg/Cm ²
	OPERATING	-	Kg/Cm ²
TEMP. (SENSOR)	DESIGN	-20 ~ 80	°C
	OPERATING	-	°C
TEMP. (ELECTRONICS)	DESIGN	-20 ~ 60	°C
	OPERATING	-	°C
SP.GR.	MORE THAN 0.74		
VISCOSITY	10 P / 1 Pa.s		
ENCLOSURE	WEATHER PROOF		
FLANGE SIZE	JIS 10K 80A FF		
FLOAT TYPE	φ49x50L		

TAG NO.	L	L1	L2	L3	L4

NOTES

1. () Dimensions are reference dimensions.

REVISION

7	COUPLING	316SS	1		
6	FLOAT	316SS	2		
5	FLOAT STOPPER	304SS	4		
4	STEM	304SS	1	φ13.8	
3	FLANGE	304SS	1		
2	HOUSING	ADC12	1		
1	COVER	ADC12	1		

NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK
----	-------------	----------	------	---------------	--------

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-


TITLE	FLOAT TYPE LEVEL SWITCH ST-2S-B-1-A-1-D-1-B-3 ASSEMBLY DRAWING
-------	--

MANUFACTURER	SeoJin Instech Co., Ltd.
--------------	--------------------------

SCALE	N/S	ERP CODE	-	Work Order No.	-	REV.	
-------	-----	----------	---	----------------	---	------	--

DWG NO.	SJ-M003-DWG-AP010
---------	-------------------

WIRING DIAGRAM



ELECTRIC RATING (RESISTIVE)

MAX.CONTACT RATING	5W
MAX.SWITCHING CURRENT	DC 0.4A / AC 0.28A
MAX.SWITCHING VOLTAGE	125VAC 175VDC