


ELECTRIC RATING (RESISTIVE)	
MAX.CONTACT RATING	5W
MAX.SWITCHING CURRENT	DC 0.4A / AC 0.28A
MAX.SWITCHING VOLTAGE	125VAC 175VDC

		10				11	
DESIGN DATA							
CODE		N/A					
UNIT		mm					
KIND OF FLUID			-				
PRESS.	DESIGN	Max. 10			Kg/Cm ²		
	OPERATING	-			Kg/Cm ²		
TEMP. (SENSOR)	DESIGN	-20 ~ 80			°C		
	OPERATING	-			°C		
TEMP. (ELECTRONICS)	DESIGN	-20 ~ 60			°C		
	OPERATING	-			°C		
SP.GR.		MORE THAN 0.74					
VISCOSITY		10 P / 1 Pa.s					
ENCLOSURE		WEATHER PROOF					
FLANGE SIZE		JIS 10K 80A FF					
FLOAT TYPE		ø49x50L					
TAG NO.		L	L1	L2	L3	L4	
NOTES							
1. () Dimensions are reference dimensions.							
REVISION							
7	COUPLING		316SS	1			
6	FLOAT		316SS	3			
5	FLOAT STOPPER		304SS	6			
4	STEM		304SS	1	ø13.8		
3	FLANGE		304SS	1			
2	HOUSING		ADC12	1			
1	COVER		ADC12	1			
NO	DESCRIPTION		MATERIAL	Q'TY	SPECIFICATION	REMARK	
BILL OF MATERIAL							
CUSTOMER							
PROJECT							
TITLE							
FLOAT TYPE LEVEL SWITCH							
ST-4S-D-1-A-1-D-1-B-3							
ASSEMBLY DRAWING							
MANUFACTURER							
SeoJin Instech Co.,Ltd.							
SCALE			ERP CODE	Work Order No.		REV.	
N/S	DWG NO.		SJ-M003-DWG-AP022				