



WIRING DIAGRAM

ELECTRIC RATING (RESISTIVE)	
MAX.CONTACT RATING	50W / 70VA
MAX.SWITCHING CURRENT	0.5A
MAX.SWITCHING VOITAGE	350VDC 300VAC

DESIGN DATA

CODE	N/A				
UNIT	mm				
KIND OF FLUID	—				
PRESS.	DESIGN	—			Kg/Cm ²
	OPERATING	—			Kg/Cm ²
TEMP. (SENSOR)	DESIGN	-20 ~ 80			°C
	OPERATING	—			°C
TEMP. (ELECTRONICS)	DESIGN	-20 ~ 60			°C
	OPERATING	—			°C
SP.GR.	MORE THAN 0.74				
VISCOSITY	10 P / 1 Pa.s				
ENCLOSURE	WEATHER PROOF				
FLANGE SIZE	JIS 10K 80A FF(6T)				
FLOAT TYPE	φ49x50L				
TAG NO.	L	L1	L2	L3	L4
	—	—	—	—	—

NOTES

1. () Dimensions are reference dimensions.

REVISION

7	COULPING	316SS	1		
6	FLOAT	316SS	4		
5	FLOAT STOPPER	316SS	8		
4	STEM	316SS	1	φ13.8	
3	FLANGE	316SS	1		
2	HOUSING	ADC12	1		
1	COVER	ADC12	1		

NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK
----	-------------	----------	------	---------------	--------

BILL OF MATERIAL

CUSTOMER	-
----------	---

PROJECT	-
---------	---

TITLE	FLOAT TYPE LEVEL SWITCH ST-4S-D-1-B-1-A-1-B-3 ASSEMBLY DRAWING
-------	--

MANUFACTURER	SeoJin Instech Co., Ltd.
--------------	--------------------------

SCALE	N/S	ERP CODE	-	Work Order No.	-	REV.	
DWG NO.	SJ-M003-DWG-AP020						