



WIRING DIAGRAM

ELECTRIC RATING (RESISTIVE)	
MAX.CONTACT RATING	50W / 70VA
MAX.SWITCHING CURRENT	0.5A
MAX.SWITCHING VOITAGE	350VDC 300VAC

DESIGN DATA

CODE	N/A	
UNIT	mm	
KIND OF FLUID	-	
PRESS.	DESIGN	Max. 5 Kg/Cm <sup>2</sup>
	OPERATING	AMT Kg/Cm <sup>2</sup>
TEMP. (SENSOR)	DESIGN	-20 ~ 60 °C
	OPERATING	AMB °C
TEMP. (ELECTRONICS)	DESIGN	-20 ~ 60 °C
	OPERATING	AMB °C
SP.GR.	MORE THAN 0.62	
VISCOSITY	10 P / 1 Pa.s	
ENCLOSURE	WEATHER PROOF	
FLANGE SIZE	JIS 10K 80A FF	
FLOAT TYPE	ø75x80L	

NOTES

1. ( ) Dimensions are reference dimensions.

REVISION

6	FLOAT	PVC	4		
5	FLOAT STOPPER	PVC	8		
4	STEM	304SS+PVC	1	ø22	
3	FLANGE	PVC	1		
2	HOUSING	ADC12	1		
1	COVER	ADC12	1		

NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK
----	-------------	----------	------	---------------	--------

BILL OF MATERIAL

CUSTOMER	-
----------	---

PROJECT	-
---------	---

TITLE	FLOAT TYPE LEVEL SWITCH ST-4S-D-1-C-1-A-1-B-3 ASSEMBLY DRAWING
-------	--

MANUFACTURER	SeoJin Instech Co., Ltd.
--------------	--------------------------

SCALE	N/S	ERP CODE	-	Work Order No.	-	REV.	
DWG NO.	SJ-M003-DWG-AP023						