

ELECTRIC RATING (RESISTIVE)	
MAX.CONTACT RATING	50W / 70VA
MAX.SWITCHING CURRENT	0.5A
MAX.SWITCHING VOITAGE	350VDC 300VAC

DESIGN DATA						
CODE	N/A					
UNIT	mm					
KIND OF FLUID	—					
PRESS.	DESIGN	Max. 1		Kg/Cm ²		
	OPERATING	—		Kg/Cm ²		
TEMP. (SENSOR)	DESIGN	-20 ~ 80		°C		
	OPERATING	—		°C		
TEMP. (ELECTRONICS)	DESIGN	-20 ~ 60		°C		
	OPERATING	—		°C		
SP.GR.	MORE THAN 1.0					
VISCOSITY	10 P / 1 Pa.s					
ENCLOSURE	WEATHER PROOF					
FLANGE SIZE	JIS 10K 80A FF					
FLOAT TYPE	ø66x79L					
TAG NO.	L	L1	L2	L3	L4	



NOTES

1. () Dimensions are reference dimensions.

REVISION

7	COUPLING	316SS	1	
6	FLOAT	PTFE	4	
5	FLOAT STOPPER	PTFE	8	
4	STEM	304SS+PTFE	1	Ø16
3	FLANGE	304SS+PTFE	1	
2	HOUSING	ADC12	1	
1	COVER	ADC12	1	

BILL OF MATERIAL

CUSTOMER					—
PROJECT					—
TITLE FLOAT TYPE LEVEL TRANSMITTER ST-4S-D-2-D-1-D-1-B-3 ASSEMBLY DRAWING					
MANUFACTURER  SeoJin Instech Co., Ltd.					
SCALE		ERP CODE	Work Order No.	REV.	
N/S	DWG NO.	SJ-M003-DWG-AP030	—	—	