


SEE NOTE A.



WIRING DIAGRAM

NOTES

- A. CONDUIT CONNECTION
- ☒ PF1/2"
  - ☐ PT1/2"
  - ☐ PF3/4"
  - ☐ PT3/4"
  - ☐ NPT1/2"
  - ☐ NPT3/4"
  - ☐ Etc.( )

DESIGN DATA

CODE	N/A	UNIT	m/m
KIND OF FLUID	DESIGN	OPERATING	3(Max.) kg/Cm <sup>2</sup>
PRESS.	DESIGN	OPERATING	-20 ~ 70 °C
TEMP. (SENSOR)	DESIGN	OPERATING	-20 ~ 70 °C
TEMP. (ELECTRONICS)	DESIGN	OPERATING	-20 ~ 70 °C
CONTACT RATING	DESIGN	OPERATING	-
POWER SUPPLY	DESIGN	OPERATING	DC 15 ~ 36V
ENCLOSURE	DESIGN	OPERATING	WEATHER PROOF
OUTPUT	DESIGN	OPERATING	4 to 20 mA DC (2 Wire) / LCD With Backlight
VISCOSITY	DESIGN	OPERATING	1Pa.s/10P Less
MOISTURE	DESIGN	OPERATING	Max 80%RH
COMPENSATION Temp.	DESIGN	OPERATING	0 ~ 50 °C
ACCURACY	DESIGN	OPERATING	±0.25% of F.S.
APPLICATION	DESIGN	OPERATING	SUBMERSIBLE LIQUID L/T

NOTES

- 전송기는 밀폐된 공간에 설치하면 안되며, 대기압이 유지되는 공간에 설치되어야 한다.
- 설치 시 센서를 내부에 이물질이 쌓이지 않도록 조치 후 설치해야 한다.

REVISION

NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK
4	CABLE	Unshielded & SPS Wire Armored	1	m	
3	CONNECTOR	304SS	1		
2	DISPLAY HOUSING	ADC12	1		
1	SENSOR HOUSING	316LSS	1		

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-
TITLE	PRESSURE TYPE LEVEL TRANSMITTER SPT-1-A-1-A-1-A-1-A-1-A ASSEMBLY DRAWING
MANUFACTURER	Seojin Instech Co., Ltd.

REV	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED
△					
△					
△					
△					
△	FOR APPROVAL				

SCALE	N/S	DATE	0000	REV	-
MANUFACTURER	SJ-M019-DWG-AP001	DATE	0000	REV	-