

WIRING DIAGRAM

NOTES

- A. CONDUIT CONNECTION
- ☒ PF1/2"
- ☐ PT1/2"
- ☐ PF3/4"
- ☐ PT3/4"
- ☐ NPT1/2"
- ☐ NPT3/4"
- ☐ Etc. (

DESIGN DATA			
CODE	N/A		
UNIT	mm		
KIND OF FLUID	—		
PRESS.	DESIGN	3(Max.)	Kg/Cm ²
TEMP.	OPERATING	—	Kg/Cm ²
(SENSOR)	DESIGN	—20 ~ 70	°C
TEMP.	OPERATING	—	°C
(ELECTRONICS)	DESIGN	—20 ~ 70	°C
OPERATING	OPERATING	—	°C
CONTACT RATING	—		
POWER SUPPLY	DC 15 ~ 36V		
ENCLOSURE	WEATHER PROOF		
OUTPUT	4 to 20 ma DC (2 Wire) /CD With Backlight		
MOISTURE	1Pas/10P Less		
ACCURACY	Max 80%RH		
APPLICATION	0 ~ 50 °C		
	±0.25% of F.S.		
	SUBMERGIBLE LIQUID L/T		

NOTES

1. 전승기는 밀폐된 공간에 설치하면 안되며, 다7암이 유지되는 공간에 설치되어야 한다.
2. 설치 시 센서를 내부에 이물질이 쌓이지 않도록 조치 후 설치해야 한다.

REVISION



NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK
7	SINKER	304SS	1		
4	CABLE	Unhepa & 3/8 Wire Armored	m		
3	CONNECTOR	304SS	1		
2	DISPLAY HOUSING	ADC12	1		
1	SENSOR HOUSING	316LSS	1		

BILL OF MATERIAL	
CUSTOMER	—
PROJECT	—

REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED
△					
△					
△					
△					
△	FOR APPROVAL				

SPT-A-1-A-1-C-1-A
 ASSEMBLY DRAWING

MANUFACTURER
SeoJin Instech Co., Ltd.

SCALE	 1st angle projection	
DWG. NO.	EDP CODE 0000	WORK ORDER NO. -
N/S	REV. 	

SJJ-M019-DWG-AP004