



SUPPORT

DESIGN DATA

CODE	N/A	
UNIT	mm	
KIND OF FLUID	-	
PRESS.	DESIGN	Max. 10 Kg/cm ²
	OPERATING	- Kg/cm ²
TEMP.	DESIGN	-10 ~ 80 °C
(SENSOR)	OPERATING	- °C
TEMP.	DESIGN	-20 ~ 60 °C
(ELECTRONICS)	OPERATING	- °C
CONTACT RATING	250V AC, 5A	
POWER SUPPLY	220V AC ±10%, 5/60Hz	
ENCLOSURE	WEATHER PROOF	
POWER CONSUMPTION	Max. 4.0W	

NOTES

- () Dimensions are reference dimensions.

REVISION

NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION
7	SUPPORT	304SS	3	3.0t
6	PADDLE	304SS	1	
5	MAIN SHAFT	304SS	1	
4	FLANGE	304SS	1	JIS 10K 100A FF
3	STEM	304SS	1	
2	HOUSING	ADC	1	
1	COVER	ADC	1	

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-
TITLE	FLOAT TYPE LEVEL TRANSMITTER SPS+ / SUPPORT ASSEMBLY DRAWING
MANUFACTURER	Seojin Instech Co., Ltd.

SCALE	N/S	DATE	2020.05.21	DESIGNED	S.J.LIM	REVIEWED	D.N.LEE	APPROVED	S.H.LEE
FOR APPROVAL	2019.04.11	DATE	2020.05.21	DESIGNED	S.J.LIM	REVIEWED	D.N.LEE	APPROVED	S.H.LEE
REV.	Δ	DESCRIPTION	FOR APPROVAL	DATE	2019.04.11	DESIGNED	S.J.LIM	REVIEWED	D.N.LEE