



△							
△							
△							
△	FOR REVISION	2020.05.21	S.J.LIM	D.N.LEE	S.H.LEE		
△	FOR APPROVAL	2018.1.29	H.J.OJUNG	S.H.LEE	S.H.LEE		
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED		

DESIGN DATA			
CODE	N/A		
UNIT	mm		
KIND OF FLUID	—		
PRESS.	DESIGN OPERATING	Max. 10	Kg/Cm <sup>2</sup>
TEMP.	DESIGN OPERATING	—	Kg/Cm <sup>2</sup>
(SENSOR)	DESIGN OPERATING	-10 ~ 80	°C
TEMP.	DESIGN OPERATING	-20 ~ 60	°C
(ELECTRONICS)	DESIGN OPERATING	—	°C
CONTACT RATING	250V AC, 5A		
POWER SUPPLY	220V AC ±10%, 5/60Hz		
ENCLOSURE	WEATHER PROOF		
POWER CONSUMPTION	Max. 4.0W		
TAG NO.	L		

- NOTES**
1. ( ) Dimensions are reference dimensions.
  2. 2.5inch Flange 용임
  3. P type Paddle 꼭 조정하여 적용

**REVISION**

NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK
7	PADDLE GUARD	304SS	1		
6	PADDLE	304SS	1		
5	MAIN SHAFT	304SS	1		
4	NIPPLE	304SS	1		
3	STEM	304SS	1		
2	HOUSING	ADC12	1		
1	COVER	ADC12	1		

**BILL OF MATERIAL**

**CUSTOMER** —

**PROJECT** —

**TITLE** FLOAT TYPE LEVEL TRANSMITTER  
SPS+3-A-1-C-OP-OP-4-A  
ASSEMBLY DRAWING

**MANUFACTURER** **Seojin Instech Co., Ltd.**

**SCALE** N/S **DATE** 2020.05.21 **REV** 1

**APP. CODE** 0000 **WORK ORDER NO.** —