

Automatic Cutting Machine Series KM-3200



Digital Control Panel



- Digital Window for easy set-up
- Push button set-up for all machine functions
- Count of pieces needed
- Five-memory storage
- Various warning messages and alarm functions

Various sensors

- Material run-out sensor
- Default Value sensor for blade height
- Proximity sensor
- Power sensor to save working data in case of power failure

Feeding Part

- Material Hanger and Guide
- Aux. Roller and Feeding roller
- A knob for roller lift-up
- Roller friction adjusting nut
- Material pressing plate and adjusting nut

Cutting Part

- Upper/Lower/Wing blades
- Carbonated Blade life two times the life of competitor model
- Operate friendly design for easy replacement







Precise, Convenient, Accurate!

Specifications

Dimension(mm)	395 X 365 X 335 (W x D x H)
Weight (KG)	25
Cutting Material	Shrink tube, Hose, Rubber, Tin/Copper plate, Wire, Braided wire, Paper, Silicon tube, Film, vinlyl, etc.
Max. cutting width	200mm
Power supply	110/220 VAC, 50/60Hz, Single Phase
Power consumption	18 W ~ 250 W

^{*} Specifications are subject to change without notice.

Options



C	(0	P		-	3		1	2
M		a	t	е		r	i	а	
P	r	е	-	f	е	е	d	е	r

• more than 100mm wide



COP-314 <u>Static Remover</u>


 Removes static remaining between blades and material



C O P - 3 1 3

<u>Tube Spreading Unit</u>

• Increases productivity by spreading the compressed vinyl tube to be cut.



C O P - 3 1 5 / 3 1 6
Limit switch/
Photo sensor
Cuts costs by connecting to the extruder machine and output materials

940 Gosaek-dong, Gwonseon-gu, Suwon-si, Kyeonggi-do, 441-813, Korea Tel. 031-8012-9900 / Fax. 031-8012-9999



