



WIRING DIAGRAM

DESIGN DATA

CODE	N/A	
UNIT	mm	
KIND OF FLUID	-	
PRESS.	DESIGN OPERATING	3(Max.) Kg/Cm <sup>2</sup>
TEMP.	DESIGN OPERATING	-20 ~ 70 °C
TEMP.	DESIGN OPERATING	-20 ~ 70 °C
(ELECTRONICS)	DESIGN OPERATING	-
CONTACT RATING	-	-
POWER SUPPLY	DC 15 ~ 36V	
ENCLOSURE	WEATHER PROOF	
OUTPUT	4 to 20 mA DC (2 Wire) / LCD With Backlight	
VISCOSITY	1Pa.s/10P Less	
MOISTURE	Max 80%RH	
COMPENSATION Temp.	0 ~ 50 °C	
ACCURACY	±0.25% of F.S.	
APPLICATION	SUBMERSIBLE LIQUID L/T	

MEASURING RANGE ( m ) Max. 30m

TAG NO. -

NOTES

1. 전송기는 밀폐된 공간에 설치하면 안되며, 대기압이 유지되는 공간에 설치되어야 한다.
2. 설치 시 센서를 내부에 이물질이 쌓이지 않도록 조치 후 설치해야 한다.

REVISION

NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK
4	CABLE	Wireless & SPS Wire Armored	m		
1	SENSOR HOUSING	316LSS	1		

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-
TITLE	PRESSURE TYPE LEVEL TRANSMITTER SPL-1-A ASSEMBLY DRAWING

△					
△					
△					
△					
△	FOR APPROVAL				
REV	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED

MANUFACTURER

Seojin Instech Co., Ltd.

SCALE

DATE NO.

TEMP CODE

0000

WATER ORDER NO.

-

REV

N/S

SU-M020-DWG-AP002