



DESIGN DATA			
CODE	N/A		
UNIT	mm		
KIND OF FLUID		-	
PRESS.	DESIGN	5(Max.)	kg/cm <sup>2</sup>
	OPERATING	-	kg/cm <sup>2</sup>
TEMP. (SENSOR)	DESIGN	-10 ~ 120	°C
	OPERATING	-	°C
TEMP. (ELECTRONICS)	DESIGN	-10 ~ 120	°C
	OPERATING	-	°C
CONTACT RATING	250V AC, 0.5A		
POWER SUPPLY	-		
ENCLOSURE	WEATHER PROOF		
SP-GR	0.65(Min.)		
OUTPUT	<input type="checkbox"/> 1 SPST	<input type="checkbox"/>	
	<input type="checkbox"/> 1 SPDT	<input type="checkbox"/>	
VISCOSITY	1Pa.s/10P Less		
MOISTURE	Max 80%RH		
TAG NO.	-		

NOTES

REVISION

8	COVER	ADC 12	1		
7	HOUSING	ADC 12	1		
6	FLANGE	304SS	1		
4	SUPPORT	304SS	1		
3	PIN	304SS	1		
2	SHAFT	304SS	1		
1	FLOAT	304SS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-

TITLE	Magnetic Float Type Level Switch SFM-12-A-1-A-1-A-1 APPROVAL DRAWING
-------	--

MANUFACTURER

**Seojin Instech Co., Ltd.**

SCALE: 1:1

DATE: 0000

REV: N/S

WORK ORDER NO.: SU-MO10-DWG-AP003

RELT: