



WIRING DIAGRAM

DESIGN DATA

CODE	N/A
UNIT	mm
KIND OF FLUID	-
PRESS.	5(Max.) kg/Cm <sup>2</sup>
TEMP. (SENSOR)	-10 ~ 120 °C
TEMP. (ELECTRONICS)	-10 ~ 120 °C
CONTACT RATING	250V AC, 0.5A
POWER SUPPLY	-
ENCLOSURE	WEATHER PROOF
SP.GR	0.65(Min.)
OUTPUT	<input type="checkbox"/> 1 SPST <input type="checkbox"/> 1 SPDT
VISCOSITY	1Pa.s/10P Less
MOISTURE	Max 80%RH
TAG NO.	- , L1= L-151

NOTES

REVISION

10	PLATE	316SS	1	
9	SPACER BOLT	316SS	2	
8	COVER	ADC 12	1	
7	HOUSING	ADC 12	1	
6	FLANGE	316SS	1	
5	STEM	316SS	1	
4	SUPPORT	316SS	1	
3	PIN	316SS	1	
2	SHAFT	316SS	1	
1	FLOAT	316SS	1	
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION
				REMARK

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-
TITLE	Magnetic Float Type Level Switch SFM-14-B-1-A-1-A-1 APPROVAL DRAWING
MANUFACTURER	Seojin Instech Co., Ltd.
SCALE	1:1
DATE	0000
REV	N/S
FOR APPROVAL	DESCRIPTION
DATE	DESIGNED
REVIEWED	APPROVED