

Current Transformer (25.8kV)



- 옥내용 (For Indoor)
- 권선형 (Winding Type)
- 일반 계기 및 보호 계전기용 (For Metering & Protection)
- Epoxy Mold로 절연특성 강화
(Insulation : Epoxy Vacuum Molding)


■ For Metering

Type	WE6BA or WE6DBA	
Standard	KS C 1706	IEC 61869-2
Max. Voltage	25.8 kV	24 kV
Insulation Level	25.8 / 50 / 125 kV (20 B)	24 / 50 / 125 kV
Short time Current Max. kA	25 kA / 1 sec.	
Rated Primary Current	800 A or 800 / 400 A 이하	
Rated Secondary Current	5 or 1 A	
Rated Burden	15 ~ 40 VA	
Accuracy Class	1.0	
Rated Continuous Thermal Current	1.0 In	1.2 In
Frequency	60 Hz (Others on request)	
Weight	≒ 7 kg	

■ For Protection

Type	WE6RBA or WE6DRBA	
Standard	JEC 1201	IEC 61869-2
Max. Voltage	23 kV	24 kV
Insulation Level	23 / 50 / 125 kV	24 / 50 / 125 kV
Short time Current Max. kA	25 kA / 1 sec.	
Rated Primary Current	800 A or 800 / 400 A 이하	
Rated Secondary Current	5 or 1 A	
Rated Burden	15 ~ 40 VA	
Accuracy Class	1P	5P, 10P
Over Current Factor	n > 10 or 20	n > 10 or 20
Rated Continuous Thermal Current	1.0 In	1.2 In
Frequency	60 Hz (Others on request)	
Weight	≒ 7 kg	

■ Dimension & Drawing



Specification

Service	Type	Short time Current	Current Ratio (A)	KS C 1706		JEC 1201			IEC 61869-2		
				Class	Burden	Class	Burden	n >	Class	Burden	n >
Metering	WE6BA (1 Core Single Ratio)	40 In	400 ~ 600 / 5	0.5	15	—	—	—	0.5	15	—
		75 In	300 / 5								
		8 kA	400 ~ 800 / 5								
		12.5 kA	400 ~ 800 / 5								
		25 kA	500 ~ 800 / 5	1.0	40	—	—	—	1.0	30	—
		40 In	400 ~ 600 / 5								
		75 In	300 / 5								
		8 kA	400 ~ 800 / 5								
	WE6DBA (1 Core Double Ratio)	12.5 kA	400 ~ 800 / 5	0.5	15	—	—	—	0.5	15	—
		25 kA	500 ~ 800 / 5								
		40 In	400,200 ~ 600,300 / 5								
		75 In	300,150 / 5								
		8 kA	400,200 ~ 800,400 / 5	1.0	40	—	—	—	1.0	30	—
		12.5 kA	400,200 ~ 800,400 / 5								
		25 kA	500,250 ~ 800,400 / 5								
		40 In	400,200 ~ 600,300 / 5								
Protection	WE6RBA (1 Core Single Ratio)	75 In	300 / 5	—	—	1P	15	10	5P 10P	15	10
		8 kA	400 ~ 800 / 5								
		12.5 kA	400 ~ 800 / 5								
		25 kA	400 ~ 800 / 5								
		40 In	400 ~ 600 / 5	—	—	1P	15 40	20 10	5P 10P	15 30	20 10
		8 kA	400 ~ 600 / 5								
		12.5 kA	400 ~ 600 / 5								
		25 kA	500 ~ 600 / 5								
	WE6DRBA (1 Core Double Ratio)	40 In	400,200 ~ 600,300 / 5	—	—	1P	15	20/10	5P 10P	15	20/10
		8 kA	400,200 ~ 600,300 / 5								
		12.5 kA	400,200 ~ 600,300 / 5								
		40 In	400,200 ~ 600,300 / 5	—	—	1P	40	10/5	5P 10P	30	10/5
		8 kA	400,200 ~ 600,300 / 5								
		12.5 kA	400,200 ~ 600,300 / 5								

※ IEEE C 57.13 규격에 의한 제품의 생산이 가능하며, 계급, 부담, 과전류 정수 등의 사양변경에 따라 다양한 생산도 가능합니다.

Can manufacture the products based on IEEE C 57.13 standards, and also Can manufacture the various products by change of specification, such as the Accuracy class, Burden and Over-current factor.

※ 단시간 과전류값은 2차측에 정격 부담의 25% 부담을 접속한 상태에서의 보증치입니다.

Short time current being subject to 25% rated burden connection at secondary side for all ratios.