



WIRING DIAGRAM

DESIGN DATA

CODE	N/A				
UNIT	mm				
KIND OF FLUID	—				
PRESS.	DESIGN	Max. 2		Kg/Cm ²	
	OPERATING	—		Kg/Cm ²	
TEMP. (SENSOR)	DESIGN	-10 ~ 80		°C	
	OPERATING	—		°C	
TEMP. (ELECTRONICS)	DESIGN	-10 ~ 80		°C	
	OPERATING	—		°C	
ENCLOSURE	WEATHER PROOF				
MOUNTING TYPE&SIZE	PF 2"				
ELECTRODE MATERIAL	<input type="checkbox"/> 304SS	<input type="checkbox"/> 316SS			
ELECTRODE TUBING MATERIAL	<input type="checkbox"/> PE	<input type="checkbox"/> PTFE			
TAG NO.	L1	L2	L3	—	—

NOTES

REVISION

5	KEEPER	PVC	1		
4	ELECTRODE	304SS	2		
3	LOCK NUT	304SS	2		
2	ELECTRODE HOLDER	MBsBE2	5		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	—				
PROJECT	—				
TITLE	ELECTRODE TYPE LEVEL SWITCH SH-3-A-1-A-1-A-1 ASSEMBLY DRAWING				
MANUFACTURER	SeoJin Instech Co., Ltd.				
SCALE	N/S		ERP CODE	Work Order No.	REV.
DWG NO.	SJ-M009-DWG-AP004				

△					
△					
△					
△					
△	FOR APPROVAL				
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED