



WIRING DIAGRAM

DESIGN DATA

CODE	N/A		
UNIT	mm		
KIND OF FLUID	—		
PRESS.	DESIGN	Max. 2	Kg/Cm ²
	OPERATING	—	Kg/Cm ²
TEMP. (SENSOR)	DESIGN	−10 ~ 80	°C
	OPERATING	—	°C
TEMP. (ELECTRONICS)	DESIGN	−10 ~ 80	°C
	OPERATING	—	°C

ENCLOSURE	WEATHER PROOF
MOUNTING TYPE&SIZE	PF 2"

ELECTRODE MATERIAL	<input type="checkbox"/> 304SS <input type="checkbox"/> 316SS
--------------------	---

ELECTRODE TUBING MATERIAL	<input type="checkbox"/> PE <input type="checkbox"/> PTFE
---------------------------	---

TAG NO.	L1	L2	L3	L4	—

NOTES

REVISION

5	KEEPER	PVC	1		
4	ELECTRODE	304SS	4		
3	LOCK NUT	304SS	4		
2	ELECTRODE HOLDER	MBsBE2	5		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	—
----------	---

PROJECT	—
---------	---

TITLE	ELECTRODE TYPE LEVEL SWITCH SH-4-A-1-A-1-A-1 ASSEMBLY DRAWING
-------	---

MANUFACTURER	SeoJin Instech Co., Ltd.
--------------	---------------------------------

SCALE	N/S	ERP CODE	—	Work Order No.	—	REV.	
DWG NO.	SJ-M009-DWG-AP006						

	FOR APPROVAL				
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED