

진돗개 화재 및 가스 감지기류 (JINDOGAE FIRE & GAS DETECTORS)



Smoke Detector

Optical Smoke Detector
Conventional & Addressable Detector
Isolating function
Operating voltage: 17-28V DC
Quiescent current: 350uA
MED Approval from DNV
Intrinsically safe type also available



Gas Detector (BDS2000-GD)

Ex d IIC T4 certificate
Flammable, Oxygen, Toxic sensors
Output signal: RS485, 4-20mA
IP 65
SUS 316 sensor housing
16 x 2 DIGIT display



Heat Detector

Conventional & Addressable Detector
Isolating function
A1 Grade
Operating voltage: 17-28V DC
Quiescent current: 350uA
MED approval from DNV
Intrinsically safe type also available



Gas Detector (BDS2000-GDN)

Ex d IIC T4 certificate
Flammable, Oxygen, Toxic sensors
IP 65
SUS 316 sensor housing



Multi Detector

Optical Smoke & Heat detector
Conventional & Addressable detection
Isolating function
Operating voltage: 17-28V DC
Quiescent current: 550uA
Intrinsically safe: Ex ia IIC T4 grade



Gas Detector

Ex d IIC T4 certificate
ATEX approval J/B
Output Signal: RS485, 4-20mA
IP 65
Flammable, Oxygen and toxic sensors



Flame Detector

Analogue Addressable UV Flame Detector
Output Singal : RS485 / PLC / 4~20mA
Operating Voltage : DC24V
Detecting View : 90'
Working Distance : 40M (Certified Distance : 25M)
MED, LR, KFI Type Approval



Water Detector

Capacitance type
Sensing Distance : 15mm
Housing Material : SUS304/316
Power Supply Voltage : 10~30VDC
Top or Side Mounting
Ex ia IIB T6

Produced by ARIRANG Valley, KOREA

TEL: +82-2-706-3077