

# BT-400

## Phototherapy



- 20,000 hour operating time
- High intensity with efficient treatment
- Operating & total using time display
- Timer, 2 level adjustable intensity
- Light weight and compact size



# Technical Specification

## Light Source – Blue LEDs

Wavelength	• Peak between 450 ~ 475 nm
Intensity	• 20 ~ 100 $\mu W/cm^2/nm$ at 40 cm
Variation in intensity over 6 hours	• $\pm 10\%$ (within illumination area)
Effective surface area	• 40 x 20 cm

## Function

Intensity Control	• Low Intensity : 20 ~ 70 $\mu W/cm^2/nm \pm 10\%$ • High Intensity : 40 ~ 100 $\mu W/cm^2/nm \pm 10\%$
Timer	• 30 min. ~ 999 hours 30 min.
Heat output	• Over 6 hours < 10 °C warmer than ambient (at 40 cm)
LCD Display	• Operating Hour, Total Hour, Timer, Adjustable Intensity
Installation	• Mobile Cart, Pole Mounted, Incubator Top

## Electrical mains

Input	• 100 - 240 VAC, 50/60 Hz,
Consumption	• 70VA

## Safety

Leakage current	• < 100 $\mu A$
Audible Noise	• < 60 dB

## Dimension

Maximum height	• 200 cm
Main Unit	• 34 x 21 x 7.5 cm

## Weight

Main Unit	• 3.6 kg
Cart	• 8.4 kg

Regulatory Standards	• Type BF, EN60601-1, EN60601-1-2, EN60601-2-50
----------------------	---

Optional Accessory	• Cart, Shade
--------------------	---------------

Warranty	• 2 years
----------	-----------



## Installation

Allow a main unit to move vertically to provide a proper treatment

Treatment timer & adjustable intensity



Main Unit with Optional Cart

Main Unit



Main Unit with IV Pole

Cart (Option)



Main Unit with Infant Incubator (BT-500)

Manufacturer: Bistos Co., Ltd.

7th Fl., A Bldg., 144-3, Sangdaewon-dong, Jungwon-gu, Seongnam-si, Gyeonggi-do, Korea.

Tel : +82 31 750 0340 (ext. 103) Fax : +82 31 750 0344 E-mail : sales@bistos.co.kr

WWW.BISTOS.CO.KR