

튜브 벤더



누마벤드 ST

튜브

> Ø 3~10x1mm, 300N/mm² 또는 Ø 0.12~0.375x0.038", 43KSI



 NUMALLIANCE

와이어, 튜브,
스트립 포밍 머신
CNC 기술 혁신

튜브 벤더

튜브

누마벤드 ST

| | ST8C | ST8 | ST10 |
|-------|-------------------------------|------------------------------|------------------------------|
| 튜브 길이 | 230~2200mm 9~86.5" | 230~4000mm 9~157.5" | 230~4000mm 9~157.5" |
| 바닥 치수 | 7300 x 4000mm 287 x 157.5" | 10500 x 4800mm 413 x 189" | 10500 x 4800mm 413 x 189" |

주요 특징


- > 사전 절단 길이에서 3D 벤딩
- > 스몰 튜브 벤더
- > 브레이크 라인, A/C 라인, 연료 라인에 적합

제어

- > 산업용 PC 기반 소프트웨어
- > 19" 터치스크린 다국어 대화 및 프로그래밍 인터페이스
- > 외부 장치 제어를 위한 보조 기능 및 입력/출력 지원
- > 프로그램 시뮬레이션
- > 인터넷 연결: 원격 지원 및 채팅방
- > 3D 측정장치의 자동보정 피드백

중량

- > 구성에 따라 다름



Parc d'Activités - F 88470 SAINT MICHEL SUR MEURTHE
전화 : +33 (0)3 29 58 36 15 - 팩스 : +33 (0)3 29 58 46 47

이메일 : numalliance@numalliance.com

www.numalliance.com

FTECH-누마벤드ST-EN-18

www.dagdesign.com