

Description	Refrigerated/Heating Circulators DRCL8
Group	CHILLER
Keyword	Refrigerated/Heating Circulators
Detail	CPT Order No : 910005 Model : DRCL8 Filling volume : 8 liters Working temp. range : - 35.0 ~ +160.0 • Temperature setting to 0.1 • Temp. stability : ± 0.1 • Temp. controller : PID temperature control Heat cap. : 1000W Cooling capacity W (Bath fluid : Ethanol) 20 : 150W Pump capacity Flow rate : 9 l/min Pressure : 0.35 bar Pump In/Out : 10.9Ø Bath opening/Filling bath depth volume(W× D× H)(cm):17× 17.5× 15 Dimensions(W× D× H(cm)) : 33× 41× 79 Weight : 37.2 kg
	CPT INC. http://www.cpt.or.kr TEL: 82 - 31 - 457 - 1735 FAX: 82 - 31 - 454 - 8693 E - mail : cpt1287@nate.com

Refrigerated/Heating Circulators

DRCL8

- LED Temperature display with resolution 0.1
- Built in with automatic shut off overheat protection
- Safety apparatus for the electric leakage and excess

Application Area

- External temperature control applications to external circulation

*Measuring cells *Fomenters *Electrophoresis chambers *Polari meters * Chromatography columns

*Photometers *Rotary evaporators *Viscometers

- Pump In / Out : 10.9Ø
- Temp. controller : PID temperature control
- Cooling capacity test (Bath fluid : Ethanol)
- DRCL Model connections Application (Page: 5,6)

CPT Order No	CPT Model	Working Temp Range	Temp Stab	Heat Cap W	Cooling capacity W (Bath fluid: Ethanol)	Pump capacity Flow rate/Pressure l/min. bar		Bath opening bath depth W×D×H cm	Fill. vol. liters	Dimensions W*D*H cm	Weight kg
910005	DRCL8	-35.0~160.0	±0.1	1000	150	9	0.35	17*17.5*15	8	33*41*79	37.2

Dimensions: External features of size(mm)

