

Description	Refrigerated/Heating Circulators DRCL20
Group	CHILLER
Keyword	Refrigerated/Heating Circulators



Detail

CPT Order No : 910065

Model : DRCL20

Filling volume : 20 liters

Working temp. range : -35.0 ~+160.0

- Temperature setting to 0.1
- Temp. stability : ± 0.1
- Temp. controller : PID temperature control

Heat cap. : 1800W

Cooling capacity W (Bath fluid: Ethanol)20 : 460W

Pump capacity Flow rate : 9 l/min

Pressure : 0.35 bar

Pump In/Out : 10.9Ø

Bath opening/Filling bath depth volume(W×D×H)(cm):30×20.5×20

Dimensions(W×D×H)(cm) : 38.5×45.5×78

Weight : 48 kg



CPT INC. <http://www.cpt.or.kr>

TEL: 82 - 31 - 457 - 1735 FAX: 82 - 31 - 454 - 8693

E - mail : cpt1287@nate.com

Refrigerated/Heating Circulators

DRCL20

- LED Temperature display resolution 0.1
- Heater adjustable high temperature cut-off visible via
- Safety apparatus for the electric leakage and excess

Application

- External temperature control applications to external circulation

*Measuring cells *Fomenters *Electrophoresis chambers *Polari meters * Chromatography columns

*Photometers *Rotary evaporators *Viscometers

- Pump In / Out : 10.9Ø
- Temp. controller : PID temperature control
- Cooling capacity test (Bath fluid : Ethanol)
- DRC Model connections Application (Page: 5,6)

CPT Order No	CPT Model	Working Temp range	Temp Stab	Heat Cap W	Cooling capacity W (Bath fluid: Ethanol) 20	Pump capacity Flow rate/Press .Suct l/min. bar	Bath opening bath depth W×D×H cm	Fill. vol. liters	Dimensions W*L*H cm	Weight kg
910065	DRCL20	-35.0~160.0	±0.1	1800	460	9 0.35	30*20.5*20	20	38.5*45.5*78	48

Dimensions (mm)

