



- ▶ Displacement 250 cc/rev
- ▶ 9 piston design
- ▶ Suitable for use in open or closed loop circuits
- ▶ High global efficiency
- ▶ Dual direction of rotation
- ▶ Compact size
- ▶ High weight-power ratio
- ▶ Low noise level
- ▶ Long service life
- ▶ Option : speed sensor
- ▶ SAE-D or SAE-E mounting flange

Order code system :




Dimensions in mm [inches] :




Shafts available :

Splined shaft 2"
SAE J498b 15T 8/16DP
S1




Cylindrical keyed shaft Ø 2"
12.7x12.7x76.7
K1




► Inlet ports available :

Side flange
SAE J518 1 1/4" 6000 PSI
N0



Rear flange
SAE J518 1 1/4" 6000 PSI
M0



► Technical characteristics :

Motor	Displacement	Continuous max.speed	Intermittent max.speed	Max. flow absorbed	Theoretical torque	Theoretical torque at 350 bar [5100 psi]	Theoretical max. power at 400 bar [5800 psi]	Max. allowable pressure Continuous / peak	Weight*
	cc [cu.in]	rpm	rpm	l/mn [gpm]	N.m/bar [lbf.ft/psi]	N.m [lbf.ft]	kW [HP]	bar [psi]	Kg [lbs]
MA 250	250.2 [15.27]	2700	3000	675.5 [178.5]	4 [0.2]	1393.7 [1028]	405.3 [543.1]	400 / 450 [5800 / 6525]	69.5 [152.1]


*Weight with bottom flange.

► Acceptable forces applied to motor shaft :

Motor		250
Fr	N	22000
	lbf	4946
Fa	N/bar [N/psi]	150 [10.35]
	lbf/psi	2.33

F_r : radial force measured at mid point of length of shaft.


Fa : axial force.



For other forces, please contact us.

► Options on request :

Speed sensor.



For further information, please contact Customer Service.

Hervé COLIN - tel : +33(0)3 83 76 05 37 - hcolin@hydroleduc.com

Dimensions in mm [inches] are given only as an indication.



www.hydroeduc.com

HYDRO LEDUC SAS
Siège social & Usine
Head Office and Factory
BP 9
F-54122 AZERAILLES
FRANCE
Tel. +33 (0)3 83 76 77 40
Fax +33 (0)3 83 75 21 58

HYDRO LEDUC GmbH
Am Ziegelplatz 20
D-77746 SCHUTTERWALD
DEUTSCHLAND
Tel. +49 (0) 781-9482590
Fax + 49 (0) 781-9482592

HYDRO LEDUC AB
Betongvägen 11
461 38 TROLLHÄTTAN
SWEDEN
Tel. + 46 (0) 520 10 820

HYDRO LEDUC BV
Ericssonstraat 2
5121 ML Rijen
The Netherlands
Tel. +31 6 202 40 651

HYDRO LEDUC N.A. Inc.
Grand Parkway Industrial Park
23549 Clay Road
KATY, TX 77493
USA
Tel. +1 281 679 9654