

터치&현장용 데이터로거 | GTDL-600

This data logger is dynamic & static strain measurement equipment which can monitor result and record data without PC by built-in touch screen and SD memory card. This data logger can be measured for static without PC because of has built-in SD memory and touch screen. The data can be transmitted to PC easy through the front side USB port.



Feature

Static & dynamic Miti functions data logger for site.
 Easy moement and strong and waterproof case
 Remove noise by low pass filter.

Auto zero by auto zero button
 Selctable Tajimi or 5p Screw connector
 8 chs per slot type

Specification

Model	GTDL-600	GTDL-600-S (static)
Number of Channel	8, 16, 24, 32, 40, 48, 56 channel	
Display & data memory	7" TFT Touch LCD 16G SD Data Memory , USB Memory Stick Port (EXT)	
Measure Hz	1000Hz	Bridge exciting time : 50msec
Connector for sensor	5p Screw connector or TAJIMI	
Input Sensor	- 1Gage & 2Gage : 120Ω, 350Ω - 4Gage Bridge Sensor : 0.5 mV/V ~ 100mV/V - Potentionmeter Sensor - Pt100 RTD - Voltage : 10V	
Strain Input Range	10000, 100000, 1000000 X 10 ⁻⁶ strain	
Low Pass Filter	10Hz, 100Hz, 1Khz, Pass Program Selectable	
Interface	USB	
Program	Multiscan S/W & Multiload S/W	
Demension	500(W)*380(D)*190(H)mm	
Power	AC220V 50~60Hz or DC 12V	