



Beer Coolers

Insulation

Whole units including cabinet and door are filled with energy efficient high density polyurethane.



Back Bar Solid Type



Beer Dispenser



Back Bar Glass Type



▲Features

- Side mount compressor provides space-efficient front breathing system
- 4" diameter swivel casters with brakes for 1door unit. (option for other units)
- Incandescent interior lights for clear vision.
- PVC coated sturdy wire shelves are included
- Automatic evaporation system

▲Strong & Durable

- Heavy gauge stainless steel made tops are all equipped.
- stainless steel or galvanized interior for lasting utmost condition of the units.

▲Environmently Friendly

- All Back Bar units utilize R134a refrigerant which is CFC and HCFC -free.
- Free ozon depletion potential and zero global warming potential polyurethan isulation

▲Exterior Model Options

- Clean and simple looking stainless exterior and interior
- magnificent black vinyl laminated exterior and galvanized steel interior

Food Preservation

- Refrigerator holds 0°C ~ 4.4°C for optimum food preservation
- Indirect cooling system

Temperature Range

► Refrigerator

0°C ~ 4.4°C

32°F ~ 40°F

Beer Coolers

>> Refrigerator

*Heavy gauge stainless steel made tops are all equipped.
stainless steel or galvanized interior for lasting utmost condition of the units.*

Back Bar Solid Type		LBB-24-1B/1S	LBB-60-2B/2S	LBB-79-3B/3S	LBB-90-4B/4S	Back Bar Glass Type			
Beer Dispenser		LBD-24-1B/1S	LBD-60-2B/2S	LBD-79-3B/3S	LBD-90-4B/4S	LBB-24-1BG/1SG	LBB-60-2BG/2SG	LBB-79-2BG/2SG	LBB-90-3BG/3SG
Capacity	L	198	538	651	892	198	538	651	892
	Cu.fi	7	19	23	31.5	7	19	23	31.5
Exterior Dimension (Including 5" casters)	W	23 2/5	59	69	90 1/3	23 2/5	59	69	90 1/3
	D	29 1/2	27 1/9	27 1/9	27 1/9	29 1/2	27 1/9	27 1/9	27 1/9
	H	39 1/4	37	37	37	39 1/4	37	37	37
Exterior Dimension(mm) (Including 5" casters)	W	595	1500	1755	2295	595	1500	1755	2295
	D	749	688	688	688	749	688	688	688
	H	995	940	940	940	995	940	940	940
Net Weight	Kg	85	125	135	200	90	135		
	Lb	187	276	298	441	198	298	320	474
Control		Thermostat Control				Thermostat Control			
Rated Voltage		115V 60Hz /220V 50, 60Hz				115V 60Hz /220V 50, 60Hz			
Amps		3.3 / 2.0	6.3 / 2.2	6.3 / 3.3	6.3 / 3.3	3.3 / 2.0	6.3 / 2.2	6.3 / 3.3	6.3 / 3.3
Compressor(HP)		1/5	3/8	3/8	3/8	1/5	3/8	3/8	3/8
Number of Doors		1	2	2	3	1	2	2	3
Shelves		None				None			
Door Type		Solid Door				Glass Door			
Door Lock		YES				YES			
Lamp		LED LAMP				LED LAMP			
Refrigerant		R-134a				R-134a			
Temperature Range		0~4.4°C / 32 ~ 40°F				0~4.4°C / 32 ~ 40°F			



DAEYONG E&B Co., Ltd.

55 Sandan-ro 163 Gil, Danwon-gu Ansan-si, Gyeonggi-do, 425-851, South Korea

Tel. +82(0)31-364-8961 Fax. +82(0)31-491-1603 E-Mail. hn.huh@daeyeong.co.kr

www.daeyeong.co.kr

