

DASAN compact Aerial work platform series

DAP 110 | DAP 120 | DAP 140

DASAN Heavy Industries are always thinking about what we should do in providing our customers with much trust & confidence and in manufacturing the most advanced product carrying out optimal function & high performance.

Ultimate Product with DASAN philosophy - DASAN compact Aerial work platform series. Feel DASAN high-quality wide selection.





Outrigger operation levers

Convenient to carry out automatically horizontal & vertical control by using operating levers installed on both sides of the equipment. Valve can be safely protected by using separate cover and appearance is elegantly furnished in modern type.



Overthrow preventive system

Sensor perceives vehicle-overthrow without delay, Users promptly recognize it by buzzer-typed watch-light. Being secure by stoping its operation beyond safety range in case of overthrow-warning.





Winch

Raises heavy weight of 900kgf at high speed. it guarantees safe operation by the installation of wet-corrosion automatic brakes.



Automatic bucket Tilting system

Bucket can be manually bended to suit user's operation type, which makes it possible to do inner clean-up. it assures safe operation by being automatically tilted when up & down.



Remote control system

Remote control Device operated in safety function range :
Multi-operation, Safety operation by choosing manual/automatic function to prevent duplicate motion.




Outrigger

Double extention box makes it possible to maximize extention width, Safety operation on rough ground by using cross-axis widerange pedals carries out the strong support.



		DAP 110	DAP 120	DAP 140
Winch working capacity		900 kgf	900 kgf	900 kgf
Maximum working raidus		6.8 m	8.1 m	10.2 m
Maximum working height	Winch	8.4 m	10.8 m	12.4 m
	Bucket	10.1 m	12.3 m	14.2 m
Neutral flow		12 Q / min	12 Q / min	12 ℓ / min
Oil tank capacity		45 Q	33 Q	33 ℓ
Extension / folding Speed		3.4 m / 17 sec	5.55 m / 26 sec	7.4 m / 26 sec
Up / down Speed		-24 ° ~ 77 ° / 19 sec	-24 ° ~ 77 ° / 19 sec	-24 ° ~ 77 ° / 19 sec
Rotation angle		360-degree revolution	360-degree revolution	360-degree revolution
Rotation speed		2 rpm	2 rpm	2 rpm
Main winch	Wire rope	p 8 X 30 m, multistrand 19 X 7	φ 8 X 30 m, multistrand 19 X 7	p 8 X 30 m, multistrand 19 X 7
	Wire speed	14 m / min	14 m / min	14 m / min
Outrigger		Main: Horizontal Vertical Automatic Extension (2.8m)	Main: Horizontal Vertical Automatic Extension (3.4m)	
		Front (A): Vertical automatic Extension (1.8m)		
		Rear (A): Vertical automatic Extension (1.5m)		
Safety device		Safety valve (relief valve)		
		Overcenter valve for preventing dropping of boom		
		Double overcenter valve for preventing extract, entrance of booms		
		Winch automatic brake for preventing dropping of hook		
		Double pilot check valve for preventing extract, entrance of jack cylinder		
		Safety hook for preventing the breakaway from force		
		Fuse valve prepairing hose breakage		
		Upper & lower interlock / 3 color light (buzzar attached)		
		Preventive device from being overthrowned		
		Alarm & preventive device of being overwinded		
		Bucket shock prevention device		
Basic specification		2-stage main wide range outrigger (horizontal / vertical)		
		-	Rear (A)	Front (A), Rear (A)
		Remote control Remote control, Working light		
		OVM tool, Bucket auto horizontal Device		
Vehicles		Over 1 ton 'Bong-go'	Over 1.2 ton 'Bong-go'	
Options		Outrigger: Front (A), Rear (B)	Outrigger : Front (A)	
		Bucket Canopy, Bucket working light		
		Winch, Inverter		









www.dasancrane.co.kr

1 Factory

Head Office & 2 Factory

10-5, Oegacheon-ri, Wongok-myeon, Anseong-si, Gyeonggi-do, Korea

21, Oegacheon-ri, Wongok-myeon, Anseong-si, Gyeonggi-do, Korea

Tel: +82-31-618-0053 / Fax: +82-31-691-2441