



Rocker

- It mixes by moving inclined in left and right directions of 25 – 48 degrees.
- It can be used for various fields such as Gel washing, Mixing, Hybridization, Staining, De staining Agitating.
- Natural rubber is used to prevent the container sliding., afety device is attached such as automatic stop function in case of overload, etc.



DS - 303T		
Speed	Range	0 - 100 R.P.M
	controller	Solid state feed back controller
Motor		Unique b/1 plate motor
Angle		25 ° - 48° dia-circular adjustable type
Dimension		285 x 290 x 100 (WxDxH)mm, To tray
Tray size		305 x 290 (WxD)mm
Material(Body)		Steel plate (SCP-1)
Platform (Option)		Single plate(RT-A1) , Dual plate(RT-A2) (Option)
Power		AC220V, 60Hz, 0.1Kw

Hula Shaker

- It is a rotating mixer like as the plate twists
- Quiet, Vibration-free operation
- After mixing, solving, dilluting, electrophoresis of solution, it is used in gel staining, de staining, western blotting.
- Natural rubber is used to prevent the container sliding., afety device is attached such as automatic stop function in case of overload, etc.



DS - 303HL		
Speed	Range	0 - 36 R.P.M
	controller	Electronic controller
Motor		Mechanical geared motor
Pitch angle		Max 15 °
Dimension		305 x 295 x 220 (WxDxH)mm
Tray size		310 x 310 x 15(DxH)mm
Stroke		20 to 40mm, Adjustable
Material(Body)		Steel plate (SCP-1)
Power		AC220V, 60Hz, 0.1Kw