

# UV Sterilizer

자외선멸균기

- 초자류 멸균, 보관 및 실험기구 멸균, 보관등에 이용.
- 자외선로부터 사용자 안전을 위하여 16mm 이중 진공유리를 사용하고, Door open시 자동으로 자외선 램프 Off
- 사용 용도에 따라 자외선 살균 및 건열 멸균기로 사용가능하다
- Door interlock switch 부착 – Door open시 가열 정지로 히터 수명연장

## DS-88US



## DS-88UM



## DS-88UL



		DS - 88US	DS - 88UM	DS - 88UL
Type		Forced convection type		
Main controller		Microprocessor digital displayed Auto-tuning multi-functional P.I.D controller (Temp, Time)		
Temperature	Range	Ambient +5℃ to 120℃		
	Accuracy	±0.3℃ at 80℃		
UV sterilizer controller		Day and night UV sterilizer controller (24hr. 15min./step)		
UV sterilizer lamp		UVL 20W x 2sets		UVL 30W x 2sets
Timer		99min. 59sec. or 99hr. 59min. or 99days 23hours or continuous selectable		
Dimensions (WxDxH)mm	In	600 x 500 x 500	600 x 500 x 1000	800 x 650 x 1000
	Out	780 x 600 x 910	720 x 690 x 1390	960 x 790 x 1490
Capacity		150 L	300 L	520 L
Material (In/Out)		Stainless steel (SUS 304) / Steel plate with powder coating(SCP-1)		
Circulation		60W blower fan		
Insulation		Ceramic and glass wool board		
Shelves		SUS 2ea	SUS 3ea	SUS 4ea
Door (Packing/Key)		Magnetic packing silicon rubber / Lock system		
Window		Three fold tempered glass(5mm)		
Safety system		Over heat protector, Power breaker		
Power(AC220V, 60Hz)		1Kw	1.3Kw	1.5Kw