

# Glass Drying Oven

유리 건조기

- 유리기구 멸균, 보관 및 실험기구 멸균, 보관등에 이용.
- 자외선로부터 사용자 안전을 위하여 16mm 이중 진공유리를 사용하고, Door open시 자동으로 자외선 램프 Off
- 사용 용도에 따라 자외선 멸균 및 건열 멸균기로 사용가능.
- Door interlock switch 부착 – Door open시 가열 정지로 히터 수명연장

## DS-86GS



## DS-86GL



## DS-86GD



		DS - 86GS	DS - 86GM	DS - 86GL	DS - 86GD
Type		Forced convection type			
Main controller		Microprocessor digital displayed Auto-tuning multi-functional P.I.D controller (Temp, Time)			
Temperature	Range	Ambient to 100°C			
	Accuracy	±0.3°C at 70°C			
Timer		99min. 59sec. or 99hr. 59min. or 99days 23hours or continuous selectable			
Dimensions (WxDxH)mm	In	700 x 400 x 500	600 x 700 x 1000	1000 x 500 x 1500	1200 x 600 x 1500
	Out	970 x 500 x 760	760 x 890 x 1520	1300 x 600 x 1800	1500 x 700 x 1800
Capacity		140 L	420 L	750 L	1080 L
Material (In/Out)		Stainless steel (SUS 304) / Steel plate with powder coating(SCP-1)			
Circulation		60W blower fan			
Insulation		Ceramic and glass wool board			
Shelves		SUS 2ea	SUS 3ea	SUS 4ea	
Door		Removable tempered glass sliding doors	Magnetic packing door with tempered glass viewing window		Removable tempered glass sliding doors
Safety system		Over heat protector, Power breaker			
Power(AC220V, 60Hz)		1Kw	1.3Kw	2.5Kw	3Kw