



PA Series

Variable Area Flowmeter

- Field indicated Flow meter for use without power supply
- Designed to fit into small spaces for easy installation in general factory piping lines and panels
- Easily check the flow of fluid (bubble, color, etc.)

■ PA-83 Series General Specifications

| | |
|--------------------|------------------|
| Size | 1/4" |
| Process Connection | PT |
| Measuring Fluid | Water, Air |
| Accuracy | ±5.0 % F.S |
| Fluid Temperature | Max. 60 °C |
| Max. Pressure | Max. 6 kgf/cm².G |

MODEL CODE

| PA-83 | - | <input type="checkbox"/> | - | <input type="checkbox"/> | Specification |
|-------|---|--------------------------|---|--------------------------|--|
| | | W | | | Measured for Water |
| | | A | | | Measured for Air |
| | | | | 1 ~ 3 | Refer to Water Flow ranges Rear to Rear |
| | | | | 1 ~ 4 | Refer to Air Flow ranges Rear to Rear |

FLOW RANGES

| Model | Measure Range | Model | Measure Range |
|-----------|---------------|-----------|---------------|
| | Water (L/min) | | Air (NL/min) |
| PA-83-W-1 | 1 - 4 | PA-83-A-1 | 10 - 100 |
| PA-83-W-2 | 1 - 7 | PA-83-A-2 | 20 - 140 |
| PA-83-W-3 | 1 - 9 | PA-83-A-3 | 20 - 200 |
| | | PA-83-A-4 | 30 - 300 |

DIMENSIONS DRAWING

