


6 SNAP SWITCH



WIRING DIAGRAM

TOTAL Q'TY : - SETS

NO.	TAG NO.	FLUID(UPPER/LOWER)	OPER. PRESS. MAX.(Bar)	OPER. TEMP. MAX.(C)	SET POINT	C TO C (MEASURING RANGE)	CONNECTION 1"SW 3000# (SIDE-SIDE)	Q'TY
1	-	-	-	-	150	-	-	SETS

OR	OPENS ON RISING LEVEL
CR	CLOSES ON RISING LEVEL
OF	OPENS ON FALLING LEVEL
CF	CLOSES ON FALLING LEVEL
V	SWITCH ACTION

△					
△					
△					
△					
△					
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVE

DESIGN DATA

CODE	KEPIC MGE & ASME B31.1		
UNIT	mm		
ENCLOSURE	WEATHER PROOF		
ORDERING CODE	PROCESS TEMP.(CONTACT RATING)		SNAP SWITCH MAT'L
1	Max.120°C (10A 120V AC / 0.6A 125V DC)		P.C. PHENOL,304SS
2	Max.230°C (5A 250V AC / 0.5A 125V DC)		P.C. CERAMIC,304SS
3	Max.400°C (1A 250V AC / 1A 30V DC)		P.C. CERAMIC,304SS
4	Max.230°C (15A 250V AC / 1A 30V DC)		P.C. CERAMIC,304SS
5	Max.400°C (1A 115V AC / 3A 28V DC)		P.C. CERAMIC,304SS
	HERMETICAL SEAL TYPE		

NOTES

6. SPEC : SEOJIN STD.
7. TEST FOR WELDING : HYDRO TEST

7	GLOBE VALVE	-	1	NPT 1/2"	
6	SNAP SWITCH				
5	PROCESS CONNECTION	A105	2	1"SW 3000#	
4	CHAMBER ASS'Y	A105 AC2B WFB	1	4" Sch.40	
3	FLOAT	316LSS	1	ø90	
2	BASE	AC2B	1		
1	COVER	C.S	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-

TITLE
VERTICAL FLOAT TYPE LEVEL SWITCH
SMC-73B-1-A-1-A-1-A-1
ASSEMBLY DRAWING

MANUFACTURER
Seojin Instech Co., Ltd.

SCALE	1:1	REV	
DATE	SJ-MO15-DWG-AP711-A	REV	
N/S		REV	