


WIRING DIAGRAM



8 SNAP SWITCH

DESIGN DATA			
CODE	KEPIC MGE & ASME B31.1		
UNIT	mm		
ENCLOSURE	WEATHER PROOF		
ORDERING CODE	PROCESS TEMP.(CONTACT RATING)		SNAP SWITCH MAT'L
1	Max.120°C (10A 120V AC / 0.6A 125V DC)		PC, PHENOL,304SS
2	Max.230°C (5A 250V AC / 0.5A 125V DC)		PC, CERAMIC,304SS
3	Max.400°C (1A 250V AC / 1A 30V DC)		PC, CERAMIC,304SS
4	Max.230°C (15A 250V AC / 1A 30V DC)		PC, CERAMIC,304SS
5	Max.400°C (1A 115V AC / 3A 28V DC)		PC, CERAMIC,304SS
HERMETICAL SEAL TYPE			

NOTES

- REFER TO INSTALLATION MANUAL WHEN YOU SET IT UP
- CABLE SIZE : 14 AWG.
- DEAD BAND IS 15mm FIXEDLY
- HEAD ROOM OF 300mm MUST BE SECURED ABOVE THE HEAD FOR INSTALLATION / REMOVAL AND MAINTENANCE
- CABLE CONNECTION IN TERMINAL PART VIA CLAMPED RING TYPE
- PAINTING SPEC : SEOJIN STD.
- TEST FOR WELDING : HYDRO TEST
- CHAMBER ORDERING INFORMATION, SMC-73CH-B-1-B-1-A-1-E-1-A

TOTAL Q'Ty : - SETS

NO.	TAG NO.	FLUID(UPPER/LOWER)	OPER. PRESS. MAX.(Bar)	OPER. TEMP. MAX.(C)	RATING	SET POINT	C TO C (MEASURING RANGE)	CONNECTION (ANSI 150# 1" RF (SIDE-BOTTOM))	Q'Ty
1	-	-	-	-	150#	150	-	-	- SETS

OR	OPENS ON RISING LEVEL
CR	CLOSES ON RISING LEVEL
OF	OPENS ON FALLING LEVEL
CF	CLOSES ON FALLING LEVEL
V	SWITCH ACTION

△									
△									
△									
△									
△									
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED				

BILL OF MATERIAL									
CUSTOMER -									
PROJECT -									
TITLE VERTICAL FLOAT TYPE LEVEL SWITCH									
SMC-73F-1-A-1-A-1-A-1									
ASSEMBLY DRAWING									
MANUFACTURER									
Seojin Instech Co., Ltd.									
SCALE	UNIT	TYPE CODE	ITEM CODE	ITEM CODE	ITEM CODE	ITEM CODE	ITEM CODE	ITEM CODE	ITEM CODE
N/S	mm	SJ	MO15-DWG	AP211-A					