


6 SNAP SWITCH



WIRING DIAGRAM

TOTAL Q'TY : - SETS

NO.	TAG NO.	FLUID(UPPER/LOWER)	OPER. PRESS. MAX.(Bar)	OPER. TEMP. MAX.(C)	SET POINT	C TO C (MEASURING RANGE)	CONNECTION 1"SW 3000# (SIDE-BOTTOM)	Q'TY
1	-	-	-	-	150	-	-	SETS

OR	OPENS ON RISING LEVEL
CR	CLOSES ON RISING LEVEL
OF	OPENS ON FALLING LEVEL
CF	CLOSES ON FALLING LEVEL
V	SWITCH ACTION

△					
△					
△					
△					
△					
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVE

DESIGN DATA

CODE	KEPIC MGE & ASME B31.1		
UNIT	mm		
ENCLOSURE	WEATHER PROOF	IP65	
ORDERING CODE	PROCESS TEMP/CONTACT RATING)		SNAP SWITCH MAT'
1	Max.120°C (10A 120V AC / 0.6A 125V DC)		PC, PHENOL.304SS
2	Max.230°C (6A 250V AC / 0.5A 125V DC)		PC, CERAMIC.304SS
3	Max.400°C (1A 250V AC / 1A 30V DC)		PC, CERAMIC.304SS
4	Max.230°C (15A 250V AC / 1A 125V DC)		PC, CERAMIC.304SS
	HERMETICAL SEAL TYPE		

NOTES

- REFER TO INSTALLATION MANUAL
- WHEN YOU SET IT UP
- CABLE SIZE : 14 AWG.
- DEAD BAND IS 15mm FIXEDLY
- HEAD ROOM OF 300mm MUST BE SECURED ABOVE THE HEAD FOR INSTALLATION / REMOVAL AND MAINTENANCE
- CABLE CONNECTION IN TERMINAL PART VIA CLAMPED RING TYPE
- PAINTING SPEC : SEQUIN STD.
- TEST FOR WELDING : HYDRO+PT TEST
- CHAMBER ORDERING INFORMATION.
- SMC-75CH-A-1-A-1-A-1-C-1-A

BILL OF MATERIAL

NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK
6	SNAP SWITCH		1		
5	PROCESS CONNECTION	A105	2	1"SW 3000#	
4	CHAMBER ASS'Y	A105g, 1/2x2 WER	1	5" Sch.40	
3	FLOAT	316LSS	1	ø110	
2	BASE	AC2B	1		
1	COVER	C.S	1		

CUSTOMER	-
PROJECT	-

TITLE
SMC-75B-1-A-1-A-1-A-1
ASSEMBLY DRAWING

MANUFACTURER

Seojin Instech Co., Ltd.

SCALE	1:1	REV	
DATE	SJ-MO15-DWG-AP801-B	REV	