


5 SNAP SWITCH



WIRING DIAGRAM

DESIGN DATA

CODE	KEPIC MGE & ASME B31.1		
UNIT	mm	WEATHER PROOF	IP65
ENCLOSURE	PROCESS TEMP (CONTACT RATING)	SNAP SWITCH MAT'L	
ORDERING CODE	Max 400°C (1A 115V AC / 3A 28V DC)	PC, CERAMIC,304SS	
5	HERMETICAL SEAL TYPE	PC, CERAMIC,304SS	
6	Max.350°C (5A 250V AC / 0.5A 125V DC)	PC, CERAMIC,304SS	
7	Max.450°C (1A 250V AC / 1A 30V DC)	PC, CERAMIC,304SS	
8	Max.350°C (15A 250V AC / 1A 125V DC)	PC, CERAMIC,304SS	
9	Max.450°C (1A 115V AC / 3A 28V DC)	PC, CERAMIC,304SS	

NOTES

- REFER TO INSTALLATION MANUAL WHEN YOU SET IT UP
- CABLE SIZE : MAX.14 AWG.
- DEAD BAND IS 15mm FIXEDLY
- HEAD ROOM OF 300mm MUST BE SECURED ABOVE THE HEAD FOR INSTALLATION / REMOVAL AND MAINTENANCE
- CABLE CONNECTION IN TERMINAL PART VIA CLAMPED RING TYPE
- IF SET POINT EXCEED 300mm, PLEASE CONTACT SEOJIN.

TOTAL Q'TY : - SETS

NO.	TAG NO.	FLUID(UPPER/LOWER)	OPPR. PRESS. MAX.(Bar)	OPPR. TEMP. MAX.(°C)	RATING	SET POINT	Q'TY
1	-	-	-	-	150#	150	- SETS

OR	OPENS ON RISING LEVEL
CR	CLOSES ON RISING LEVEL
OF	OPENS ON FALLING LEVEL
CF	CLOSES ON FALLING LEVEL
V	SWITCH ACTION

REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED
△					
△					
△					
△					