



## STATIONARY CONCRETE PUMP

# ETP970 Crawler Type

### General Dimension

Overall length	5,210mm
Overall width	2,320mm
Overall height	2,590mm
Total weight	8,500kg

### Engine

Maker	DOOSAN
Model	PU086T, 6 cyl. in line
Power output	151kW at 2,200rpm
Torque	826 Nm at 1,400rpm
Displacement	8.071 lit
Bore x Stroke	111 x 139mm
Fuel consumption	254g/kW.h at 2,200rpm
Maker	DEUTZ
Model	BF04M1013EC
	4 cyl. in line
Power output	118kW at 2,300rpm
Torque	577Nm at 1,400rpm
Displacement	4.76 lit.
Bore x Stroke	108 x 130mm
Fuel consumption	215g/kW.h at 1,400rpm
Emission standard	TIER-1
Cooling system	Water cooled
Battery	24V

### Crawler

Motor max stroke vol.	39.8 cc/rev
Motor flow	60L/min
Motor output speed	26rpm
Motor torque	748.4 kgf.m
Traveling speed	50 m/min



### Hydraulic Pump

Main pump type	Rexroth A4VG125
Main pump capacity	No. 1 x 125cc/rev
Main pump pressure	350kg/cm <sup>2</sup>
Accumulator pump	Rexroth A10V28

### Concrete Drive

Max. Theoretical Concrete Output	
Rod side	90m <sup>3</sup> /hr at 71 bar
Piston side	60m <sup>3</sup> /hr at 106 bar
Drive cylinder	dia. 110 x L1,600mm
Concrete cylinder	dia. 200 x L1,600mm
Transfer	S-tube, S2015 (dia. 200mm-150mm)

### Pumable Reach

Theoretical Vertical Reach	
Rod side	114m
Piston side	194m
Theoretical Horizontal Reach	
Rod side	231m
Piston side	350m

### Service Refill Capacities

Fuel tank	250L
Hydraulic oil tank	400L
Change interval	500hours

### Features

Outrigger	No application
Aux support	No application
Axle	No application
Water pump	Optional
Water tank	No application
Hopper	EZ Clean Type, 600L
Hopper lubrication	Manual greasing port
Agitator motor	Single motor on hopper
Remote control	Optional, wire or wireless

\* Technical amendments are reserved. The specifications are subject to change with or without prior notice.

#### Head Office & Factory

332-3, Janggwan-Ri, Jincheon-Eub, Chungcheongbuk-Do, Korea  
Tel\_+82-43-530-3300 Fax\_+82-43-530-3429

#### Sales & Marketing Office

Room #1203, Woolim Lion's Valley 2, 680, Gasan-Dong, Geumcheon-Gu, Seoul, Korea  
Tel\_+82-2-801-0800 Fax\_+82-2-801-0899