


INSTALLATION DRAWING



WIRING DIAGRAM

DESIGN DATA

CODE	N/A
UNIT	mm
KIND OF FLUID	—
PRESS.	DESIGN — ATM kg/Cm OPERATING — kg/Cm
TEMP. (SENSOR)	DESIGN —20 ~ 85 °C OPERATING —
TEMP. (ELECTRONICS)	DESIGN —10 ~ 60 °C OPERATING —
MEASURING RANGE	Max 10 M
SPECIFIC GRAVITY	More than 0.6
MOISTURE	Max 95% RH
INPUT POWER	Max 10 M
OUTPUT	DIAL DISPLAY
ACCURACY	±20mm
MOUNTING SIZE	JIS 10K 80A FF (6t)
LOOP IMPEDANCE	450 Ω (20V DC)
CALIBRATION	ZERO & SPAN

NOTES

REVISION

6	FLOAT	304SS	1		
5	SPRING	304SS	1		
4	WIRE	316SS	1		
3	FLANGE	304SS	1		
2	CONVERTER	ABS	1		
1	BODY	ABS	1		

NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK
----	-------------	----------	-----	---------------	--------

BILL OF MATERIAL

CUSTOMER	—
PROJECT	—
TITLE	GEAR TYPE LIQUID LEVEL TRANSMITTER SGL-2-A-1-A-3-A ASSEMBLY DRAWING
MANUFACTURER	Seojin Instech Co., Ltd.
SCALE	1:1
DATE	0000
REV	—
REV	—