



| | | | | | | | | | |
|-----|--------------|------|----------|----------|----------|--|--|--|--|
| △ | | | | | | | | | |
| △ | | | | | | | | | |
| △ | | | | | | | | | |
| △ | | | | | | | | | |
| △ | FOR APPROVAL | | | | | | | | |
| REV | DESCRIPTION | DATE | DESIGNED | REVIEWED | APPROVED | | | | |

| DESIGN DATA | | | |
|---------------------|-----------|---------------------|-------|
| CODE | N/A | | |
| UNIT | mm | | |
| KIND OF FLUID | | - | |
| PRESS. | DESIGN | | kg/Cm |
| | OPERATING | ATM | kg/Cm |
| TEMP. (SENSOR) | DESIGN | -20 ~ 85 °C | |
| | OPERATING | - | |
| TEMP. (ELECTRONICS) | DESIGN | -10 ~ 60 °C | |
| | OPERATING | - | |
| MEASURING RANGE | | Max 10 M | |
| SPECIFIC GRAVITY | | More than 0.6 | |
| MOISTURE | | Max 95% RH | |
| INPUT POWER | | Max 10 M | |
| OUTPUT | | DIAL DISPLAY | |
| ACCURACY | | ±20mm | |
| MOUNTING SIZE | | JIS 10K 80A FF (6t) | |
| LOOP IMPEDANCE | | 450 Ω (20V DC) | |
| CALIBRATION | | ZERO & SPAN | |
| TAG NO. | L | L1 | L2 |
| | | | |
| | | | |

NOTES

REVISION

| | | | | | |
|----|-------------|----------|-----|---------------|--------|
| 7 | CONVERTER | ABS | 1 | | |
| 6 | FLOAT | 304SS | 1 | | |
| 5 | SPRING | 304SS | 1 | | |
| 4 | WIRE | 316SS | 1 | | |
| 3 | FLANGE | 304SS | 1 | | |
| 2 | SCALE | AL | 1 | | |
| 1 | BODY | ABS | 1 | | |
| NO | DESCRIPTION | MATERIAL | QTY | SPECIFICATION | REMARK |

BILL OF MATERIAL

| | | |
|--------------------|---------|---|
| CUSTOMER | | - |
| PROJECT | | - |
| TITLE | | GEAR TYPE LIQUID LEVEL TRANSMITTER SGL-3-A-1-A-3-A ASSEMBLY DRAWING |
| MANUFACTURER | | Seojin Instech Co., Ltd. |
| SCALE | DWG NO. | 0000 |
| N/S | REV | 1 |
| SUI-MO08-DWG-AP011 | | |