

WELDING POSITIONER - HPO series

FIRM STRUCTURE AND INCREASED DURABILITY TRUSTFUL POWER WELDING POSITIONER HPO-30

- IT CAN BE USED FOR VARIOUS WELDING PURPOSES AND ITS SENSITIVE HANDLING CAN INCREASE PRODUCTIVITY AND ALSO PREVENT MUSCULOSKELETAL DISORDERS OF WORKERS.
- IT HAS BEEN PRODUCED AFTER EXTENSIVE RESEARCH WITH ONSITE DATA AND CONSIDERING ITS CONVENIENCE ABOVE ALL.
- THERE ARE TWO TYPES AVAILABLE CHUCK TYPE AND TABLE TYPE RESPECTIVELY.




HPO-30
POSITIONER

Option ▶



- **TABLE TYPE**
IT CAN BE USED WITH ATTACHMENT OF SIMPLE JIG FOR VARIOUS KINDS OF WELDING.



- **CHUCK TYPE**
IT IS BOTH SAME PIPE & STRUCTURAL WORK ARE POSSIBLE.

1 SPECIFICATION

MODEL	HPO-10	HPO-20	HPO-30	HPO-50	HPO-100
LOAD CAPACITY	1 TON	2 TON	3 TON	5 TON	10 TON
TABLE DIAMETER	φ1000 mm	φ1100 mm	φ1200 mm	φ1400 mm	φ1800 mm
ROTATION SPEED	0.1~1 rpm	0.05~0.5 rpm	0.05~0.5 rpm	0.05~0.5 rpm	0.03~0.5 rpm
TILTING ANGLE	0~135°	0~135°	0~135°	0~135°	0~90°
TILTING SPEED	135°/30sec	135°/30sec	135°/45sec	135°/60sec	90°/60sec
POWER SOURCE	AC220/380V x 3φ (4 WIRES INCLUDING N PHASE)x60HZ				
CONTROL SYSTEM	MAIN ELEC' PANEL, PENDANT S/W, SPEED CONTROL S/W				
OPTION	CLAMPING CHUCK, WELDING TORCH HOLDER				