

Specification for CPEs

KPC-2500	200Mbps Data CPE (Desk-Top) & TD-Repeater
	<p>Chipset <input type="checkbox"/> DSS 9001</p> <p>Data Transfer Rate <input type="checkbox"/> Up to 200 Mbps through the powerline interface</p> <p>Interface <input type="checkbox"/> Ethernet 10/100 Base-T / RJ-45</p> <p>Management & Configuration <input type="checkbox"/> Remote management via standard SNMP <input type="checkbox"/> Auto-configuration by DHCP and TFTP <input type="checkbox"/> Configuration and upgrade files by TFTP</p> <p>Security <input type="checkbox"/> Compliant with RADIUS protocol <input type="checkbox"/> Supports VLAN /Q VLAN <input type="checkbox"/> DES/3DES Encryption</p> <p>Environmental Requirements <input type="checkbox"/> Operating Temperature: 0 ~ +40°C <input type="checkbox"/> Operating Humidity: 5% ~ 95%, non-condensing</p> <p>Power Requirements <input type="checkbox"/> Power consumption: 7W <input type="checkbox"/> Voltage: 90 ~ 265 VAC, 50/60Hz</p> <p>Standards (CE/FCC/MIC) <input type="checkbox"/> Electrical safety: EN60950-1 <input type="checkbox"/> EMC: EN55022 (Class B), EN61000-3-2, EN61000-3-3, EN55024</p> <p>Physical <input type="checkbox"/> Dimension: 150mm X 45mm X 118mm <input type="checkbox"/> Weight: Max 400 g</p>