


Specification for CPEs

KPC-2104C	200Mbps Data CPE (Desk-Top)	
	<p>Chipset</p> <ul style="list-style-type: none"> <input type="checkbox"/> DSS 9010 <p>Data Transfer Rate</p> <ul style="list-style-type: none"> <input type="checkbox"/> Up to 200 Mbps through the coaxial cable connector <p>Interface</p> <ul style="list-style-type: none"> <input type="checkbox"/> Ethernet 10/100 Base-T / RJ-45 <input type="checkbox"/> F-Type Connector <p>Management & Configuration</p> <ul style="list-style-type: none"> <input type="checkbox"/> Remote management via standard SNMP <input type="checkbox"/> Auto-configuration by DHCP and TFTP <input type="checkbox"/> Configuration and upgrade files by TFTP <p>Security</p> <ul style="list-style-type: none"> <input type="checkbox"/> Compliant with RADIUS protocol <input type="checkbox"/> Supports VLAN /OVLAN <input type="checkbox"/> DES/3DES Encryption 	<p>Environmental Requirements</p> <ul style="list-style-type: none"> <input type="checkbox"/> Operating Temperature: 0 ~ +40℃ <input type="checkbox"/> Operating Humidity: 5% ~ 95%, non-condensing <p>Power Requirements</p> <ul style="list-style-type: none"> <input type="checkbox"/> Power consumption: 7W <input type="checkbox"/> Voltage: 90 ~ 265 VAC, 50/60Hz <p>Standards (CE/ FCC/ MIC)</p> <ul style="list-style-type: none"> <input type="checkbox"/> Electrical safety: EN60950-1 <input type="checkbox"/> EMC: EN55022 (Class B), EN61000-3-2, EN61000-3-3, EN55024 <p>Physical</p> <ul style="list-style-type: none"> <input type="checkbox"/> Dimension: 150mm X 45mm X 118mm <input type="checkbox"/> Weight: Max 410 g