


HPS6524FO



HPS 6524FO

Symbol				
Electrical connection				
Nil	G	T	D	Z

How to Order

HPS 65 24 FO - AC220V

① ② ③ ④

① Orifice

65	Ø65
----	-----

② Port size

24	2 1/2
----	-------

③ Electrical connection

Nil	Console box (Standard)
G	Grommet coil
T	Terminal box
D	DIN coil + DIN connector
Z	DIN coil + DIN connector & lamp

④ Voltage

AC110V	AC110V 50Hz/60Hz
AC220V	AC220V 50Hz/60Hz
DC24V	DC24V
AC220V-50Hz	AC 220V 50Hz
AC240V-50Hz	AC 240V 50Hz
AC 24V-50Hz	AC 24V 50Hz

Specifications

Classification	Standard	Option	Classification	Standard	Option
Fluid	Air, Steam, Hot water		Voltage	AC100V 50/60Hz AC110V 60Hz AC200V 50/60Hz AC220V 60Hz DC24V	AC220V 50Hz AC240V 50Hz AC 24V 50Hz
Fluid temp.	0 ~ 180℃				
Ambient temp.	50℃ (Max.)				
Pressure range	0.5 ~ 7kgf/cm ² (0.05 ~0.7MPa)		Allowable voltage fluctuation	±10%(AC), ±5% (DC)	
Coil insulation	Class H		Power consumption	AC, DC : 14W	
Electrical connection	Lead wire G(PF)1/2	Grommet coil Terminal box DIN connector	Body material	Bronze	
End connection	JIS 10K FF		Seal material	PTFE + SUS 304 PISTON	
Orifice	Ø65		Weight	14.3kg	

※ Not available in explosive atmosphere.

Features

- Piston pilot type
- Normally open type
- Fire resistant structure, high durability
- High temperature type(MAX 180 °C)
- Large capacity

Applications

- Steam piping
- Heat exchanger
- Steam presser
- Industrial cleaner
- Sterilizer
- Ventilator

Dimensions

