

**KGCRANES**

# HOIST TECHNICAL GUIDE





## DB CRAB 04

---

DB Crab 08

DB Crab S Series 20



## WIRE HOIST 32

---

A Type 32

Wide-Flange Type 60

Special Type 64

Explosion Proof Type 72



## LS HOIST (only for LScrane) 94

---



## CHAIN HOIST 98

---

VLC Chain Hoist 104



## TURNING DEVICE 110

---



## TURN OVER HOIST 112

---




## KG new product Introduction 117

---



# HOIST Positioning Map



# DB Crab Series

**TECHNOLOGICAL  
INNOVATION  
of KG Cranes**


## DB Crab

More smaller and light with competitive price, suitable for high-lift and high-frequency facility




## DB Crab S Series

Easy to assemble and maintain using modular system, possible to have design flexibility and adaptability of the structure according to the space



DB Crab Series from KG Cranes can be applied to the various fields. DB Crab Series are called GREEN HOIST because it save resources and energy using KGP system.



## VLC Chain Hoist

Next generation chain hoist. Suitable for the work of high frequency, using high frequency and high capacity torque motor



## KGP (Power Regenerative Unit)



- By using KGP, you can save cost compare with existing damping resistance system
- Saving electric bill by reuse damping resistance power with KGP
- Best choice for the Lifting load equipments
- Space-saving, easy to install and use
- Continuous duty and reputation duty(%ED) are higher than existing damping resistance system, and also can be adjusted as necessary.
- **We can apply KGP to all kinds of products which produced by KG Cranes.**

# KGP KG Power regeneration system


## KGP Power Regenerative Unit



### Characteristic

#### Energy Conservation


- You can save energy and electric bill by reusing regenerative power which was wasted to resistor in past damping resistance system by installing our KGP.





**I You can save space by using KGP!**

– Save space compare with existing damping resistance system



**I You can save electric bill by using KGP!**

MOTOR Capacity (KW)	Reduction rate after using KGP(%)	electric saving capacity(KW)	Saving electric bill(USD)			Remark
			3,600 hour	4,800 hour	5,400 hour	
11	11	1,21	218	290	327	* 100%ED * Industrial electric bill 0,05USD per 1Kw/h
15	11	1,65	297	396	446	
18,5	13	2,405	433	577	649	
22	17	3,74	673	898	1,010	
30	21	6,3	1,134	1,512	1,701	
37	22	8,14	1,465	1,954	2,198	
45	21	9,45	1,701	2,268	2,552	
55	21	11,55	2,079	2,772	3,119	
75	23	17,25	3,105	4,140	4,658	
90	22	19,8	3,564	4,752	5,346	
110	22	24,2	4,356	5,808	6,534	
132	22	29,04	5,227	6,970	7,841	

# DB Crab



## Characteristic

---

- 40% Saving cost
- 40% More light, smaller
- Flexible design
- Suitable for high-lift and high-frequency facility
- Various speed and silence
- Easy to maintain with modular design
- Saving electric bill (up to 30%) by using KGP (option)






### TS Geared Motor

- BBS Design
- Easy Maintenance
- Compact System

### Inverter Motor

- Powerful
- Modular Design



### Gear Box & DC MG BRAKE

- Modular Design
- Variable Speed
- Variety Type of Brakes

### Inverter Panel

- VVVF Control
- Usage Memory Function

### Wheel Block

- 10 Kinds Modular Design
- Package Type

# DB Crab

1. 200 ton DB Crab


2. 245ton DAM Gate Crane

3. 400/150ton DB Crab

4. 120ton DB Transporter


5. 280ton Ladle DB Crab

6. 600ton Goliath DB Crab



# DB Crab

DB 500 (2.5~25ton)





MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R1600	R2000	R2400	R2800	R3200	R3600		10	15	20	30	40
db504	27	36	46	55	64	73	10×4	T0	T0	T0	T1	T1
db508	13,5	18,2	22,8	27,3	31,9	36,5	10×8	T0	T1	T1	T2	T2
db512	9,0	12,1	15,2	18,2	21,3	24,3	10×12	T1	T2	T2	T3	T4
db516	6,8	9,1	11,4	13,7	16,0	18,2	10×16	T1	T2	T2	T3	T4

MODEL	Capacity	FEM		Hoisting Speed m/min					Dimensions mm				
		ISO		C4	C5	C6	C7	D1	a	b	c	h	WB
db504	6,3	1Am	M4	3,0	4,4	6,0	8,8	12,0	1750	min26		780	1350
	5	2m	M5	3,7	5,6	7,6	11,1	15,2				780	
	4	3m	M6	4,7	6,9	9,5	13,9	18,9				780	
	3,2	4m	M7	5,8	8,7	11,8	17,4	23,7				780	
	2,5	5m	M8	7,5	11,1	15,2	22,2	30,3				780	
db508	12	1Am	M4	1,6	2,3	3,2	4,6	6,3	1850	min34	max, 1000	830	1400
	10	2m	M5	1,9	2,8	3,8	5,6	7,6				830	
	8	3m	M6	2,3	3,5	4,7	6,9	9,5				830	
	6,3	4m	M7	3,0	4,4	6,0	8,8	12,0				830	
	5	5m	M8	3,7	5,6	7,6	11,1	15,2				830	
db512	20	1Am	M4	0,9	1,4	1,9	2,8	3,8	1850	min34	max, 1000	950	1400
	16	2m	M5	1,2	1,7	2,4	3,5	4,7				950	
	12	3m	M6	1,6	2,3	3,2	4,6	6,3				950	
	10	4m	M7	1,9	2,8	3,8	5,6	7,6				950	
	8	5m	M8	2,3	3,5	4,7	6,9	9,5				950	
db516	25	1Am	M4	0,7	1,1	1,5	2,2	3,0	1950	min34	max, 1000	1000	1450
	20	2m	M5	0,9	1,4	1,9	2,8	3,8				1000	
	16	3m	M6	1,2	1,7	2,4	3,5	4,7				1000	
	12	4m	M7	1,6	2,3	3,2	4,6	6,3				1000	
	10	5m	M8	1,9	2,8	3,8	5,6	7,6				1000	

# DB Crab

DB 800 (4~40ton)




MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R1600	R2000	R2400	R2800	R3200	R3600		10	15	20	30	40
db804	27	36	45	54	64	73	12,5×4	T0	T1	T1	T2	T2
db808	13,4	18,1	22,6	27,2	31,8	36,6	12,5×8	T1	T2	T2	T3	T4
db812	8,9	12,0	15,1	18,1	21,2	24,2	12,5×12	T2	T2	T3	T4	T4
db816	6,7	9,0	11,3	13,6	15,9	18,2	12,5×16	T3	T3	T4	T4	T5

MODEL	Capacity	FEM		Hoisting Speed m/min					Dimensions				
		ISO	D1	D2	D3	D4	D5	a	b	c	h	WB	
db804	10	1Am	M4	7,6	11,1	15,2	18,7	27,8	1650	min26	max. 1100	850	1350
	8	2m	M5	9,5	13,9	18,9	23,4	34,7				800	
	6,3	3m	M6	12,0	17,6	24,0	29,7	44,1				850	
	5	4m	M7	15,2	22,2	30,3	37,4	55,6				850	
	4	5m	M8	18,9	27,8	37,9	46,7	69,4				850	
db808	20	1Am	M4	3,8	5,6	7,6	9,3	13,9	1800	min34	max. 1100	950	1400
	16	2m	M5	4,7	6,9	9,5	11,7	17,4				900	
	12	3m	M6	6,3	9,3	12,6	15,6	23,1				950	
	10	4m	M7	7,6	11,1	15,2	18,7	27,8				950	
	8	5m	M8	9,5	13,9	18,9	23,4	34,7				950	
db812	30	1Am	M4	2,5	3,7	5,1	6,2	9,3	2000	min34	max. 1100	1000	1500
	25	2m	M5	3,0	4,4	6,1	7,5	11,1				950	
	20	3m	M6	3,8	5,6	7,6	9,3	13,9				1000	
	16	4m	M7	4,7	6,9	9,5	11,7	17,4				1000	
	12	5m	M8	6,3	9,3	12,6	15,6	23,1				1000	
db816	40	1Am	M4	1,9	2,8	3,8	4,7	6,9	2100	min44	max. 1100	1050	1550
	32	2m	M5	2,4	3,5	4,7	5,8	8,7				1000	
	25	3m	M6	3,0	4,4	6,1	7,5	11,1				1050	
	20	4m	M7	3,8	5,6	7,6	9,3	13,9				1050	
	16	5m	M8	4,7	6,9	9,5	11,7	17,4				1050	



# DB Crab

DB 1000 (5~50ton)




MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R2000	R2400	R2800	R3200	R3600	R4000		10	15	20	30	40
db1004	36	45	54	64	73	82	14×4	T0	T1	T1	T2	T2
db1008	18,0	22,6	27,2	31,8	36,4	41,0	14×8	T1	T2	T2	T3	T4
db1012	12,0	15,1	18,1	21,2	24,3	27,3	14×12	T2	T3	T4	T4	T5
db1016	9,0	11,3	13,6	15,9	18,2	20,5	14×16	T2	T3	T4	T5	T6

MODEL	Capacity	FEM		Hoisting Speed m/min					Dimensions mm				
		ISO	D1	D2	D3	D4	D5	a	b	c	h	WB	
db1004	12	1Am	M4	6,3	9,3	12,6	15,6	23,1	2100	min34		1150	1750
	10	2m	M5	7,6	11,1	15,2	18,7	27,8				1100	
	8	3m	M6	9,5	13,9	18,9	23,4	34,7				1150	
	6,3	4m	M7	12,0	17,6	24,0	29,7	44,1				1150	
	5	5m	M8	15,2	22,2	30,3	37,4	55,6				1150	
db1008	25	1Am	M4	3,0	4,4	6,1	7,5	11,1	2300	min34	max, 1200	1350	1850
	20	2m	M5	3,8	5,6	7,6	9,3	13,9				1300	
	16	3m	M6	4,7	6,9	9,5	11,7	17,4				1350	
	12	4m	M7	6,3	9,3	12,6	15,6	23,1				1350	
	10	5m	M8	7,6	11,1	15,2	18,7	27,8				1400	
db1012	40	1Am	M4	1,9	2,8	3,8	4,7	6,9	2400	min44	max, 1200	1450	1900
	32	2m	M5	2,4	3,5	4,7	5,8	8,7				1400	
	25	3m	M6	3,0	4,4	6,1	7,5	11,1				1450	
	20	4m	M7	3,8	5,6	7,6	9,3	13,9				1450	
	16	5m	M8	4,7	6,9	9,5	11,7	17,4				1500	
db1016	50	1Am	M4	1,5	2,2	3,0	3,7	5,6	2500	min46	max, 1200	1550	1950
	40	2m	M5	1,9	2,8	3,8	4,7	6,9				1500	
	32	3m	M6	2,4	3,5	4,7	5,8	8,7				1550	
	25	4m	M7	3,0	4,4	6,1	7,5	11,1				1550	
	20	5m	M8	3,8	5,6	7,6	9,3	13,9				1600	



MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R2000	R2400	R2800	R3200	R3600	R4000		10	15	20	30	40
db1204	35	44	53	62	71	79	16×4	T1	T1	T2	T2	T3
db1208	17,3	21,9	26,3	30,8	35,3	39,7	16×8	T2	T2	T3	T4	T4
db1212	11,5	14,6	17,6	20,5	23,5	26,5	16×12	T2	T3	T4	T5	T6
db1216	8,6	10,9	13,2	15,4	17,6	19,9	16×16	T3	T4	T4	T5	T6

MODEL	Capacity	FEM		Hoisting Speed m/min					Dimensions				
		ISO	D1	D2	D3	D4	D5	a	b	c	h	WB	
db1204	16	1Am	M4	4,7	6,9	9,5	11,7	17,4	2300	min34	max. 1300	1250	1850
	12	2m	M5	6,3	9,3	12,6	15,6	23,1				1200	
	10	3m	M6	7,6	11,1	15,2	18,7	27,8				1250	
	8	4m	M7	9,5	13,9	18,9	23,4	34,7				1250	
	6,3	5m	M8	12,0	17,6	24,0	29,7	44,1				1250	
db1208	32	1Am	M4	2,4	3,5	4,7	5,8	8,7	2500	min44	max. 1300	1450	1950
	25	2m	M5	3,0	4,4	6,1	7,5	11,1				1400	
	20	3m	M6	3,8	5,6	7,6	9,3	13,9				1450	
	16	4m	M7	4,7	6,9	9,5	11,7	17,4				1450	
	12	5m	M8	6,3	9,3	12,6	15,6	23,1				1450	
db1212	50	1Am	M4	1,5	2,2	3,0	3,7	5,6	2700	min46	max. 1300	1700	2050
	40	2m	M5	1,9	2,8	3,8	4,7	6,9				1650	
	30	3m	M6	2,5	3,7	5,1	6,2	9,3				1700	
	25	4m	M7	3,0	4,4	6,1	7,5	11,1				1700	
	20	5m	M8	3,8	5,6	7,6	9,3	13,9				1700	
db1216	63	1Am	M4	1,2	1,8	2,4	3,0	4,4	2800	min46	max. 1300	1750	2100
	50	2m	M5	1,5	2,2	3,0	3,7	5,6				1700	
	40	3m	M6	1,9	2,8	3,8	4,7	6,9				1750	
	32	4m	M7	2,4	3,5	4,7	5,8	8,7				1750	
	25	5m	M8	3,0	4,4	6,1	7,5	11,1				1750	





MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R2400	R2800	R3200	R3600	R4000	R4500		10	15	20	30	40
db1604	43	52	61	70	79	90	18×4	T1	T2	T2	T3	T4
db1608	21,7	26,1	30,5	35,0	39,4	45,0	18×8	T2	T3	T4	T4	T5
db1612	14,4	17,4	20,4	23,3	26,3	30,0	18×12	T3	T4	T4	T5	T6
db1616	10,8	13,0	15,3	17,5	19,7	22,5	18×16	T3	T4	T5	T6	T7

MODEL	Capacity	FEM		Hoisting Speed m/min					Dimensions mm				
		ISO	D2	D3	D4	D5	D6	a	b	c	h	WB	
db1604	20	1Am	M4	5,6	7,6	9,3	13,9	18,9	2400	min34		1350	1950
	16	2m	M5	6,9	9,5	11,7	17,4	23,7				1300	
	12	3m	M6	9,3	12,6	15,6	23,1	31,6				1350	
	10	4m	M7	11,1	15,2	18,7	27,8	37,9				1400	
	8	5m	M8	13,9	18,9	23,4	34,7	47,3				1450	
db1608	40	1Am	M4	2,8	3,8	4,7	6,9	9,5	2700	min44	max, 1400	1550	2100
	32	2m	M5	3,5	4,7	5,8	8,7	11,8				1500	
	25	3m	M6	4,4	6,1	7,5	11,1	15,2				1550	
	20	4m	M7	5,6	7,6	9,3	13,9	18,9				1600	
	16	5m	M8	6,9	9,5	11,7	17,4	23,7				1650	
db1612	63	1Am	M4	1,8	2,4	3,0	4,4	6,0	2900	min46	max, 1400	1800	2200
	50	2m	M5	2,2	3,0	3,7	5,6	7,6				1750	
	40	3m	M6	2,8	3,8	4,7	6,9	9,5				1800	
	32	4m	M7	3,5	4,7	5,8	8,7	11,8				1850	
	25	5m	M8	4,4	6,1	7,5	11,1	15,2				1900	
db1616	80	1Am	M4	1,4	1,9	2,3	3,5	4,7	3100	min46	max, 1400	1850	2300
	63	2m	M5	1,8	2,4	3,0	4,4	6,0				1800	
	50	3m	M6	2,2	3,0	3,7	5,6	7,6				1850	
	40	4m	M7	2,8	3,8	4,7	6,9	9,5				1900	
	32	5m	M8	3,5	4,7	5,8	8,7	11,8				1950	




# DB Crab

DB 2000 (10~100ton)



MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R2400	R2800	R3200	R3600	R4000	R4500		10	15	20	30	40
db2004	44	53	62	71	80	91	20×4	T1	T2	T2	T3	T4
db2008	21,8	26,3	30,8	35,3	39,8	45,4	20×8	T2	T3	T4	T5	T6
db2012	14,5	17,5	20,5	23,5	26,5	30,3	20×12	T3	T4	T5	T6	T7
db2016	10,9	13,2	15,4	17,6	19,9	22,7	20×16	T4	T5	T6	T7	T8

MODEL	Capacity	FEM		Hoisting Speed m/min					Dimensions mm				
		ISO	D2	D3	D4	D5	D6	a	b	c	h	WB	
db2004	25	1Am	M4	4,4	6,1	7,5	11,1	15,2	2700	min34	max, 1500	1650	2200
	20	2m	M5	5,6	7,6	9,3	13,9	18,9				1600	
	16	3m	M6	6,9	9,5	11,7	17,4	23,7				1650	
	12	4m	M7	9,3	12,6	15,6	23,1	31,6				1700	
	10	5m	M8	11,1	15,2	18,7	27,8	37,9				1750	
db2008	50	1Am	M4	2,2	3,0	3,7	5,6	7,9	2900	min46	max, 1500	1850	2300
	40	2m	M5	2,8	3,8	4,7	6,9	9,5				1800	
	32	3m	M6	3,5	4,7	5,8	8,7	11,8				1850	
	25	4m	M7	4,4	6,1	7,5	11,1	15,2				1900	
	20	5m	M8	5,6	7,6	9,3	13,9	18,9				1950	
db2012	80	1Am	M4	1,4	1,9	2,3	3,5	4,7	3150	min46	max, 1500	1900	2350
	63	2m	M5	1,8	2,4	3,0	4,4	6,0				1850	
	50	3m	M6	2,2	3,0	3,7	5,6	7,6				1900	
	40	4m	M7	2,8	3,8	4,7	6,9	9,5				1950	
	32	5m	M8	3,5	4,7	5,8	8,7	11,8				2000	
db2016	100	1Am	M4	1,1	1,5	1,9	2,8	3,8	2900	min84	max, 1500	1950	2300
	80	2m	M5	1,4	1,9	2,3	3,5	4,7				1900	
	63	3m	M6	1,8	2,4	3,0	4,4	6,0				1950	
	50	4m	M7	2,2	3,0	3,7	5,6	7,6				2000	
	40	5m	M8	2,8	3,8	4,7	6,9	9,5				2050	





MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R2400	R2800	R3200	R3600	R4000	R4500		10	15	20	30	40
db2504	43	52	61	70	79	90	22,4×4	T2	T2	T3	T4	T4
db2508	21,5	25,9	30,4	34,9	39,3	44,9	22,4×8	T3	T4	T4	T5	T6
db2512	14,3	17,3	20,3	23,2	26,2	29,9	22,4×12	T4	T5	T5	T7	T7
db2516	10,7	13,0	15,2	17,4	19,7	22,5	22,4×16	T4	T5	T6	T7	T8

MODEL	Capacity	FEM		Hoisting Speed m/min					Dimensions mm				
		ISO	D2	D3	D4	D5	D6	a	b	c	h	WB	
db2504	32	1Am	M4	3,5	4,7	5,8	8,7	11,8	2800	min34		1550	2250
	25	2m	M5	4,4	6,1	7,5	11,1	1500					
	20	3m	M6	5,6	7,6	9,3	13,9	18,9				1550	
	16	4m	M7	6,9	9,5	11,7	17,4	23,7				1600	
	12	5m	M8	9,3	12,6	15,6	23,1	31,6				1650	
db2508	63	1Am	M4	1,8	2,4	3,0	4,4	6,0	3000	min46		1850	2400
	50	2m	M5	2,2	3,0	3,7	5,6	7,6				1800	
	40	3m	M6	2,8	3,8	4,7	6,9	9,5				1850	
	32	4m	M7	3,5	4,7	5,8	8,7	11,8				1900	
	25	5m	M8	4,4	6,1	7,5	11,1	15,2				1950	
db2512	100	1Am	M4	1,1	1,5	1,9	2,8	3,8	3000	min84	max, 1600	1950	2400
	80	2m	M5	1,4	1,9	2,3	3,5	4,7				1900	
	63	3m	M6	1,8	2,4	3,0	4,4	6,0				1950	
	50	4m	M7	2,2	3,0	3,7	5,6	7,6				2000	
	40	5m	M8	2,8	3,8	4,7	6,9	9,5				2050	
db2516	125	1Am	M4	0,9	1,2	1,5	2,2	3,0	3050	min84		2050	2400
	100	2m	M5	1,1	1,5	1,9	2,8	3,8				2000	
	80	3m	M6	1,4	1,9	2,3	3,5	4,7				2050	
	63	4m	M7	1,8	2,4	3,0	4,4	6,0				2100	
	50	5m	M8	2,2	3,0	3,7	5,6	7,6				2150	

# DB Crab

DB 3200 (20~200ton)




MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R2400	R2800	R3200	R3600	R4000	R4500		10	15	20	30	40
db3204	42	51	59	68	77	88	26×4	T2	T3	T4	T4	T5
db3208	20,9	25,3	29,7	34,1	38,5	44,0	26×8	T4	T4	T5	T6	T7
db3212	14,0	16,9	19,8	22,7	25,7	29,3	26×12	T4	T5	T6	T7	T8
db3216	10,5	12,7	14,9	17,1	19,3	22,0	26×16	T5	T6	T7	T8	T9

MODEL	Capacity	FEM		Hoisting Speed m/min					Dimensions				
		ISO	D3	D4	D5	D6	D7	a	b	c	h	WB	
db3204	50	1Bm	M3	3,0	3,7	5,6	7,6	9,1	2760	min44	max, 1700	1800	2360
	40	1Am	M4	3,8	4,7	6,9	9,5	11,4				1750	
	32	2m	M5	4,7	5,8	8,7	11,8	14,2				1700	
	25	3m	M6	6,1	7,5	11,1	15,2	18,2				1280	
	20	4m	M7	7,6	9,3	13,9	18,9	22,7				1280	
db3208	100	1Bm	M3	1,5	1,9	2,8	3,8	4,5	3100	min46	max, 1700	2000	2450
	80	1Am	M4	1,9	2,3	3,5	4,7	5,7				1950	
	63	2m	M5	2,4	3,0	4,4	6,0	7,2				1900	
	50	3m	M6	3,0	3,7	5,6	7,6	9,1				1950	
	40	4m	M7	3,8	4,7	6,9	9,5	11,4				2000	
db3212	160	1Bm	M3	0,9	1,2	1,7	2,4	2,8	3100	min84	max, 1700	2200	2450
	125	1Am	M4	1,2	1,5	2,2	3,0	3,6				2150	
	100	2m	M5	1,5	1,9	2,8	3,8	4,5				2100	
	80	3m	M6	1,9	2,3	3,5	4,7	5,7				2150	
	63	4m	M7	2,4	3,0	4,4	6,0	7,2				2200	
db3216	200	1Bm	M3	0,8	0,9	1,4	1,9	2,3	2950	min84	max, 1700	2350	2400
	160	1Am	M4	0,9	1,2	1,7	2,4	2,8				2300	
	125	2m	M5	1,2	1,5	2,2	3,0	3,6				2250	
	100	3m	M6	1,5	1,9	2,8	3,8	4,5				2300	
	80	4m	M7	1,9	2,3	3,5	4,7	5,7				2350	

# DB Crab

DB 5000 (32~320ton)





MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R2800	R3200	R3600	R4000	R4500	R5000		10	15	20	30	40
db5004	51	60	69	77	89	100	32×4	T3	T4	T4	T5	T6
db5008	25,4	29,8	34,3	38,7	44,3	49,9	32×8	T4	T5	T6	T7	T8
db5012	16,9	19,9	22,9	25,8	29,5	33,3	32×12	T5	T7	T7	T9	T9
db5016	12,7	14,9	17,1	19,4	22,2	24,9	32×16	T6	T7	T8	T9	T10

MODEL	Capacity	FEM		Hoisting Speed m/min					Dimensions mm				
		ISO		D4	D5	D6	D7	D8	a	b	c	h	WB
db5004	80	1Bm	M3	2,3	3,5	4,7	5,7	6,9	3650	min46	max, 1800	1750	3000
	63	1Am	M4	3,0	4,4	6,0	7,2	8,8				1700	
	50	2m	M5	3,7	5,6	7,6	9,1	11,1				1650	
	40	3m	M6	4,7	6,9	9,5	11,4	13,9				1700	
	32	4m	M7	5,8	8,7	11,8	14,2	17,4				1750	
db5008	160	1Bm	M3	1,2	1,7	2,4	2,8	3,5	3650	min84	max, 1800	2300	3000
	125	1Am	M4	1,5	2,2	3,0	3,6	4,4				2250	
	100	2m	M5	1,9	2,8	3,8	4,5	5,6				2200	
	80	3m	M6	2,3	3,5	4,7	5,7	6,9				2250	
	63	4m	M7	3,0	4,4	6,0	7,2	8,8				2300	
db5012	250	1Bm	M3	0,7	1,1	1,5	1,8	2,2	3250	min84	max, 1800	2500	2650
	200	1Am	M4	0,9	1,4	1,9	2,3	2,8				2450	
	160	2m	M5	1,2	1,7	2,4	2,8	3,5				2400	
	125	3m	M6	1,5	2,2	3,0	3,6	4,4				2450	
	100	4m	M7	1,9	2,8	3,8	4,5	5,6				2500	
db5016	320	1Bm	M3	0,6	1,1	1,2	1,4	1,7	3300	min84	max, 1800	2700	2700
	250	1Am	M4	1,7	1,1	1,5	1,8	2,2				2650	
	200	2m	M5	0,9	1,4	1,9	2,3	2,8				2600	
	160	3m	M6	1,2	1,7	2,4	2,8	3,5				2650	
	125	4m	M7	1,5	2,2	3,0	3,6	4,4				2700	

# DB Crab

DB 6300 (40~400ton)



MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R2800	R3200	R3600	R4000	R4500	R5000		10	15	20	30	40
db6304	50	59	68	76	87	99	35,5×4	T3	T4	T5	T6	T7
db6308	24,9	29,4	33,8	38,2	43,7	49,3	35,5×8	T5	T6	T7	T8	T9
db6312	16,6	19,6	22,5	25,5	29,2	32,8	35,5×12	T6	T7	T8	T9	T10
db6316	12,5	14,7	16,9	19,1	21,9	24,6	35,5×16	T7	T8	T9	T10	T11

MODEL	Capacity	FEM		Hoisting Speed m/min					Dimensions				
		ISO	D4	D5	D6	D7	D8	a	b	c	h	WB	
db6304	100	1Bm	M3	1,9	2,8	3,8	4,5	5,6	4000	min46	max. 1900	1950	3300
	80	1Am	M4	2,3	3,5	4,7	5,7	6,9				1900	
	63	2m	M5	3,0	4,4	6,0	7,2	8,8				1850	
	50	3m	M6	3,7	5,6	7,6	9,1	11,1				1900	
	40	4m	M7	4,7	6,9	9,5	11,4	13,9				1950	
db6308	200	1Bm	M3	0,9	1,4	1,9	2,3	2,8	3400	min84	max. 1900	2600	2850
	160	1Am	M4	1,2	1,7	2,4	2,8	3,5				2550	
	125	2m	M5	1,5	2,2	3,0	3,6	4,4				2500	
	100	3m	M6	1,9	2,8	3,8	4,5	5,6				2550	
	80	4m	M7	2,3	3,5	4,7	5,7	6,9				2600	
db6312	300	1Bm	M3	0,6	0,9	1,3	1,5	1,9	3600	min84	max. 1900	2800	3000
	250	1Am	M4	0,7	1,1	1,5	1,8	2,2				2750	
	200	2m	M5	0,9	1,4	1,9	2,3	2,8				2700	
	150	3m	M6	1,2	1,9	2,5	3,0	3,7				2750	
	125	4m	M7	1,5	2,2	3,0	3,6	4,4				2800	
db6316	400	1Bm	M3	0,5	0,7	0,9	1,1	1,4	3800	min84	max. 1900	3000	3150
	320	1Am	M4	0,6	0,9	1,2	1,4	1,7				2950	
	250	2m	M5	0,7	1,1	1,5	1,8	2,2				2900	
	200	3m	M6	0,9	1,4	1,9	2,3	2,8				2950	
	160	4m	M7	1,2	1,7	2,4	2,8	3,5				3000	

# DB Crab S Series

DB Crab S Series is a new generation special type of DB Crab from KG Cranes. It is more light and easy to maintain by using progressive technique of modular system.

Competitive Price


Compact Size

Modular Design

Flange type Drive Unit

Powerful

More Safe




## Characteristic

- Competitive price more than 20%
- Easy to assemble and maintain by using progressive technique of modular system
- Design flexibility and adaptability of the structure according to the space
- More compact and light by using flange type drive unit
- More safe by using drum brake
- All the hoists are fitted with a load cell
- Up to 600tons capacity
- Saving electric bill (up to 30%) by using KGP (option)



## Variety





Regular Type




Square Type



Competitive Price  
Light weight  
Modular design



DRUM



UPPER SHEAVE BLOCK



HOIST DRIVE



GEARED MOTOR




LOAD BLOCK

# MODULE

Compact design,  
On time delivery,  
Easy to assemble and maintain

# DB Crab s Series

S 500 (2.5~25ton)





MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R1600	R2000	R2400	R2800	R3200	R3600		10	15	20	30	40
S504	27	36	46	55	64	73	10×4	P07	P07	P07	P07	P07
S508	13,5	18,2	22,8	27,3	31,9	36,5	10×8	P07	P07	P07	P07	P07
S512	9	12,1	15,2	18,2	21,3	24,3	10×12	P07	P07	P07	P10	P15
S516	6,8	9,1	11,4	13,7	16,0	18,2	10×16	P07	P07	P07	P15	P15


MODEL	Capacity	FEM / ISO	Hoisting Speed m/min					Dimensions						
			S37	S55	H09	H11	H15	a	b	c		h	WB	
S504	6,3	1Am / M4	3,0	4,4	6,0	8,8	12,0	max 1000	min 26	1200	1350	780	900	
	5	2m / M5	3,7	5,6	7,6	11,1	780							
	4	3m / M6	4,7	6,9	9,5	13,9	780							
	3,2	4m / M7	5,8	8,7	11,8	17,4	23,7					780		
	2,5	5m / M8	7,5	11,1	15,2	22,2	30,3					780		
S508	12	1Am / M4	1,6	2,3	3,2	4,6	6,3		max 1000	min 34	1250	1350	830	950
	10	2m / M5	1,9	2,8	3,8	5,6	7,6						830	
	8	3m / M6	2,3	3,5	4,7	6,9	9,5						830	
	6,3	4m / M7	3,0	4,4	6,0	8,8	12,0						830	
	5	5m / M8	3,7	5,6	7,6	11,1	15,2						830	
S512	20	1Am / M4	0,9	1,4	1,9	2,8	3,8	max 1000		min 34	1300	1350	950	1000
	16	2m / M5	1,2	1,7	2,4	3,5	4,7						950	
	12	3m / M6	1,6	2,3	3,2	4,6	6,3						950	
	10	4m / M7	1,9	2,8	3,8	5,6	7,6						950	
	8	5m / M8	2,3	3,5	4,7	6,9	9,5						950	
S516	25	1Am / M4	0,7	1,1	1,5	2,2	3,0		max 1000	min 34	1350	1350	1000	1050
	20	2m / M5	0,9	1,4	1,9	2,8	3,8						1000	
	16	3m / M6	1,2	1,7	2,4	3,5	4,7						1000	
	12	4m / M7	1,6	2,3	3,2	4,6	6,3						1000	
	10	5m / M8	1,9	2,8	3,8	5,6	7,6						1000	

# DB Crab s Series

S 800 (4~40ton)



(R) Type




(S) Type

MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R1600	R2000	R2400	R2800	R3200	R3600		10	15	20	30	40
S804	27	36	45	54	64	73	12,5×4	P07	P07	P07	P07	P07
S808	13,4	18,1	22,6	27,2	31,8	36,6	12,5×8	P07	P07	P07	P10	P15
S812	8,9	12,0	15,1	18,1	21,2	24,2	12,5×12	P07	P07	P10	P15	P22
S816	6,7	9,0	11,3	13,6	15,9	18,2	12,5×16	P07	P10	P15	P22	P37

MODEL	Capacity	FEM / ISO	Hoisting Speed m/min					Dimensions							
			H11	H30	H37	H45	H55	a	b	c		h	WB		
			(R)	(S)											
S804	10	1Am / M4	7,6	11,1	15,2	18,7	27,8	max 1100	min 26	1250	1500	850	900		
	8	2m / M5	9,5	13,9	18,9	23,4	34,7					800			
	6,3	3m / M6	12,0	17,6	24,0	30,3	44,1					850			
	5	4m / M7	15,2	22,2	30,3	37,4	55,6					850			
	4	5m / M8	18,9	27,8	37,9	46,7	69,4					850			
S808	20	1Am / M4	3,8	5,6	7,6	9,3	13,9		max 1100	min 34	1300	1500	950	950	
	16	2m / M5	4,7	6,9	9,5	11,7	17,4						900		
	12	3m / M6	6,3	9,3	12,6	15,6	23,1						950		
	10	4m / M7	7,6	11,1	15,2	18,7	27,8						950		
	8	5m / M8	9,5	13,9	18,9	23,4	34,7						950		
S812	30	1Am / M4	2,5	3,7	5,1	6,2	9,3			max 1100	min 34	1350	1500	1000	1000
	25	2m / M5	3,0	4,4	6,1	7,5	11,1							950	
	20	3m / M6	3,8	5,6	7,6	9,3	13,9							1000	
	16	4m / M7	4,7	6,9	9,5	11,7	17,4							1000	
	12	5m / M8	6,3	9,3	12,6	15,6	23,1							1000	
S816	40	1Am / M4	1,9	2,8	3,8	4,7	6,9	max 1100			min 44	1400	1500	1050	1050
	32	2m / M5	2,4	3,5	4,7	5,8	8,7							1000	
	25	3m / M6	3,0	4,4	6,1	7,5	11,1							1050	
	20	4m / M7	3,8	5,6	7,6	9,3	13,9							1050	
	16	5m / M8	4,7	6,9	9,5	11,7	17,4							1050	

# DB Crab s Series

S 1000 (5~50ton)





MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R2000	R2400	R2800	R3200	R3600	R4000		10	15	20	30	40
S1004	36	45	54	64	73	82	14×4	P07	P07	P07	P07	P07
S1008	18	22,6	27,2	31,8	36,4	41,0	14×8	P07	P07	P07	P15	P15
S1012	12,0	15,1	18,1	21,2	24,3	27,3	14×12	P07	P10	P15	P22	P37
S1016	9,0	11,3	13,6	15,9	18,2	20,5	14×16	P07	P15	P15	P22	P37


MODEL	Capacity	FEM / ISO	Hoisting Speed m/min					Dimensions							
			H15	H22	H30	H37	H55	a	b	c		h	WB		
			(R)	(S)											
S1004	12	1Am / M4	6,3	9,3	12,6	15,6	23,1	max 1200	min 34	1300	1550	1150	950		
	10	2m / M5	7,6	11,1	15,2	18,7	27,3					1100			
	8	3m / M6	9,5	13,9	18,9	23,4	34,7					1150			
	6,3	4m / M7	12,0	17,6	24,0	29,7	44,1					1150			
	5	5m / M8	15,2	22,2	30,3	37,4	55,6					1150			
S1008	25	1Am / M4	3,0	4,4	6,1	7,5	11,1		max 1200	min 34	1350	1550	1350	1000	
	20	2m / M5	3,8	5,6	7,6	9,3	13,9						1300		
	16	3m / M6	4,7	6,9	9,5	11,7	17,4						1350		
	12	4m / M7	6,3	9,3	12,6	15,6	23,1						1350		
	10	5m / M8	7,6	11,1	15,2	18,7	27,8						1400		
S1012	40	1Am / M4	1,9	2,8	3,8	4,7	6,9			max 1200	min 44	1400	1550	1450	1050
	32	2m / M5	2,4	3,5	4,7	5,8	8,7							1400	
	25	3m / M6	3,0	4,4	6,1	7,5	11,1	1450							
	20	4m / M7	3,8	5,6	7,6	9,3	13,9	1450							
	16	5m / M8	4,7	6,9	9,5	11,7	17,4	1500							
S1016	50	1Am / M4	1,5	2,2	3,0	3,7	5,6	max 1200			min 46	1450	1550	1550	1100
	40	2m / M5	1,9	2,8	3,8	4,7	6,9							1500	
	32	3m / M6	2,4	3,5	4,7	5,8	8,7		1550						
	25	4m / M7	3,0	4,4	6,1	7,5	11,1		1550						
	20	5m / M8	3,8	5,6	7,6	9,3	13,9		1600						

# DB Crab s Series

S 1200 (6.3~63ton)



(R) Type




(S) Type

MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R2000	R2400	R2800	R3200	R3600	R4000		10	15	20	30	40
S1204	35	44	53	62	71	79	16×4	P07	P07	P07	P07	P07
S1208	17,3	21,9	26,3	30,8	35,3	39,7	16×8	P07	P07	P10	P15	P22
S1212	11,5	14,6	17,6	20,5	23,5	26,5	16×12	P07	P15	P15	P22	P37
S1216	8,6	10,9	13,2	15,4	17,6	19,9	16×16	P10	P15	P22	P37	P37

MODEL	Capacity	FEM / ISO	Hoisting Speed m/min					Dimensions					
			H15	H22	H30	H37	H55	a	b	c		h	WB
				(R)	(S)								
S1204	16	1Am / M4	4,7	6,9	9,5	11,7	17,4	max 1300	min 34	1300	1650	1250	900
	12	2m / M5	6,3	9,3	12,6	15,6	23,1					1200	
	10	3m / M6	7,6	11,1	15,2	18,7	27,8					1250	
	8	4m / M7	9,5	13,9	18,9	23,4	34,7					1250	
	6,3	5m / M8	12,0	17,6	24,0	29,7	44,1					1250	
S1208	32	1Am / M4	2,4	3,5	4,7	5,8	8,7		min 44	1400	1650	1450	1000
	25	2m / M5	3,0	4,4	6,1	7,5	11,1					1400	
	20	3m / M6	3,8	5,6	7,6	9,3	13,9					1450	
	16	4m / M7	4,7	6,9	9,5	11,7	17,4					1450	
	12	5m / M8	6,3	9,3	12,6	15,6	23,1					1450	
S1212	50	1Am / M4	1,5	2,2	3,0	3,7	5,6		min 46	1500	1650	1700	1100
	40	2m / M5	1,9	2,8	3,8	4,7	6,9					1650	
	30	3m / M6	2,5	3,7	5,1	6,2	9,3					1700	
	25	4m / M7	3,0	4,4	6,1	7,5	11,1					1700	
	20	5m / M8	3,8	5,6	7,6	9,3	13,9					1700	
S1216	63	1Am / M4	1,2	1,8	2,4	3,0	4,4	min 46	1600	1650	1750	1200	
	50	2m / M5	1,5	2,2	3,0	3,7	5,6				1700		
	40	3m / M6	1,9	2,8	3,8	4,7	6,9				1750		
	32	4m / M7	2,4	3,5	4,7	5,8	8,7				1750		
	25	5m / M8	3,0	4,4	6,1	7,5	11,1				1750		

# DB Crab s Series

S 1600 (8~80ton)



(R) Type

(S) Type



MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R2400	R2800	R3200	R3600	R4000	R4500		10	15	20	30	40
S1604	43	52	61	70	79	90	18×4	P07	P07	P07	P10	P15
S1608	21,7	26,1	30,5	35,0	39,4	45,0	18×8	P07	P10	P15	P22	P37
S1612	14,4	17,4	20,4	23,3	26,3	30,0	18×12	P10	P15	P22	P37	P37
S1616	10,8	13,0	15,3	17,5	19,7	22,5	18×16	P15	P22	P37	P37	T55

MODEL	Capacity	FEM / ISO	Hoisting Speed m/min					Dimensions					
			H22	H30	H37	H55	H75	a	b	c		h	WB
			(R)	(S)									
S1604	20	1Am / M4	5,6	7,6	9,3	13,9	18,6	max 1400	min 34	1350	1750	1350	1200
	16	2m / M5	6,9	9,5	11,7	17,4	23,7					1300	
	12	3m / M6	9,3	12,6	15,6	23,1	31,6					1350	
	10	4m / M7	11,1	15,2	18,7	27,8	37,9					1400	
	8	5m / M8	13,9	18,9	23,4	34,7	47,3					1450	
S1608	40	1Am / M4	2,8	3,8	4,7	6,9	9,5		min 44	1450	1750	1550	1250
	32	2m / M5	3,5	4,7	5,8	8,7	11,8					1500	
	25	3m / M6	4,4	6,1	7,5	11,1	15,1					1550	
	20	4m / M7	5,6	7,6	9,3	13,9	18,9					1600	
	16	5m / M8	6,9	9,5	11,7	17,4	23,7					1650	
S1612	63	1Am / M4	1,8	2,4	3,0	4,4	6,0		min 46	1550	1750	1800	1250
	50	2m / M5	2,2	3,0	3,7	5,6	7,6					1750	
	40	3m / M6	2,8	3,8	4,7	6,9	9,5					1800	
	32	4m / M7	3,5	4,7	5,8	8,7	11,8					1850	
	25	5m / M8	4,4	6,1	7,5	11,1	15,2					1900	
S1616	80	1Am / M4	1,4	1,9	2,3	3,5	4,7	min 46	1650	1750	1850	1350	
	63	2m / M5	1,8	2,4	3,0	4,4	6,0				1800		
	50	3m / M6	2,2	3,0	3,7	5,6	7,6				1850		
	40	4m / M7	2,8	3,8	4,7	6,9	9,5				1900		
	32	5m / M8	3,5	4,7	5,8	8,7	11,8				1950		




# DB Crab s Series

S 2000 (10~100ton)



(R) Type




(S) Type

MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R2400	R2800	R3200	R3600	R4000	R4500		10	15	20	30	40
S2004	44	53	62	71	80	91	20×4	P07	P07	P07	P15	P15
S2008	21,8	26,3	30,8	35,3	39,8	45,4	20×8	P07	P15	P15	P22	P37
S2012	14,5	17,5	20,5	23,5	26,5	30,3	20×12	P15	P22	P37	P37	T55
S2016	10,9	13,2	15,4	17,6	19,9	22,7	20×16	P15	P22	P37	T55	T75

MODEL	Capacity	FEM / ISO	Hoisting Speed m/min					Dimensions							
			H22	H30	H37	H55	H75	a	b	c		h	WB		
			(R)	(S)											
S2004	25	1Am / M4	4,4	6,1	7,5	11,1	15,2	max 1500	min 34	1400	1800	1650	1000		
	20	2m / M5	5,6	7,6	9,3	13,9	18,9					1600			
	16	3m / M6	6,9	9,5	11,7	17,4	23,7					1650			
	12	4m / M7	9,3	12,6	15,6	15,6	31,6					1700			
	10	5m / M8	11,1	15,2	18,7	18,7	37,9					1750			
S2008	50	1Am / M4	2,2	3,0	3,7	3,7	7,9		max 1500	min 46	1500	1800	1850	1100	
	40	2m / M5	2,8	3,8	4,7	4,7	9,5						1800		
	32	3m / M6	3,5	4,7	5,8	5,8	11,8						1850		
	25	4m / M7	4,4	6,1	7,5	7,5	15,2						1900		
	20	5m / M8	5,6	7,6	9,3	9,3	18,9						1950		
S2012	80	1Am / M4	1,4	1,9	2,3	2,3	4,7			max 1500	min 46	1600	1800	1900	1200
	63	2m / M5	1,8	2,4	3,0	3,0	6,0							1850	
	50	3m / M6	2,2	3,0	3,7	3,7	7,6							1900	
	40	4m / M7	2,8	3,8	4,7	4,7	9,5							1950	
	32	5m / M8	3,5	4,7	5,8	5,8	11,8							2000	
S2016	100	1Am / M4	1,1	1,5	1,9	1,9	3,8	max 1500			min 84	1700	1800	1950	1300
	80	2m / M5	1,4	1,9	2,3	2,3	4,7							1900	
	63	3m / M6	1,8	2,4	3,0	3,0	6,0							1950	
	50	4m / M7	2,2	3,0	3,7	3,7	7,6							2000	
	40	5m / M8	2,8	3,8	4,7	4,7	9,5							2050	

# DB Crab s Series

S 2500 (12.5~125ton)



(R) Type



(S) Type

MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R2400	R2800	R3200	R3600	R4000	R4500		10	15	20	30	40
S2504	43	52	61	70	79	90	22,4×4	P07	P07	P10	P15	P22
S2508	21,5	25,9	30,4	34,9	39,3	44,9	22,4×8	P10	P15	P22	P37	P37
S2512	14,3	17,3	20,3	23,2	26,2	29,9	22,4×12	P15	P22	P37	T55	T75
S2516	10,7	13,0	15,2	17,4	19,7	22,5	22,4×16	P22	P37	P37	T55	T75


MODEL	Capacity	FEM / ISO	Hoisting Speed m/min					Dimensions							
			H22	H30	H37	H55	H75	a	b	c		h	WB		
			(R)	(S)											
S2504	32	1Am / M4	3,5	4,7	5,8	8,7	11,8	max 1600	min 34	1550	2000	1550	1100		
	25	2m / M5	4,4	6,1	7,5	11,1	1500								
	20	3m / M6	5,6	7,6	9,3	13,9	1550								
	16	4m / M7	6,9	9,5	11,7	17,4	1600								
	12	5m / M8	9,3	12,6	15,6	23,1	1650								
S2508	63	1Am / M4	1,8	2,4	3,0	4,4	6,0		max 1600	min 46	1650	2000	1850	1200	
	50	2m / M5	2,2	3,0	3,7	5,6	7,6						1800		
	40	3m / M6	2,8	3,8	4,7	6,9	9,5						1850		
	32	4m / M7	3,5	4,7	5,8	8,7	11,8						1900		
	25	5m / M8	4,4	6,1	7,5	11,1	15,2						1950		
S2512	100	1Am / M4	1,1	1,5	1,9	2,8	3,8			max 1600	min 84	1750	2000	1950	1300
	80	2m / M5	1,4	1,9	2,3	3,5	4,7							1900	
	63	3m / M6	1,8	2,4	3,0	4,4	6,0							1950	
	50	4m / M7	2,2	3,0	3,7	5,6	7,6							2000	
	40	5m / M8	2,8	3,8	4,7	6,9	9,5							2050	
S2516	125	1Am / M4	0,9	1,2	1,5	2,2	3,0	max 1600			min 84	1850	2000	2050	1400
	100	2m / M5	1,1	1,5	1,9	2,8	3,8							2000	
	80	3m / M6	1,4	1,9	2,3	3,5	4,7							2050	
	63	4m / M7	1,8	2,4	3,0	4,4	6,0							2100	
	50	5m / M8	2,2	3,0	3,7	5,6	7,6							2150	

# DB Crab s Series

S 3200 (20~200ton)



(R) Type





(S) Type

MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R2400	R2800	R3200	R3600	R4000	R4500		10	15	20	30	40
S3204	42	51	59	68	77	88	26×4	P07	P10	P15	P22	P37
S3208	20,9	25,3	29,7	34,1	38,5	44,0	26×8	P15	P22	P37	P37	T55
S3212	14,0	16,9	19,8	22,7	25,7	29,3	26×12	P22	P37	P37	T55	T75
S3216	10,5	12,7	14,9	17,1	19,3	22,0	26×16	P37	P37	T55	T75	T11


MODEL	Capacity	FEM / ISO	Hoisting Speed m/min					Dimensions					
			H30	H37	H55	H75	H90	a	b	c		h	WB
			(R)	(S)									
S3204	50	1Bm / M3	3,0	3,7	5,6	7,6	9,1	max 1700	min 44	1650	2200	1800	1200
	40	1Am / M4	3,8	4,7	6,9	9,5	11,4					1750	
	32	2m / M5	4,7	5,8	8,7	11,8	14,2					1700	
	25	3m / M6	6,1	7,5	11,1	15,2	18,2					1280	
	20	4m / M7	7,6	9,3	13,9	18,9	22,7					1280	
S3208	100	1Bm / M3	1,5	1,9	2,8	3,8	4,5		min 46	1750	2200	2000	1300
	80	1Am / M4	1,9	2,3	3,5	4,7	5,7					1950	
	63	2m / M5	2,4	3,0	4,4	6,0	7,2					1900	
	50	3m / M6	3,0	3,7	5,6	7,6	9,1					1950	
	40	4m / M7	3,8	4,7	6,9	9,5	11,4					2000	
S3212	160	1Bm / M3	0,9	1,2	1,7	2,4	2,8		min 84	1850	2200	2200	1400
	125	1Am / M4	1,2	1,5	2,2	3,0	3,6					2150	
	100	2m / M5	1,5	1,9	2,8	3,8	4,5					2100	
	80	3m / M6	1,9	2,3	3,5	4,7	5,7					2150	
	63	4m / M7	2,4	3,0	4,4	6,0	7,2					2200	
S3216	200	1Bm / M3	0,8	0,9	1,4	1,9	2,3	min 84	1950	2200	2350	1500	
	160	1Am / M4	0,9	1,2	1,7	2,4	2,8				2300		
	125	2m / M5	1,2	1,5	2,2	3,0	3,6				2250		
	100	3m / M6	1,5	1,9	2,8	3,8	4,5				2300		
	80	4m / M7	1,9	2,3	3,5	4,7	5,7				2350		

# DB Crab s Series

S 5000 (32~320ton)



(R) Type





(S) Type

MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R2400	R2800	R3200	R3600	R4000	R4500		10	15	20	30	40
S5004	51	60	69	77	89	100	32×4	P10	P15	P22	P37	P37
S5008	25,4	29,8	34,3	38,7	44,3	49,9	32×8	P22	P37	P37	T55	T75
S5012	16,9	19,9	22,9	25,8	29,5	33,3	32×12	P37	T55	T75	T11	T15
S5016	12,7	14,9	17,1	19,4	22,2	24,9	32×16	P37	T55	T75	T11	T15


MODEL	Capacity	FEM / ISO	Hoisting Speed m/min					Dimensions							
			H22	H30	H37	H55	H75	a	b	c		h	WB		
			(R)	(S)											
S5004	80	1Bm / M3	2,3	3,5	4,7	5,7	6,9	max 1800	min 46	2000	2550	1750	1500		
	63	1Am / M4	3,0	4,4	6,0	7,2	8,8					1700			
	50	2m / M5	3,7	5,6	7,6	9,1	11,1					1650			
	40	3m / M6	4,7	6,9	9,5	11,4	13,9					1700			
	32	4m / M7	5,8	8,7	11,8	14,2	17,4					1750			
S5008	160	1Bm / M3	1,2	1,7	2,4	2,8	3,5		max 1800	min 84	2050	2550	2300	1600	
	125	1Am / M4	1,5	2,2	3,0	3,6	4,4						2250		
	100	2m / M5	1,9	2,8	3,8	4,5	5,6						2200		
	80	3m / M6	2,3	3,5	4,7	5,7	6,9						2250		
	63	4m / M7	3,0	4,4	6,0	7,2	8,8						2300		
S5012	250	1Bm / M3	0,7	1,1	1,5	1,8	2,2			max 1800	min 84	2150	2550	2500	1700
	200	1Am / M4	0,9	1,4	1,9	2,3	2,8							2450	
	160	2m / M5	1,2	1,7	2,4	2,8	3,5							2400	
	125	3m / M6	1,5	2,2	3,0	3,6	4,4							2450	
	100	4m / M7	1,9	2,8	3,8	4,5	5,6							2500	
S5016	320	1Bm / M3	0,6	1,1	1,2	1,4	1,7	max 1800			min 84	2250	2550	2700	1800
	250	1Am / M4	1,1	1,5	1,8	2,2	2,8							2650	
	200	2m / M5	0,9	1,4	1,9	2,3	2,8							2600	
	160	3m / M6	1,2	1,7	2,4	2,9	3,5							2650	
	125	4m / M7	1,5	2,2	3,0	3,6	4,4							2700	

# DB Crab s Series

S 6300 (40~400ton)



(R) Type



(S) Type

MODEL	Lifting Height m						Rope Reeving	Traversing Speed m/min				
	R2800	R3200	R3600	R4000	R4500	R5000		10	15	20	30	40
S6304	50	59	68	76	87	99	36×4	P15	P22	P37	P37	T55
S6308	24,9	29,4	33,8	38,2	43,7	49,3	36×8	P37	P37	T55	T75	T11
S6312	16,6	19,6	22,5	25,5	29,2	32,8	36×12	P37	T55	T75	T11	T15
S6316	12,5	14,7	16,9	19,1	21,9	24,6	36×16	T55	T75	T11	T15	T22



MODEL	Capacity	FEM / ISO	Hoisting Speed m/min					Dimensions							
			H37	H55	H75	H90	H110	a	b	c		h	WB		
			(R)	(S)											
S6304	100	1Bm / M3	1,9	2,8	3,8	4,5	5,6	max 1900	min 46	2100	2800	1950	1700		
	80	1Am / M4	2,3	3,5	4,7	5,7	6,9					1900			
	63	2m / M5	3,0	4,4	6,0	7,2	8,8					1850			
	50	3m / M6	3,7	5,6	7,6	9,1	11,1					1900			
	40	4m / M7	4,7	6,9	9,5	11,4	13,9					1950			
S6308	200	1Bm / M3	0,9	1,4	1,9	2,3	2,8		max 1900	min 84	2200	2800	2600	1800	
	160	1Am / M4	1,2	1,7	2,4	2,8	3,5						2550		
	125	2m / M5	1,5	2,2	3,0	3,6	4,4						2500		
	100	3m / M6	1,9	2,8	3,8	4,5	5,6						2550		
	80	4m / M7	2,3	3,5	4,7	5,7	6,9						2600		
S6312	300	1Bm / M3	0,6	0,9	1,3	1,5	1,9			max 1900	min 84	2300	2800	2800	1900
	250	1Am / M4	0,7	1,1	1,5	1,8	2,2							2750	
	200	2m / M5	0,9	1,4	1,9	2,3	2,8							2700	
	150	3m / M6	1,2	1,9	2,5	3,0	3,7							2750	
	125	4m / M7	1,5	2,2	3,0	3,6	4,4							2800	
S6316	400	1Bm / M3	0,5	0,7	0,9	1,1	1,4	max 1900			min 84	2400	2800	3000	2000
	320	1Am / M4	0,6	0,9	1,2	1,4	1,7							2950	
	250	2m / M5	0,7	1,1	1,5	1,8	2,2							2900	
	200	3m / M6	0,9	1,4	1,9	2,3	2,8							2950	
	160	4m / M7	1,2	1,7	2,4	2,8	3,5							3000	





# WIRE HOIST A Type

## Regular Type Suspension Hoist




Model		KN 0,5-F	KN 1-F	KN 2-F	KN 2,8-F	KN 3-F	KN 5-F	
Capacity(ton)		1/2	1	2	2,8	3	5	
Type	Hoisting Speed	High Speed	KN1/2-H6(12)	KN1-H6(12)	KN2-H6(12)	KN2,8-H6(12)	KN3-H6(12)	KN5-H6(12)
		Low Speed	KN1/2-L6(12)	KN1-L6(12)	KN2-L6(12)	KN2,8-L6(12)	KN3-L6(12)	KN5-L6(12)
Hoist	Max. lift(m)		6(12)	6(12)	6(12)	6(12)	6(12)	6(12)
	Hoisting Speed (m/min)	High Speed 50/60(HZ)	10/12	10/12	8,4/10	7,5/9	7,5/9	4,7/5,6
		Low Speed 50/60(HZ)	5/6	5/6	4,2/5	3,7/4,5	3,7/4,5	3,5/4,2
	Hoisting Motor (kwxP)	High Speed	1,2x4	2,4x4	3,7x4	4,8x4	5,5x4	5,5x6
		Low Speed	0,6x8	1,2x8	1,8x8	2,4x8	2,8x8	4,2x8
	Wire Rope	Construction	6x37	6x37	6x37	6x37	6x37	6x37
Dial(mm)x No. of Ropes		6x2	8x2	10x2	12,5x2	12,5x2	16x2	
Brake		DC Magnet Disc Brake						
Dimensions (approx.) (mm)	H	640	750	920	1060	1060	1245	
	A	370(465)	405(505)	465(565)	520(620)	520(620)	605(705)	
	B	355(455)	380(480)	410(510)	440(540)	440(540)	500(585)	
	C	150	170	205	210	210	250	
	D	230	255	290	350	380	415	
	G	160	160	200	200	200	280	
	F	28	28	3	34,5	34,5	44,5	
	I	112	112	150	150	150	180	
	K	385	360	470	560	560	690	
	M	340(530)	350(550)	350(550)	364(564)	364(564)	450(650)	
	N	160	150	200	200	200	250	
	P	48	45	47	44	44	55	
	d <sup>1</sup>	26	26	33	33	33	47	
d <sup>2</sup>	17	17	17	17	17	17		
Weight(approx.) (kg)		100(120)	142(170)	240(240)	300(345)	300(345)	460(525)	

Note : Figures in parentheses are for hoists of 12-meter lift

※ KN □□□□-N-H□□-F Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Regular Type Suspension Hoist




Model		KN 7,5-F	KN 10-F	KN 15-F	KN 20-F	
Capacity(ton)		7,5	10	15	20	
Type	Hoisting Speed	High Speed	KN 7,5-H12	KN 10-H12	KN 15-H12	KN 20-H12
		Low Speed	KN 7,5-L12	KN 10-L12	KN 15-L12	KN 20-L12
Hoist	Max. lift(m)		12	12	12	12
	Hoisting Speed (m/min)	High Speed 50/60(HZ)	3,1/3,8	3,7/4,5	3,7/4,5	3,5/4,2
		Low Speed 50/60(HZ)	2,3/2,8	2,5/3	2,5/3	2,3/2,8
	Hoisting Motor (kwxP)	High Speed	5,5x6	9x8	13x8	17x8
		Low Speed	4,2x8	6x12	8,5x12	11,5x12
	Wire Rope	Construction	6x37	6x37	6x37	6x37
Dial(mm)x No. of Ropes		14x4	16x4	20x4	22,4x4	
Brake		DC Magnet Disc Brake				
Dimensions (approx.) (mm)	H	1270	1330	1660	1900	
	A	925	975	1075	1165	
	B	835	955	1005	1220	
	C	300	330	370	400	
	D	480	510	620	640	
	G	800	800	800	850	
	F	232	232	272	272	
	I	50	50	65	65	
	K	720	740	965	1150	
	M	1100	1100	1150	1250	
	N	400	400	500	500	
	P	62	62	70	70	
	d <sup>1</sup>	47	47	63	63	
d <sup>2</sup>	25	25	25	25		
Weight(approx.) (kg)		700	1000	1500	1900	

※ KN □□□□-N-H□□-F Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Regular Type Suspension Hoist




Model		KD 35-F	KD 50-F	KD 60-F	KD 70-F	
Capacity(ton)		35	50	60	70	
Type		KD 35-H12	KD 50-H12	KD 60-H12	KD 70-H12	
Hoist	Max. lift(m)	12	12	12	12	
	Hoisting Speed(m/min) 50/60(HZ)	4/4,5	2,7/3,2	2/2,4	2/2,4	
	Hoisting Motor(kwxP)	33×6	33×6	33×6	33×6	
	Wire Rope	Construction	6×Fi(25)	6×Fi(25)	6×Fi(25)	6×Fi(25)
		Dial(mm)x No. of Ropes	28×4	28×6	28×8	28×8
Brake		DC Magnet Disc Brake				
Dimensions (approx.) (mm)	H	1500	1900	2000	2000	
	A	1455	1780	2030	2030	
	B	1360	1685	1935	1935	
	C	560	905	1000	1000	
	D	855	1100	1005	1005	
	G	1000	1000	1000	1000	
	F	1075	1430	1930	1930	
	I	1500	2250	2750	2750	
	K	1000	1600	1600	1600	
M	47	63	63	63		
Weight(approx.) (kg)		4200	6000	8200	8200	

※ KD □□□□-N-H□□-F Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Regular Type Hoist with Hand-push Trolley




Model		KN 0,5-P			KN 1-P			KN 2-P			
Capacity(ton)		1/2			1			2			
Type	Hoisting Speed	High Speed	KN 1/2-H6(12)-P			KN 1 H6(12)-P			KN 2-H6(12)-P		
		Low Speed	KN 1/2-L6(12)-P			KN 1 L6(12)-P			KN 2-L6(12)-P		
Hoist	Max. lift(m)		6(12)			6(12)			6(12)		
	Hoisting Speed (m/min)	High Speed 50/60(HZ)	10/12			10/12			8,4/10		
		Low Speed 50/60(HZ)	5/6			5/6			4,2/5		
	Hoisting Motor (kwxP)	High Speed	1,2x4			2,4x4			3,7x4		
		Low Speed	0,6x8			1,2x8			1,8x8		
	Wire Rope	Construction	6x37			6x37			6x37		
Dial(mm)x No. of Ropes		6x2			8x2			10x2			
Brake		DC Magnet Disc Brake									
Dimensions (approx.) (mm)		H	705			815			980		
		A	370(465)			405(505)			465(565)		
		B	355(450)			380(480)			410(510)		
		C	150			170			205		
		D	265			275			310		
		G	185			185			205		
I-Beam and Spacing (mm)		a <b>x</b> b <b>x</b> c	S	T	U	S	T	U	S	T	U
		200x100x7	38	46	126	38	46	126	38	46	126
		250x125x7,5	30	71	134	30	71	134	24	71	162
		300x150x10	28	96	136	28	96	136	24	96	162
Min. Radius of Curvature(m)		1,5			1,5			1,8			
Weight(approx.) (kg)		123(143)			166(194)			244(280)			

Note : 1. Dimension of I-beam in      Sections are standard ones, Other I-beam also can be changing spacers,  
2. If Curved rail requires, this must be indicated in advance,

※ KN         -N-H    -P Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Regular Type Hoist with Geared Trolley



Model		KN 0,5-G	KN 1-G	KN 2-G	KN 2,8-G	KN 3-G	KN 5-G																			
Capacity(ton)		1/2	1	2	2,8	3	5																			
Type	Hoisting Speed	High Speed	KN1/2-H6(12)-G	KN1-H6(12)-G	KN2-H6(12)-G	KN2,8-H6(12)-G	KN3-H6(12)-G	KN5-H6(12)-G																		
		Low Speed	KN1/2-L6(12)-G	KN1-L6(12)-G	KN2-L6(12)-G	KN2,8-L6(12)-G	KN3-L6(12)-G	KN5-L6(12)-G																		
Hoist	Max. lift(m)		6(12)	6(12)	6(12)	6(12)	6(12)	6(12)																		
	Hoisting Speed (m/min)	High Speed 50/60(HZ)	10/12	10/12	8,4/10	7,5/9	7,5/9	4,7/5,6																		
		Low Speed 50/60(HZ)	5/6	5/6	4,2/5	3,7/4,5	3,7/4,5	3,5/4,2																		
	Hoisting Motor (kwXp)	High Speed	1,2X4	2,4X4	3,7X4	4,8X4	5,5X4	5,5X6																		
		Low Speed	0,6X8	1,2X8	1,8X8	2,4X8	2,8X8	4,2X8																		
	Wire Rope	Construction	6X37	6X37	6X37	6X37	6X37	6X37																		
Dial(mm)x No. of Ropes		6X2	8X2	10X2	12,5X2	12,5X2	16X2																			
Brake		DC Magnet Disc Brake																								
Dimensions (approx.) (mm)	H	705	705	705	705	705	705																			
	A	370(465)	370(465)	370(465)	370(465)	370(465)	370(465)																			
	B	355(450)	355(450)	355(450)	355(450)	355(450)	355(450)																			
	C	255	255	255	255	255	255																			
	265	275	275	275	275	275	275																			
	K	200	200	200	200	200	200																			
I-Beam and Spacing (mm)	aXbXc	C	S	R	U	V	C	S	R	U	V	C	S	R	U	V	C	S	R	U	V	C	S	R	U	V
	200X100X7	329	38	46	144	172	329	38	46	144	172	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	250X125X7,5	342	30	71	153	181	342	30	71	153	181	356	24	71	182	240	356	24	71	182	240	359	39	61	222	256
	300X150X10	354	28	96	156	183	354	28	96	156	183	369	24	96	182	245	369	24	96	182	245	371	37	86	274	260
	450X175X13	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Min. Radius of Curvature(m)		1,5		1,5		1,8		1,8		1,8		2,3														
Weight(approx.) (kg)		147(179)		190(230)		273(321)		369(417)		369(417)		562(639)														


Note : 1. Figures in parentheses are for Hoists of 12-meter lift.

2. Dimensions of I-beam in yellow sections are standard ones. Other I-beam also can be used by changing spacers.

\* KN □□□□-N-H□□-G Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Regular Type Hoist with Motor-Driven Trolley



Model			KN 0,5-M	KN 1-M	KN 2-M	KN 2,8-M	KN 3-M	KN 5-M																				
Capacity(ton)			1/2	1	2	2,8	3	5																				
Type	High Speed Hoisting	traversing high	KN1/2-H6(12)-MH	KN1-H6(12)-MH	KN2-H6(12)-MH	KN2,8-H6(12)-MH	KN3-H6(12)-MH	KN5-H6(12)-MH																				
		traversing low	KN1/2-H6(12)-ML	KN1-H6(12)-ML	KN2-H6(12)-ML	KN2,8-H6(12)-ML	KN3-H6(12)-ML	KN5-H6(12)-ML																				
	Low Speed Hoisting	traversing high	KN1/2-L6(12)-MH	KN1-L6(12)-MH	KN2-L6(12)-MH	KN2,8-L6(12)-MH	KN3-L6(12)-MH	KN5-L6(12)-MH																				
		traversing low	KN1/2-L6(12)-ML	KN1-L6(12)-ML	KN2-L6(12)-ML	KN2,8-L6(12)-ML	KN3-L6(12)-ML	KN5-L6(12)-ML																				
Hoist	Max. lift(m)		6(12)	6(12)	6(12)	6(12)	6(12)	6(12)																				
	Hoisting Speed (m/min)	High Speed 50/60(HZ)	10/12	10/12	8,4/10	7,5/9	7,5/9	4,7/5,6																				
		Low Speed 50/60(HZ)	5/6	5/6	4,2/5	3,7/4,5	3,7/4,5	3,5/4,2																				
	Hoisting Motor (kw×P)	High Speed	1,2×4	2,4×4	3,7×4	4,8×4	5,5×4	5,5×6																				
		Low Speed	0,6×8	1,2×8	1,8×8	2,4×8	2,8×8	4,2×8																				
	Wire Rope	Construction	6×37	6×37	6×37	6×37	6×37	6×37																				
Dial(mm)× No. of Ropes		6×2	8×2	10×2	12,5×2	12,5×2	16×2																					
Brake			DC Magnet Disc Brake																									
Traversing	Traversing Speed (m/min)	High Speed 50/60(HZ)	20/24	20/24	20/24	20/24	20/24	20/24																				
		Low Speed 50/60(HZ)	13/16	13/16	13/16	13/16	13/16	13/16																				
	Traversing Motor (kw×P)	High Speed	0,4×4	0,4×4	0,75×4	0,75×4	0,75×4	0,75×4																				
		Low Speed	0,2×6	0,2×6	0,5×6	0,5×6	0,5×6	0,5×6																				
Dimensions (approx.) (mm)	H		705	815	980	1115	1115	1325																				
	A		370(465)	405(505)	465(565)	520(620)	520(620)	605(705)																				
	B		355(450)	380(480)	410(510)	440(540)	440(540)	500(585)																				
	D		255	275	310	365	380	415																				
	G		275	255	260	260	260	275																				
	K		200	200	225	225	225	275																				
I-Beam and Spacing (mm)	a×b×c			C	S	R	U	V	C	S	R	U	V	C	S	R	U	V	C	S	R	U	V	C	S	R	U	V
	200×100×7			385	150	38	46	144	385	170	38	46	144	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	250×125×7,5			395	150	30	71	153	395	170	30	71	153	445	205	24	71	182	445	210	23	71	182	455	250	398	61	222
	300×150×10			410	150	28	96	155	410	170	28	96	155	460	205	24	96	182	460	210	23	96	182	465	250	37	86	224
	450×175×13			-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	480	250	34	111	228
Min. Radius of Curvature(m)			1,5		1,5		1,8		1,8		1,8		2,3															
Weight(approx.) (kg)			147(167)		190(218)		278(314)		374(418)		374(418)		577(642)															

Note : 1. Figures in parentheses are for Hoists of 12-meter lift.


2. Dimensions of I-beam in yellow sections are standard ones, Other I-beam also can be used by changing spacers.

※ KN □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding



# WIRE HOIST A Type

## Regular Type Hoist with Motor-Driven Trolley




Model		KN 7.5-M	KN 10-M	KN 15-M	KN 20-M																
Capacity(ton)		7.5	10	15	20																
Type	High Speed Hoisting	traversing high	KN 7.5 - H12-MH	KN 10 - H12-MH	KN 15 - H12-MH	KN 20 - H12-MH															
		traversing low	KN 7.5 - H12-ML	KN 10 - H12-ML	KN 15 - H12-ML	KN 20 - H12-ML															
	Low Speed Hoisting	traversing high	KN 7.5 - L12-MH	KN 10 - L12-MH	KN 15 - L12-MH	KN 20 - L12-MH															
		traversing low	KN 7.5 - L12-ML	KN 10 - L12-ML	KN 15 - L12-ML	KN 20 - L12-ML															
Hoist	Max. lift(m)		12	12	12	12															
	Hoisting Speed(m/min)	High Speed 50/60(HZ)	3,1/3,8	3,7/4,5	3,7/4,5	3,5/4,2															
		Low Speed 50/60(HZ)	2,3/2,8	2,5/3	2,5/3	2,8/2,8															
	Hoisting Motor (kw X P)	High Speed	5,5X6	9X8	13X8	17X8															
		Low Speed	4,2X8	6X12	8,5X12	11,5X12															
	Wire Rope	Construction	6X37	6X37	6X37	6X37															
Dial(mm)x No. of Ropes		14X4	16X4	20X4	22,4X4																
Brake		DC Magnet Disc Brake																			
Traversing	Traversing Speed (m/min)	High Speed 50/60(HZ)	12,5/15	12,5/15	12,5/15	12,5/15															
		Low Speed 50/60(HZ)	8,3/10	8,3/10	8,3/10	8,3/10															
	Traversing Motor (kw X P)	High Speed	0,75X4	0,75X4	1,5X4	1,5X4															
		Low Speed	0,5X6	0,5X6	1X6	1X6															
Brake		DC Magnet Disc Brake																			
Dimensions (approx.) (mm)	H	1460	1520	1875	2115																
	A	925	975	1075	1165																
	B	835	955	1005	1220																
	D	480	510	620	640																
	G	800	800	800	850																
	K	276	276	300	300																
	M	276	276	300	300																
I-Beam and Spacing (mm)	aXbXc	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U
	300X150X10	500	300	35	68	224	485	330	35	68	224	-	-	-	-	-	-	-	-	-	-
	450X175X13	510	300	20	93	228	490	330	30	93	228	580	370	32	77	248	580	400	32	77	248
	600X190X13	520	300	25	118	232	495	330	25	118	232	590	370	32	92	248	590	370	32	92	248
Min. Radius of Curvature(m)		For Straight Rails Only																			
Weight(approx.) (kg)		910		1210			2030			2430											

Note : 1. Dimensions of I-beam in yellow sections are standard ones, Other I-beam also can be used by changing spacers.  
2. If curved rail requires, this must be indicated in advance.

※ KN □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Double-Rail Type Hoist with Motor-Driven Trolley




Model			KD 2-M	KD 2,8-M	KD 3-M	KD 5-M
Capacity(ton)			2	2,8	3	5
Type	High Speed Hoisting	traversing high	KD 2- H12-MH	KD 2,8- H12-MH	KD 3- H12-MH	KD 5- H12-MH
		traversing low	KD 2- H12-ML	KD 2,8- H12-ML	KD 3- H12-ML	KD 5- H12-ML
	Low Speed Hoisting	traversing high	KD 2- L12-MH	KD 2,8- L12-MH	KD 3- L12-MH	KD 5- L12-MH
		traversing low	KD 2- L12-ML	KD 2,8- L12-ML	KD 3- L12-ML	KD 5- L12-ML
Hoist	Max. lift(m)		12	12	12	(9)12
	Hoisting Speed(m/min)	High Speed 50/60(HZ)	8,4/10	7,5/9	7,5/9	4,7/5,6
		Low Speed 50/60(HZ)	4,2/5	3,7/4,5	3,7/4,5	3,5/4,2
	Hoisting Motor (kw X P)	High Speed	3,7X4	4,8/4	5,5X4	5,5X6
		Low Speed	1,8X8	2,4X8	2,8X8	4,2X8
	Wire Rope	Construction	6X37	6X37	6X37	6X37
Dial(mm)x No. of Ropes		8X4	9X4	9X4	12,5X4	
Brake		DC Magnet Disc Brake				
Traversing	Traversing Speed (m/min)	High Speed 50/60(HZ)	20/24	20/24	20/24	20/24
		Low Speed 50/60(HZ)	13/16	13/16	13/16	13/16
	Traversing Motor (kw X P)	High Speed	0,75X4	0,75X4	0,75X4	0,75X4
		Low Speed	0,5X6	0,5X6	0,5X6	0,5X6
Dimensions (approx.) (mm)	H	415	420	420	510	
	R	950	950	950	(950)1150	
	A	465	465	465	510	
	B	390	390	390	470	
	C	500	600	600	550	
	G	740	785	785	935	
	K	690	705	705	830	
	W	650	650	650	760	
	D	47	47	47	47	
	L	680	690	690	890	
	M	115	115	115	125	
	N	90	90	90	110	
P	140	140	140	165		
Q	170	170	170	190		
Weight(approx.) (kg)		450	550	550	850	
Traversing Rail		15kg/m	15kg/m	15kg/m	15kg/m	

※ KD □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Double-Rail Type Hoist with Motor-Driven Trolley




Model			KD 7,5-M	KD 10-M	KD 15-M	KD 20-M	KD 30-M
Capacity(ton)			7,5	10	15	20	30
Type	High Speed Hoisting	traversing high	KD 7,5-H12-MH	KD 10-H12-MH	KD 15-H12-MH	KD 20-H12-MH	KD 30-H12-MH
		traversing low	KD 7,5-H12-ML	KD 10-H12-ML	KD 15-H12-ML	KD 20-H12-ML	KD 30-H12-ML
	Low Speed Hoisting	traversing high	KD 7,5-L12-MH	KD 10-L12-MH	KD 15-L12-MH	KD 20-L12-MH	KD 30-L12-MH
		traversing low	KD 7,5-L12-ML	KD 10-L12-ML	KD 15-L12-ML	KD 20-L12-ML	KD 30-L12-ML
Hoist	Max. lift(m)		12	(9)12	12	12	12
	Hoisting Speed(m/min)	High Speed 50/60(HZ)	3,1/3,8	3,7/4,5	3,7/4,5	3,5/4,2	2,3/2,8
		Low Speed 50/60(HZ)	2,2/2,8	2,5/3	2,5/3	2,5/2,8	1,5/1,8
	Hoisting Motor (kw X P)	High Speed	5,5X6	9X8	13X8	17X8	17X8
		Low Speed	4,2X8	6X12	8,5X12	11,5X12	11,5X12
	Wire Rope	Construction	6X37	6X37	6X37	6X37	6X37
Dial(mm)x No. of Ropes		14X4	16X4	20X4	22,4X4	22,4X6	
Brake			DC Magnet Disc Brake				
Traversing	Traversing Speed (m/min)	High Speed 50/60(HZ)	12,5/15	12,5/15	12,5/15	12,5/15	12,5/15
		Low Speed 50/60(HZ)	8,3/10	8,3/10	8,3/10	8,3/10	8,3/10
	Traversing Motor (kw X P)	High Speed	0,75X4	0,75X4	1,5X4	1,5X4	1,5X4(2units)
		Low Speed	0,5X6	0,5X6	1X6	1X6	1X6(2units)
Dimensions (approx.) (mm)	H	730	775	995	1175	1480	
	R	1150	(950)1150	1200	1300	1800	
	A	525	565	625	670	940	
	B	480	510	555	610	940	
	C	550	695	860	900	980	
	G	925	975	1075	1165	1425	
	K	835	955	1005	1220	1480	
	W	800	865	920	1000	1540	
	D	58	58	58	58	70	
	L	852	851	872	934	1418	
	M	120	120	130	140	180	
	N	95	100	130	140	160	
P	165	165	180	220	250		
Q	195	195	210	250	280		
Weight(approx.) (kg)			900	1200	1820	2300	3450
Traversing Rail			15kg/m	15kg/m	22kg/m	22kg/m	30kg/m

※ KD □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Double-Rail Type Hoist with Motor-Driven Trolley




Model		KD 35-M	KD 40-M	KD 50-M	KD 60-M	KD 70-M	
Capacity(ton)		35	40	50	60	70	
Type	High Speed Traversing	KD 35-H12-MH	KD 40-H12-MH	KD 50-H12-MH	KD 60-H12-MH	KD 70-H12-MH	
	Low Speed Traversing	KD 35-H12-ML	KD 40-H12-ML	KD 50-H12-ML	KD 60-H12-ML	KD 70-H12-ML	
Hoist	Max. lift(m)		12	12	12	12	
	Hoisting Speed(m/min)50/60(HZ)		4/4,8	2,7/3,2	2,7/3,2	2/2,4	2/2,4
	Hoisting Motor (kwXp)		33X6	33X6	33X6	33X6	33X6
	Wire Rope	Construction	6XF(25)	6XF(25)	6XF(25)	6XF(25)	6XF(25)
Dial(mm)x No. of Ropes		28X4	28X6	28X6	28X8	28X8	
Brake		DC Magnet Disc Brake					
Traversing	Traversing Speed (m/min)	High Speed 50/60(HZ)	12,5/15	12,5/15	12,5/15	12,5/15	
		Low Speed 50/60(HZ)	8,3/10	8,3/10	8,3/10	8,3/10	
Traversing Motor (kw X P)		High Speed	2,2X4	2,2X4(2UNITS)	2,2X4(2UNITS)	2,2X4(2UNITS)	3,7X4(2UNITS)
		Low Speed	1,5X6	1,5X6(2UNITS)	1,5X6(2UNITS)	1,5X6(2UNITS)	2,2X6(2UNITS)
Dimensions (approx.) (mm)		H	1490	1680	1680	1780	1780
		R	1600	2300	2300	2800	2800
		A	1025	1432	1432	1525	1525
		B	955	1243	1243	1150	1150
		C	1013	1220	1220	1220	1220
		G	1455	1780	1780	2030	2030
		K	1360	1715	1715	1965	1965
		W	1550	2125	2125	2125	2075
		D	70	80	80	80	80
		L	1044	1430	1430	1930	1930
		M	215	275	275	275	300
		N	215	275	275	275	300
Weight(approx.) (kg)		5200	7000	7000	8500	9000	
Traversing Rail		37kg/m	50kg/m	50kg/m	50kg/m	50kg/m	

※ KD □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Low-Head Type Hoist with Motor-Driven Trolley




Model			KL 0,5-M	KL 1-M	KL 2-M	KL 2,8-M	KL 3-M	KL 5-M											
Capacity(ton)			1/2	1	2	2,8	3	5											
Type	High Speed Hoisting	traversing high	KL 1/2-H6-MH	KL 1-H6-MH	KL 2-H6-MH	KL 2,8-H6-MH	KL 3-H6-MH	KL 5-H6-MH											
		traversing low	KL 1/2-H6-ML	KL 1-H6-ML	KL 2-H6-ML	KL 2,8-H6-ML	KL 3-H6-ML	KL 5-H6-ML											
	Low Speed Hoisting	traversing high	KL 1/2-H6-MH	KL 1-H6-MH	KL 2-H6-MH	KL 2,8-H6-MH	KL 3-H6-MH	KL 5-H6-MH											
		traversing low	KL 1/2-H6-ML	KL 1-H6-ML	KL 2-H6-ML	KL 2,8-H6-ML	KL 3-H6-ML	KL 5-H6-ML											
Hoist	Max. lift(m)		6	6	6	6	6	6											
	Hoisting Speed (m/min)	High Speed 50/60(HZ)	10/12	10/12	8,4/10	7,5/9	7,5/9	4,7/5,6											
		Low Speed 50/60(HZ)	5/6	5/6	4,2/5	3,7/4,5	3,7/4,5	3,5/4,2											
	Hoisting Motor (kw x P)	High Speed	1,2x4	2,4x4	3,7x4	4,8x4	5,5x4	5,5x6											
		Low Speed	,6x8	1,2x8	1,8x8	2,4x8	2,8x8	4,2x8											
	Wire Rope	Construction	7x19	6x37	6x37	6x37	6x37	6x37											
Dial(mm)x No. of Ropes		4x4	6x4	8x4	9x4	9x4	11,2x4												
Brake			DC Magnet Disc Brake																
Traversing	Traversing Speed (m/min)	High Speed 50/60(HZ)	20/24	20/24	20/24	20/24	20/24	20/24											
		Low Speed 50/60(HZ)	13/16	13/16	13/16	13/16	13/16	13/16											
	Traversing Motor (kw x P)	High Speed	0,4x4	0,4x4	0,75x4	0,75x4	0,75x4	0,75x4											
		Low Speed	0,2x6	0,2x6	0,5x6	0,5x6	0,5x6	0,5x6											
Dimensions (approx.) (mm)	H	550	550	620	620	620	800												
	A	465	505	590	620	620	705												
	B	450	480	510	540	540	585												
	C	405	405	435	495	510	585												
	D	245	290	385	395	395	465												
	G	255	255	260	260	260	275												
	K	200	200	225	225	225	275												
I-Beam and Spacing (mm)	a x b x c	S	T	U	S	T	U	S	T	U	S	T	U	S	T	U	S	T	U
	200x100x7	38	46	144	38	46	144	-	-	-	-	-	-	-	-	-	-	-	-
	250x125x7,5	30	71	153	30	71	153	22	71	182	23	71	18	22	371	182	-	-	-
	300x150x10	28	96	155	30	71	153	22	96	182	23	96	182	23	96	182	26	86	224
	450x175x13	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	23	111	228
Min. Radius of Curvature(m)			1,5	1,5	1,8	1,8	1,8	2,3											
Weight(approx.) (kg)			175	200	350	440	440	730											

Note : 1. Dimensions of I-beam in      Sections are standard ones. Other I-beam also can be used by changing spacers.

※ KL         -N-H   Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Double Low-Head Type Hoist with Motor-Driven Trolley



Model		KP 2-M	KP 2,8-M	KP 3-M	KP 5-M	KP 7,5-M		
Capacity(ton)		2	2,8	3	5	7,5		
Type	High Speed Hoisting	traversing high	KP 2-H6-MH	KP 2,8-H6-MH	KP 3-H6-MH	KP 5-H6-MH	KP 7,5-H12-MH	
		traversing low	KP 2-H6-ML	KP 2,8-H6-ML	KP 3-H6-ML	KP 5-H6-ML	KP 7,5-H12-ML	
	Low Speed Hoisting	traversing high	KP 2-L6-MH	KP 2,8-L6-MH	KP 3-L6-MH	KP 5-L6-MH	KP 7,5-L12-MH	
		traversing low	KP 2-L6-ML	KP 2,8-L6-ML	KP 3-L6-ML	KP 5-L6-ML	KP 7,5-L12-ML	
Hoist	Max. lift(m)		6(12)	6(12)	6(12)	10	12	
	Hoisting Speed (m/min)	High Speed	50(HZ)	8,3	7,5	7,5	4,7	3,2
			60(HZ)	10	9	9	5,6	3,8
		Low Speed	50(HZ)	5	3,8	3,8	3,5	2,4
			60(HZ)	6	4,5	4,5	4,2	2,8
	Hoisting Motor (kw x P)	High Speed	3,7 x 4	4,8 x 4	5,5 x 4	5,5 x 6	5,5 x 6	
Low Speed		18,8 x 6	2,4 x 8	2,8 x 8	4,2 x 8	4,2 x 8		
Wire Rope	Construction	6 x 37	6 x 37	6 x 37	6 x 37	6 x 37		
	Dial(mm) x No. of Ropes	8 x 4	9 x 4	9 x 4	11,2 x 4	14 x 4		
Brake		DC Magnet Disc Brake						
Traversing	Traversing Speed (m/min)	High Speed	50(HZ)	20	20	20	20	
			60(HZ)	24	24	24	15	
		Low Speed	50(HZ)	13	13	13	13	8,3
			60(HZ)	16	16	16	16	10
	Traversing Motor (kw x P)	High Speed	0,75 x 4	0,75 x 4	0,75 x 4	0,75 x 4	0,75 x 4	
		Low Speed	0,5 x 6	0,5 x 6	0,5 x 6	0,5 x 6	0,5 x 6	
Brake								
Dimensions (approx.) (mm)	H	390	495	495	525	950		
	R	950	950	950	1150	1400		
	C	170	170	170	200	200		
	G	582	652	652	730	925		
	K	532	550	550	620	870		
	W	650	650	650	772	1250		
	D	47	47	47	47	47		
	P	140	140	140	165	165		
	Q	170	170	170	195	195		
Weight(approx.) (kg)		15kg/m	15kg/m	15kg/m	15kg/m	15kg/m		

Note : Available lift height over 6meters.

※ 10<sup>t</sup>, 15<sup>t</sup>, 20<sup>t</sup>, 30<sup>t</sup> Consult factory for specification.

※ KP □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding





### A Specific Character of Creep Hoist

- **Create 1/10 Hoisting Speed Ratio**
- **Working Efficiency**

Speed is freely changed with push buttons at a high speed when large movement and creep speed when fine adjusting movement.

The hoisted load is securely and efficiently stopped and unloaded.
- **Safety Design**


Two Motors of creep and high speed are provided, The creep speed selected by 2nd level pushed button and the high speed by 1st level pushed button. Even if the load is hoisted for a short distance, it is stably and smoothly.
- **Smooth Trolley Travel**

Trolley is equipped with geared motor of slow-start and stop so that the trolley position is finely and smoothly adjusted.
- **Durability and Economical Improvement**

Since inching operation is unnecessary, there is no over-current, machine mechanism shock is softened and durability is increased. Thus, the hoist is the energy saving type which reduces demand.
- **Fine Work, Various Applications**
  - Work removable to machine tool
  - Machine assembly
  - Die matching of injection machine
  - Die mounting, re-oving to press
  - Change of jigs and tools
  - Die transfer, matching and drawing works at casting shop

# WIRE HOIST A Type

## Regular Type Creep Hoist with Motor-Driven Trolley




Model		KN 1-M				KN 2-M				KN 2,8-M				KN 3-M				KN 5-M					
Capacity(ton)		1				2				2,8				3				5					
Type	High Speed Traversing	C-KN 1-H6(12)-MH				C-KN 2-H6(12)-MH				C-KN2,8-H6(12)-MH				C-KN 3-H6(12)-MH				C-KN 5-H6(12)-MH					
	Low Speed Traversing	C-KN 1-H6(12)-ML				C-KN 2-H6(12)-ML				C-KN2,8-H6(12)-ML				C-KN 3-H6(12)-ML				C-KN 5-H6(12)-ML					
Hoist	Max. lift(m)		6(12)				6(12)				6(12)				6(12)				6(12)				
	Hoisting Speed(m/min)	50(HZ)	10/1				8,4/0,84				7,5/0,75				7,5/0,75				4,7/0,47				
	High/Creep Speed	60(HZ)	12/1,2				10/1				9/0,9				9/0,9				5,6/0,56				
	Motor(KWXP)High/Creep Speed		2,4/0,4x4				3,7/0,4x4				4,8/1,1x4				5,5/1,1x4				5,5/1x6				
	Wire Rope	Construction		6x37				6x37				6x37				6x37				6,37			
Dial(mm)x No. of Ropes		8x2				10x2				12,5x2				12,5x2				16x2					
Brake		DC Magnet Disc Brake																					
Traversing	Traversing Speed (m/min)	High Speed	50(HZ)	20				20				20				20				20			
			60(HZ)	24				24				24				24				24			
		Low Speed	50(HZ)	13				13				13				13				13			
			60(HZ)	16				16				16				16				16			
Traversing Motor (kw x P)	High Speed		0,4x4				0,75x4				0,75x4				0,75x4				0,75x4				
	Low Speed		0,2x6				0,5x6				0,5x6				0,5x6				0,5x6				
Dimensions (approx.) (mm)	H		815				980				1115				1115				1325				
	A		580(680)				620(720)				740(840)				740(840)				840(940)				
	B		380(480)				410(510)				440(540)				440(540)				500(585)				
	D		275				310				365				380				415				
	F		330				370				375				375				430				
	G		255				260				260				260				275				
K		200				225				225				225				275					
I-Beam and Spacing (mm)	a x b x c		C	S	T	U	C	S	T	U	C	S	T	U	C	S	T	U	C	S	T	U	
	200x100x7		395	38	46	144	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	250x125x7,5		395	30	71	153	445	26	71	183	445	25	71	182	445	25	71	182	455	37	61	222	
	300x150x10		410	28	96	156	460	24	96	182	460	23	96	182	460	23	96	182	465	32	86	224	
	450x175x13		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	480	32	111	228	
Min. Radius of Curvature(m)		1,5				1,8				1,8				1,8				2,3					
Weight(approx.) (kg)		225(245)				320(355)				415(460)				415(460)				635(700)					

Note : 1. Dimension of I-beam in      Sections are standard ones. Other I-beam also can be changing spacers.  
2. If Curved rail requires, this must be indicated in advance.

※ KN     -C-H     Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Regular Type Creep Hoist with Motor-Driven Trolley




Model		KN 7,5-M				KN 10-M				KN 15-M				KN 20-M					
Capacity(ton)		7,5				10				15				20					
Type	High Speed Traversing	C-KN 7,5-H12-MH				C-KN 10-H12-MH				C-KN 15-H12-MH				C-KN 20-H12-MH					
	Low Speed Traversing	C-KN 7,5-H12-ML				C-KN 10-H12-ML				C-KN 15-H12-ML				C-KN 20-H12-ML					
Hoist	Max. lift(m)		12				12				12				12				
	Hoisting Speed(m/min)	50(HZ)	3,1/0,31				3,7/0,37				3,7/0,37				3,5/0,35				
		60(HZ)	3,8/0,38				4,5/0,45				4,5/0,45				4,2/0,42				
	Motor(KW×P)High/Creep Speed		5,5/1×6				9/1,1×8				13/1,8×8				17/1,8×8				
	Wire Rope	Construction		6×37				6×37				6/37				6×37			
		Dial(mm)x No. of Ropes		14×4				16×4				20×4				22,4×4			
Brake		DC Magnet Disc Brake																	
Traversing	Traversing Speed (m/min)	High Speed	50(HZ)	12,5				12,5				12,5				12,5			
			60(HZ)	15				15				15				15			
		Low Speed	50(HZ)	8,3				8,3				8,3				8,3			
			60(HZ)	10				10				10				10			
Traversing Motor (kw × P)		High Speed	0,75×4				0,75×4(2units)				1,5×4(2units)				1,5×4(2units)				
		Low Speed	0,5×6				0,5×6(2units)				1×6(2units)				1×6(2units)				
Dimensions (approx.) (mm)		H	1460				1565				1875				2115				
		A	1170				1230				1365				1460				
		B	835				955				1005				1220				
		D	480				510				620				640				
		F	465				525				575				621				
		L	850				850				870				935				
		G	800				800				800				850				
		M	276				276				300				300				
I-Beam and Spacing (mm)		a×b×c		C	S	T	U	C	S	T	U	C	S	T	U	C	S	T	U
		300×150×10		500	35	68	224	475	35	68	224	-	-	-	-	-	-	-	-
		450×175×10		510	30	93	228	490	30	93	228	580	32	77	248	580	32	77	248
		600×190×13		520	32	118	227	495	32	118	227	587	37	92	243	587	37	92	243
Min. Radius of Curvature(m)		For straight rails only																	
Weight(approx.) (kg)		970				1280				2180				2520					

Note : 1. Dimension of I-beam in      Sections are standard ones.  
 2. If Curved rail requires, this must be indicated in advance. Other I-beam also can be changing spacers.

※ KN         -C-H   Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Low-Head Type Creep Hoist with Motor-Driven Trolley




Model		KL 1-M	KL 2-M	KL 2,8-M	KL 3-M	KL 5-M												
Capacity(ton)		1	2	2.8	3	5												
Type	High Speed Traversing	C-KL 1 H6-MH	C-KL 2 H6-MH	C-KL 2,8 H6-MH	C-KL 3 H6-MH	C-KL 5 H6-MH												
	Low Speed Traversing	C-KL 1 H6-ML	C-KL 2 H6-ML	C-KL 2,8 H6-ML	C-KL 3 H6-ML	C-KL 5 H6-ML												
Hoist	Max. lift(m)		6	6	6	6												
	Hoisting Speed(m/min)	50(HZ)	10/1	8,4/0,84	7,5/0,75	7,5/0,75	4,7/0,47											
	High/Creep Speed	60(HZ)	12/1,2	10/1	9/0,9	9/0,9	5,6/0,56											
	Motor(KW×P)High/Creep Speed		2,4/0,4×4	3,7/0,4×4	4,8/1,1×4	5,5/1,1×4	5,5/1×6											
	Wire Rope	Construction	6×37	6×37	6×37	6×37	6×37											
Dial(mm)x No. of Ropes		6×4	8×4	9×4	9×4	11,2×4												
Brake		DC Magnet Disc Brake																
Traversing	Traversing Speed (m/min)	High Speed	50(HZ)	20	20	20	20	20										
		60(HZ)	24	24	24	24	24											
	Low Speed	50(HZ)	13	13	13	13	13											
		60(HZ)	16	16	16	16	16											
Traversing Motor (kw × P)		High Speed	0,4×4	0,75×4	0,75×4	0,75×4	0,75×4											
		Low Speed	0,2×6	0,5×6	0,5×6	0,5×6	0,5×6											
Dimensions (approx.) (mm)		H	550	620	620	620	800											
		A	680	740	840	840	940											
		B	510	765	765	765	820											
		C	450	450	495	510	585											
		D	290	385	400	565	635											
		G	255	260	260	260	275											
		K	200	225	225	225	275											
		E	330	375	375	375	425											
I-Beam and Spacing (mm)		a×b×c	S	T	U	S	T	U	S	T	U	S	T	U	S	T	U	
		200×100×7	38	46	144	33	46	172	-	-	-	-	-	-	-	-	-	-
		250×125×7,5	30	71	153	24	71	182	25	71	182	23	71	182	-	-	-	-
		300×150×13	28	96	155	22	96	182	23	96	182	23	96	182	37	86	224	-
		600×190×13	-	-	-	-	-	-	-	-	-	-	-	-	34	111	228	-
Min. Radius of Curvature(m)		1,5		1,8		1,8		1,8		2,8								
Weight(approx.) (kg)		275		440		545		545		775								

Note : Dimension of I-beam in      Sections are standard ones, Other I-beam also can be changing spacers,

※ KL         -C-H     Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Double Low-Head Type Creep Hoist with Motor-Driven Trolley



Model		KP 2,8-M	KP 3-M	KP 5-M	KP 7,5-M		
Capacity(ton)		2,8	3	5	7,5		
Type	High Speed Traversing	C-KP 2,8-H6-MH	C-KP 3-H6-MH	C-KP 5-H6-MH	C-KP 7,5-H6-MH		
	Low Speed Traversing	C-KP 2,8-H6-ML	C-KP 3-H6-ML	C-KP 5-H6-ML	C-KP 7,5-H6-ML		
Hoist	Max. lift(m)		6	6	6	6	
	Hoisting Speed(m/min)	50(HZ)	7,5/0,75	7,5/0,75	4,7/0,47	3,2/0,32	
		High/ Creep Speed 60(HZ)	9/0,9	9/0,9	5,6/0,65	3,8/0,38	
	Motor(KW×P)High/Creep Speed		4,8/1,1×4	5,5/1,1×4	5,5/1×6	5,5/1×6	
	Wire Rope	Construction	6×37	6×37	6×37	6×37	
		Dia(mm)× No. of Ropes	9×4	9×4	11,2×4	14×4	
Brake		DC Magnet Disc					
Traversing	Traversing Speed (m/min)	High Speed	50(HZ)	20	20	20	12,5
			60(HZ)	24	24	24	15
		Low Speed	50(HZ)	13	13	13	8,3
			60(HZ)	16	16	16	10
	Motor (kw × P)	High Speed	0,75×4	0,75×4	0,75×4	0,75×4	
		Low Speed	0,5×6	0,5×6	0,5×6	0,5×6	
Dimensions (approx.) (mm)		H	495	495	525	950	
		R	950	950	1150	1400	
		C	170	170	200	300	
		G	810	810	950	1015	
		K	550	550	620	870	
		W	650	650	772	1250	
		D	47	47	47	47	
		Q	170	170	195	195	
P	140	140	165	165			
Weight(approx.) (kg)		5400	7200	9050	9200		
Traversing Rail		37kg/m	50kg/m	50kg/m	50kg/m		


Note : Available lift height over 6 meters.

※ 10<sup>t</sup>, 15<sup>t</sup>, 20<sup>t</sup>, 30<sup>t</sup> Consult factory for specification.

※ KP □□□□-C-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Double-Rail Type Creep Hoist with Motor-Driven Trolley




Model		KD 2-M	KD 2,8-M	KD 3-M	KD 5-M	KD 7,5-M	KD 10-M	KD 15-M	KD 20-M	KD 30-M		
Capacity(ton)		2	2,8	3	5	7,5	10	15	20	30		
Type	High Speed Traversing	C-KD2-H12-MH	C-KD 2,8-H12-MH	C-KD 3-H12-MH	C-KD 5-H12-MH	C-KD 7,5-H12-MH	C-KD 10-H12-MH	C-KD 15-H12-MH	C-KD 20-H12-MH	C-KD 30-H12-MH		
	Low Speed Traversing	C-KD2-H12-ML	C-KD 2,8-H12-ML	C-KD 3-H12-ML	C-KD 5-H12-ML	C-KD 7,5-H12-ML	C-KD 10-H12-ML	C-KD 15-H12-ML	C-KD 20-H12-ML	C-KD 30-H12-ML		
Hoist	Max. lift(m)	12	12	12	12	12	12	12	12	12		
	Hoisting Speed(m/min)	50(HZ)	8,4/0,84	7,5/0,75	7,5/0,75	4,7/0,47	3,1/0,31	3,7/0,37	3,7/0,37	3,5/0,35	2,3/0,23	
		High/ Creep Speed	60(HZ)	10/1	9/0,9	9/0,9	5,6/0,56	3,8/0,38	4,5/0,45	4,5/0,45	4,2/0,42	2,8/0,28
	Motor(KW×P)High/Creep Speed		3,7/0,4×4	4,8/1,1×4	5,5/1,1×4	5,5/1×6	5,5/1×6	9/1,1×8	13/1,8×8	17/1,8×8	17/1,8×8	
	Wire Rope	Construction	6×37	6×37	6×37	6×37	6×37	6×37	6×37	6×37	6×37	
Dia(mm)× No. of Ropes		8×4	9×4	9×4	12,5×4	14×4	16×4	20×4	22,4×4	22,4×6		
Brake		DC Magnet Disc Brake										
Traversing	Traversing Speed (m/min)	High Speed	50(HZ)	20	20	20	20	12,5	12,5	12,5	12,5	12,5
			60(HZ)	24	24	24	24	15	15	15	15	15
		Low Speed	50(HZ)	13	13	13	13	8,3	8,3	8,3	8,3	8,3
			60(HZ)	16	16	16	16	10	10	10	10	10
Motor (kw × P)		High Speed	0,75×4	0,75×4	0,75×4	0,75×4	0,75×4	0,75×4	1,5×4	1,5×4	1,5×4 (2units)	
		Low Speed	0,5×6	0,5×6	0,5×6	0,5×6	0,5×6	0,5×6	1×6	1×6	1×6 (2units)	
Dimensions (approx.) (mm)		H	415	420	420	510	730	775	995	1175	1480	
		R	950	950	950	1150	1150	1150	1200	1300	1800	
		A	465	465	465	510	525	565	625	670	940	
		B	390	390	390	470	480	510	555	610	940	
		C	500	600	600	550	550	695	860	900	980	
		G	905	1020	1020	1170	1170	1230	1365	1460	1720	
		K	609	705	705	830	835	955	1005	1220	1480	
		W	650	650	650	760	800	865	920	1000	1540	
		S	45	45	45	42	42	42	30	30	55	
		D	47	47	47	47	58	58	58	58	70	
		L	680	690	690	890	850	850	870	935	1420	
		M	115	115	115	125	120	120	130	140	180	
N	90	90	90	110	95	100	130	140	180			
P	140	140	140	165	165	165	180	220	250			
Q	170	170	170	195	195	195	210	250	280			
Weight(approx.) (kg)		490	590	590	900	955	1265	1920	2385	3536		
Traversing Rail		15kg/m	15kg/m	15kg/m	15kg/m	15kg/m	15kg/m	15kg/m	22kg/m	30kg/m		

※ KD □□□□-C-H□□ Hoist Name Plate shall be typed as per above coding



# WIRE HOIST A Type

## Double-Rail Type Creep Hoist with Motor-Driven Trolley




Model		KD 35-M	KD 40-M	KD 50-M	KD 60-M	KD 70-M		
Capacity(ton)		35	40	50	60	70		
Type	High Speed Traversing	C-KD35-H12-MH	C-KD40-H12-MH	C-KD50-H12-MH	C-KD60-H12-MH	C-KD70-H12-MH		
	Low Speed Traversing	C-KD35-H12-ML	C-KD40-H12-ML	C-KD50-H12-ML	C-KD60-H12-ML	C-KD70-H12-ML		
Hoist	Max. lift(m)	12	12	12	12	12		
	Hoisting Speed(m/min) High/ Creep Speed	50(HZ)	4/0,4	2,7/0,27	2,7/0,27	2/0,2	2/0,2	
		60(HZ)	4,8/0,48	3,2/0,32	3,2/0,32	2,4/0,24	2,4/0,24	
	Motor(KW×P)High/Creep Speed		33/3,7×6/4	33/3,7×6/4	33/3,7×6/4	33/3,7×6/4	33/3,7×6/4	
	Wire Rope	Construction	6×Fi(25)	6×Fi(25)	6×Fi(25)	6×Fi(25)	6×Fi(25)	
Dia(mm)× No. of Ropes		28×4	28×6	28×6	28×8	28×8		
Brake		DC Magnet Disc Brake						
Traversing	Traversing Speed (m/min)	High Speed	50(HZ)	12,5	12,5	12,5	12,5	12,5
			60(HZ)	15	15	15	15	15
		Low Speed	50(HZ)	8,3	8,3	8,3	8,3	8,3
			60(HZ)	10	10	10	10	10
Motor (kw × P)		High Speed	2,2×4	2,2×4(2units)	2,2×4(2units)	2,2×4(2units)	3,7×4(2units)	
		Low Speed	1,5×6	1,5×6(2units)	1,5×6(2units)	1,5×6(2units)	2,2×6(2units)	
Dimensions (approx.) (mm)		H	1490	1680	1680	1780	1780	
		R	1600	2300	2300	2800	2800	
		A	1025	1432	1432	1525	1525	
		B	955	1243	1243	1150	1150	
		C	1013	1220	1220	1220	1220	
		G	1735	2060	2060	2310	2310	
		K	1360	1715	1715	1965	1965	
		W	1550	2125	2125	2125	2075	
		D	70	80	80	80	80	
		L	1044	1730	1730	1930	1930	
		M	215	275	275	275	300	
		N	215	275	275	275	300	
		P	355	450	450	450	500	
Q	355	490	490	490	540			
Weight(approx.) (kg)		5400	7200	7200	9050	9200		
Traversing Rail		37kg/m	50kg/m	50kg/m	50kg/m	50kg/m		

※ KD □□□□-C-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Double-Rail Type Main & Aux Hoist




Model		KA 5/3-M	KA 7,5/3-M	KA 10/5-M	KA 15/5-M					
Capacity(ton)		5/3	7,5/3	10/5	15/5					
Hoist	Max, lift(m)	12	12	12	12					
	Hoisting Speed (m/min)	High Speed 50/60(HZ)	4,7/5,6	7,5/9	3,1/3,8	7,5/9	3,7/4,5	4,7/5,6	3,7/4,5	4,7/5,6
		Low Speed 50/60(HZ)	3,5/4,2	3,7/4,5	2,3/2,8	3,7/4,5	2,5/3	3,5/4,2	2,5/3	3,5/4,2
	Hoisting Motor (kw X P)	High Speed	5,5X6	5,5X4	5,5X6	5,5X4	9X8	5,5X6	13X8	5,5X6
		Low Speed	4,2X8	2,8X8	4,2X8	2,8X8	6X12	4,2X8	8,5X12	4,2X8
	Wire Rope	Construction	6X37	6X37	6X37	6X37	6X37	6X37	6X37	6X37
Dia(mm)X No. of Ropes		12,5X4	12,5X2	14X4	12,5X2	16X4	16X2	20X4	16X2	
Brake		DC Magnet Disc Brake								
Traversing	Traversing Speed (m/min)	High Speed 50/60(HZ)	20/24	12,5/15	12,5/15	12,5/15				
		Low Speed 50/60(HZ)	13/16	8,3/10	8,3/10	8,3/10				
	Traversing Motor (kw X P)	High Speed	0,75X4	0,75X4	0,75X4	1,5X4				
		Low Speed	0,5X6	0,5X6	0,5X6	1X6				
Dimensions (approx.) (mm)	H1	510	730	775	995					
	H2	270	350	390	365					
	R	1150	1150	1150	1200					
	HD	485	570	600	645					
	A	370	420	460	425					
	B	365	390	400	450					
	C1	550	550	695	860					
	C2	845	725	905	930					
	G	935	925	975	1075					
	K	885	870	1060	1065					
	W	1220	1380	1460	1520					
	D	47	58	58	58					
	L	890	852	851	872					
	M	110	110	110	130					
	N	125	120	120	140					
	P	165	165	165	180					
Q	190	195	195	210						
Weight(approx.) (kg)		1285	1600	1830	2475					
Traversing Rail		15kg/m	15kg/m	15kg/m	22kg/m					

※ KA □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Double-Rail Type Main & Aux Hoist




Model		KA 20/5-M	KA 20/10-M	KA 30/10-M	KA 30/15-M	
Capacity(ton)		20/5	20/10	30/10	30/15	
Hoist	Max. lift(m)	12	12	12	12	
	Hoisting Speed (m/min)	High Speed 50/60(HZ)	3,5/4,2	4,7/5,6	3,5/4,2	3,7/4,5
		Low Speed 50/60(HZ)	2,5/2,8	3,5/4,2	2,5/4,2	2,5/3
	Hoisting Motor (kw X P)	High Speed	17X8	5,5X6	17X8	9X8
		Low Speed	11,5X12	4,2X8	11,5X12	6X12
Wire Rope	Construction	6X37	6X37	6X37	6X37	
	Dia(mm)X No. of Ropes	22,4X4	16X2	22,4X4	16X4	
Brake		DC Magnet Disc Brake				
Traversing	Traversing Speed (m/min)	High Speed 50/60(HZ)	12,5/15	12,5/15	12,5/15	
		Low Speed 50/60(HZ)	8,3/10	8,3/10	8,3/10	
	Traversing Motor (kw X P)	High Speed	1,5X4	1,5X4	1,5X4(2unts)	1,5X4(2unts)
		Low Speed	1X6	1X6	1X6(2unts)	1X6(2unts)
Dimensions (approx.) (mm)	H1	1175	1175	1480	1480	
	H2	350	425	430	615	
	R	1300	1300	1800	1800	
	HD	700	775	1010	1010	
	A	570	57	780	780	
	B	450	630	550	550	
	C1	900	900	980	980	
	C2	935	1180	995	1115	
	G	1165	1165	1425	1425	
	K	1210	1210	1480	1480	
	W	1720	1980	2340	2340	
	D	58	58	70	70	
	L	934	934	1418	1418	
	M	170	170	160	160	
	N	170	170	180	180	
P	220	220	280	280		
Q	250	250	280	280		
Weight(approx.) (kg)		2925	3475	4670	5200	
Traversing Rail		22kg/m	22kg/m	30kg/m	30kg/m	

※ KA □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Double-Rail Type Main & Aux Hoist




Model		KA 35/10-M	KA 50/10-M	KA 60/20-M	KA 70/20-M	
Capacity(ton)		35/10	50/10	60/20	70/20	
Hoist	Max, lift(m)	12		12		
	Hoisting Speed (m/min)	High Speed 50/60(HZ)	4/4,8	3,7/4,5	2,7/3,2	3,7/4,5
		Low Speed 50/60(HZ)		2,5/3		2,5/3
	Hoisting Motor (kw X P)	High Speed	33x6	9x8	33x6	9x8
		Low Speed		6x12		6x12
	Wire Rope	Construction	6xFi(25)	6x37	6xFi(25)	6x37
Dia(mm)X No. of Ropes		28x4	16x4	28x6	16x4	
Brake		DC Magnet Disc Brake				
Traversing	Traversing Speed (m/min)	High Speed 50/60(HZ)	12,5/15	12,5/15	12,5/15	
		Low Speed 50/60(HZ)	8,3/10	8,3/10	8,3/10	
	Traversing Motor (kw X P)	High Speed	2,2x4	2,2x4(2units)	2,2x4(2units)	3,7x4(2units)
		Low Speed	1,5x6	1,5x6(2units)	1,5x6(2units)	2,2x6(2units)
Dimensions (approx.) (mm)	H1	1490	1680	1780	1780	
	H2	420	50	330	330	
	R	1600	2300	2800	2800	
	HD	1100	1300	1378	1378	
	A	740	968	968	968	
	B	560	657	579	579	
	C1	1013	1220	1220	1220	
	C2	1333	1460	1750	1750	
	G	1455	1780	2030	2030	
	K	1360	1715	1965	1965	
	W	2400	2925	2925	2925	
	D	70	80	80	80	
	L	1044	1430	1930	1930	
	M	215	27	275	275	
	N	215	275	275	275	
	P	355	450	450	500	
Q	395	490	490	540		
Weight(approx.) (kg)		6400	8200	10930	11080	
Traversing Rail		37kg/m	50kg/m	50kg/m	50kg/m	

※ KA □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Double-Rail Type Creep Main & Aux Hoist




Model		KA 5/3-M	KA 7.5/3-M	KA 10/5-M	KA 15/5-M					
Capacity(ton)		5/3	7.5/3	10/5	15/5					
Hoist	Max. lift(m)	12	12	12	12					
	Hoisting Speed (m/min)	50HZ	4,7/0,47	7,5/0,75	3,1/0,31	7,5/0,75	3,7/0,37	4,7/0,47	3,7/0,37	4,7/0,47
		60HZ	5,6/0,56	9/0,9	3,8/0,38	9/0,9	4,5/0,45	5,6/0,56	4,5/0,45	5,6/0,56
	Hoisting Motor (kw X P)	High Speed	5,5/1x6	5,5/1,1x4	5,5/1x6	5,5/1,1x4	9/1,1x8	5,5/1x6	13/1,8x8	5,5/1x6
		Low Speed								
Wire Rope	Construction	6x37	6x37	6x37	6x37	6x37	6x37	6x37	6x37	
	Dia(mm)X No. of Ropes	12,5x4	12,5x2	14x4	12,5x2	16x4	16x2	20x4	16x2	
Brake		DC Magnet Disc Brake								
Traversing	Traversing Speed (m/min)	High Speed 50/60(HZ)	20/24	12,5/15	12,5/15	12,5/15	12,5/15	12,5/15	12,5/15	
		Low Speed 50/60(HZ)	13/16	8,3/10	8,3/10	8,3/10	8,3/10	8,3/10	8,3/10	
	Traversing Motor (kw X P)	High Speed	0,75x4	0,75x4	0,75x4	0,75x4	0,75x4	1,5x4	1,5x4	
		Low Speed	0,5x6	0,5x6	0,5x6	0,5x6	0,5x6	1x6	1x6	
Dimensions (approx.) (mm)	H1	510	730	775	995					
	H2	270	350	390	365					
	R	1150	1150	1150	1200					
	HD	485	570	600	645					
	A	370	420	460	425					
	B	365	390	400	450					
	C1	550	550	695	860					
	C2	845	725	905	930					
	G	1170	1185	1275	1385					
	K	885	870	1060	165					
	W	1220	1380	1460	1520					
	D	47	58	58	58					
	L	890	852	851	872					
	M	110	110	110	130					
	N	125	120	120	140					
	P	165	165	165	180					
Q	190	195	195	210						
Weight(approx.) (kg)		1385	1690	1950	2605					
Traversing Rail		15kg/m	15kg/m	15kg/m	22kg/m					

※ KA □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Double-Rail Type Creep Main & Aux Hoist





Model		KA 20/5-M	KA 20/10-M	KA 30/10-M	KA 30/15-M					
Capacity(ton)		20/5	20/10	30/10	30/15					
Hoist	Max, lift(m)	12	12	12	12					
	Hoisting Speed (m/min)	50HZ	3,5/0,35	4,7/0,47	3,5/0,35	3,7/0,37	2,3/0,23	3,7/0,37	2,3/0,23	3,7/0,37
		60HZ	4,2/0,42	5,6/0,56	4,2/0,42	4,5/0,45	2,8/0,28	4,5/0,45	2,8/0,28	4,5/0,45
	Hoisting Motor (kw X P)	High Speed	17/1,8X8	5,5/1X6	17/1,8X8	9/1,1X8	17/1,8X8	9/1,1X8	17/1,8X8	13/1,8X8
		Low Speed								
Wire Rope	Construction	6X37	6X37	6X37	6X37	6X37	6X37	6X37	6X37	
	Dia(mm)X No. of Ropes	22,4X4	16X2	22,4X4	16X4	22,4X6	16X4	22,4X6	20X4	
Brake		DC Magnet Disc Brake								
Traversing	Traversing Speed (m/min)	High Speed 50/60(HZ)	12,5/15	12,5/15	12,5/15	12,5/15	12,5/15	12,5/15	12,5/15	
		Low Speed 50/60(HZ)	8,3/10	8,3/10	8,3/10	8,3/10	8,3/10	8,3/10	8,3/10	
	Traversing Motor (kw X P)	High Speed	1,5X4	1,5X4	1,5X4	1,5X4(2units)	1,5X4(2units)	1,5X4(2units)	1,5X4(2units)	
		Low Speed	1X6	1X6	1X6	1X6(2units)	1X6(2units)	1X6(2units)	1X6(2units)	
Dimensions (approx.) (mm)	H1	1175	1175	1480	1480					
	H2	350	425	430	615					
	R	1300	1300	1800	1800					
	HD	700	775	1010	1010					
	A	570	575	780	780					
	B	450	630	550	550					
	C1	900	900	980	980					
	C2	935	1180	995	1115					
	G	1480	1480	1740	1740					
	K	1210	1210	1470	1470					
	W	1720	1980	2340	2340					
	D	58	58	70	70					
	L	934	934	1418	1418					
	M	170	170	160	160					
	N	170	170	180	180					
	P	220	220	250	250					
Q	250	250	280	280						
Weight(approx.) (kg)		3070	3600	4820	5320					
Traversing Rail		22kg/m	22kg/m	30kg/m	30kg/m					

※ KA □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST A Type

## Double-Rail Type Creep Main & Aux Hoist



Model		KA 35/10-M	KA 50/10-M	KA 60/20-M	KA 70/20-M					
Capacity(ton)		35/10	50/10	60/20	70/20					
Hoist	Max. lift(m)	12	12	12	12					
	Hoisting Speed (m/min)	50HZ	4/0,4	3,7/0,37	2,7/0,27	3,7/0,37	2/0,2	3,5/0,5	2/0,2	3,5/0,5
		60HZ	4,8/0,48	4,5/0,45	3,2/0,32	4,5/0,45	2,4/0,24	4,2/0,42	2,4/0,24	4,2/0,42
	Hoisting Motor (kw X P)	High Speed	33/3,7×6/4	9/1,1×8	33/3,7×6/4	9/1,1×8	33/3,7×6/4	17/1,8×8	33/3,7×6/4	17/1,8×8
		Low Speed								
Wire Rope	Construction	6×Fi(25)	6×37	6×Fi(25)	6×37	6×Fi(25)	6×37	6×Fi(25)	6×37	
	Dia(mm)X No. of Ropes	28×4	16×4	28×6	16×4	28×8	22,4×4	28×8	22,4×4	
Brake		DC Magnet Disc Brake								
Traversing	Traversing Speed (m/min)	High Speed 50/60(HZ)	12,5/15	12,5/15	12,5/15	12,5/15	12,5/15	12,5/15	12,5/15	
		Low Speed 50/60(HZ)	8,3/10	8,3/10	8,3/10	8,3/10	8,3/10	8,3/10	8,3/10	
	Traversing Motor (kw X P)	High Speed	2,2×4	2,2×4(2units)	2,2×4(2units)	2,2×4(2units)	2,2×4(2units)	2,2×4(2units)	3,7×4(2units)	
		Low Speed	1,5×6	1,5×6(2units)	1,5×6(2units)	1,5×6(2units)	1,5×6(2units)	1,5×6(2units)	2,2×6(2units)	
Dimensions (approx.) (mm)	H1	1490	1680	1780	1780					
	H2	420	50	330	330					
	R	1600	2300	2800	2800					
	HD	1100	1300	1378	1378					
	A	740	968	968	968					
	B	560	657	579	579					
	C1	1013	1220	1220	1220					
	C2	1333	1460	1750	1750					
	G	1735	2060	2310	2310					
	K	1360	1715	1965	1965					
	W	2400	2925	2925	2925					
	D	70	80	80	80					
	L	1044	1430	1930	1930					
	M	215	275	275	275					
	N	215	275	275	275					
P	355	450	450	500						
Q	395	490	490	540						
Weight(approx.) (kg)		6700	8500	11290	11440					
Traversing Rail		37kg/m	50kg/m	50kg/m	50kg/m					


※ KA □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding



# WIRE HOIST Wide-Flange Type

## Regular Type – Normal/Creep (0.5~5ton)

### Normal




CAPACITY(TON)		1/2				1				2				2,8				3				5							
TYPE	HIGH SPEED TRAVERSING	KN0,5-H6(12)-MH				KN1-H6(12)-MH				KN2-H6(12)-MH				KN2,8-H6(12)-MH				KN3-H6(12)-MH				KN3-H6(12)-MH							
	LOW SPEED TRAVERSING	KN0,5-H6(12)-ML				KN1-H6(12)-ML				KN2-H6(12)-ML				KN2,8-H6(12)-ML				KN3-H6(12)-ML				KN3-H6(12)-ML							
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(I-BEAM)	C	S	T	U	C	S	T	U	C	S	T	U	C	S	T	U	C	S	T	U	C	S	T	U	C	S	T	U
	I-200x100x7	385	150	38	46	385	170	38	46	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	I-250x125x7,5	395	150	30	71	395	170	30	71	445	205	24	71	445	210	23	71	445	210	23	71	455	250	398	61	-	-	-	-
	I-300x150x10	410	150	28	96	410	170	28	96	460	205	24	96	460	210	23	96	460	210	23	96	465	250	37	86	-	-	-	-
I-450x175x13	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	480	250	34	111	
DIMENSIONS(APPROX.)(MM)	H	705(745)				815(855)				980(1020)				1115(1155)				1115(1155)				1325(1365)							
H-BEAM,BOX TYPE DIMENSIONS (APPROX.)(MM)	ax200x100x16	435	29	146	153	435	29	146	153	528	28	146	190	527	27	146	190	527	27	146	190	548	36	136	230	-	-	-	-
	ax250x150x19	460	26	196	156	460	26	196	156	553	25	196	193	552	24	196	193	552	24	196	193	573	33	186	233	-	-	-	-
	ax300x200x22	485	23	246	159	485	23	246	159	578	22	246	196	577	21	246	196	577	21	246	196	598	30	236	236	-	-	-	-
	ax400x300x25	510	20	346	162	510	20	346	162	603	19	346	199	627	18	346	199	627	18	346	199	648	27	336	239	-	-	-	-
WEIGHT(APPROX.)(KG)		162(182)				205(233)				298(334)				399(443)				399(443)				607(642)							

※ KN □□□□-N-H□□-W Hoist Name Plate shall be typed as per above coding

※ Other specifications are the same as 38 page.

### Creep



CAPACITY(TON)		1				2				2,8				3				5							
TYPE	HIGH SPEED TRAVERSING	C-KN1-H6(12)-MH				C-KN2-H6(12)-MH				C-KN2,8-H6(12)-MH				C-KN3-H6(12)-MH				C-KN5-H6(12)-MH							
	LOW SPEED TRAVERSING	C-KN1-H6(12)-ML				C-KN2-H6(12)-ML				C-KN2,8-H6(12)-ML				C-KN3-H6(12)-ML				C-KN5-H6(12)-ML							
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(I-BEAM)	C	S	T	U	C	S	T	U	C	S	T	U	C	S	T	U	C	S	T	U	C	S	T	U
	I-200x100x7	395	38	46	144	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	I-250x125x7,5	395	30	71	153	445	26	71	183	445	25	71	182	445	25	71	182	455	37	61	222	-	-	-	-
	I-300x150x10	410	28	96	156	460	24	96	182	460	23	96	182	460	23	96	182	465	32	86	224	-	-	-	-
I-450x175x13	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	480	32	111	228	-	-	-	-	
DIMENSIONS(APPROX.)(MM)	H	815(855)				980(1020)				1115(1155)				1115(1155)				1325(1365)							
H-BEAM,BOX TYPE DIMENSIONS (APPROX.)(MM)	ax200x100x16	435	29	146	153	528	28	146	190	527	27	146	190	527	27	146	190	548	36	136	230	-	-	-	-
	ax250x150x19	460	26	196	156	553	25	196	193	552	24	196	193	552	24	196	193	573	33	186	233	-	-	-	-
	ax300x200x22	485	23	246	159	578	22	246	196	577	21	246	196	577	21	246	196	598	30	236	236	-	-	-	-
	ax400x300x25	510	20	346	162	603	19	346	199	627	18	346	199	627	18	346	199	648	27	336	239	-	-	-	-
WEIGHT(APPROX.)(KG)		240(260)				340(375)				440(485)				440(485)				665(730)							


※ KN □□□□-C-H□□-W Hoist Name Plate shall be typed as per above coding

※ Other specifications are the same as 46 page.

# WIRE HOIST Wide-Flange Type

## Regular Type – Normal/Creep (7.5~20ton)

### Normal




CAPACITY(TON)		7,5				10				15				20			
TYPE	HIGH SPEED TRAVERSING	KN7,5-H6(12)-MH				KN10-H6(12)-MH				KN15-H6(12)-MH				KN20-H6(12)-MH			
	LOW SPEED TRAVERSING	KN7,5-H6(12)-ML				KN10-H6(12)-ML				KN15-H6(12)-ML				KN20-H6(12)-ML			
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(I-BEAM)	C	S	T	U	C	S	T	U	C	S	T	U	C	S	T	U
	I-300x150x10	500	35	68	224	485	35	68	224	-	-	-	-	-	-	-	-
	I-450x175x13	510	20	93	228	490	30	93	228	580	32	77	248	580	32	77	248
	I-600x190x13	520	25	118	232	495	25	118	232	590	32	92	248	590	32	92	248
DIMENSIONS(APPROX.)(MM)	H	1510				1570				1930				2175			
H-BEAM,BOX TYPE DIMENSIONS (APPROX.)(MM)	ax250x110x25	577	35	168	239	577	35	168	239	690	35	152	260	690	35	152	260
	ax300x160x28	602	32	218	242	602	32	218	242	715	32	177	263	715	32	177	263
	ax400x260x30	652	30	318	244	652	30	318	244	765	30	227	265	765	30	227	265
	ax500x360x35	702	25	418	249	702	25	418	249	815	25	277	270	815	25	277	270
WEIGHT(APPROX.)(KG)		930				1240				2065				2470			

※ KN □□□□-N-H□□-W Hoist Name Plate shall be typed as per above coding

※ Other specifications are the same as 39 page.

### Creep



CAPACITY(TON)		7,5				10				15				20			
TYPE	HIGH SPEED TRAVERSING	C-KN7,5-H6(12)-MH				C-KN10-H6(12)-MH				C-KN15-H6(12)-MH				C-KN20-H6(12)-MH			
	LOW SPEED TRAVERSING	C-KN7,5-H6(12)-ML				C-KN10-H6(12)-ML				C-KN15-H6(12)-ML				C-KN20-H6(12)-ML			
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(I-BEAM)	C	S	T	U	C	S	T	U	C	S	T	U	C	S	T	U
	I-300x150x10	500	35	68	224	475	35	68	224	-	-	-	-	-	-	-	-
	I-450x175x13	510	30	93	228	490	30	93	228	580	32	77	248	580	32	77	248
	I-600x190x13	520	32	118	227	495	32	118	227	587	37	92	243	587	37	92	243
DIMENSIONS(APPROX.)(MM)	H	1510				1570				1930				2175			
H-BEAM,BOX TYPE DIMENSIONS (APPROX.)(MM)	ax250x110x25	577	35	168	239	577	35	168	239	690	35	152	260	690	35	152	260
	ax300x160x28	602	32	218	242	602	32	218	242	715	32	177	263	715	32	177	263
	ax400x260x30	652	30	318	244	652	30	318	244	765	30	227	265	765	30	227	265
	ax500x360x35	702	25	418	249	702	25	418	249	815	25	277	270	815	25	277	270
WEIGHT(APPROX.)(KG)		970				1310				2215				2560			


※ KN □□□□-C-H□□-W Hoist Name Plate shall be typed as per above coding

※ Other specifications are the same as 47 page.

# WIRE HOIST Wide-Flange Type

## Low Head Type – Normal/Creep (0.5~5ton)

### Normal




CAPACITY(TON)		1/2			1			2			2,8			3			5		
TYPE	HIGH SPEED TRAVERSING	KL0,5-H6-MH			KL1-H6-MH			KL2-H6-MH			KL2,8-H6-MH			KL3-H6-MH			KL5-H6-MH		
	LOW SPEED TRAVERSING	KL0,5-H6-ML			KL1-H6-ML			KL2-H6-ML			KL2,8-H6-ML			KL3-H6-ML			KL5-H6-ML		
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(I-BEAM)	S	T	U	S	T	U	S	T	U	S	T	U	S	T	U	S	T	U
	I-200x100x7	38	46	144	38	46	144	-	-	-	-	-	-	-	-	-	-	-	-
	I-250x125x7,5	30	71	153	30	71	153	22	71	182	23	71	182	22	371	182	-	-	-
	I-300x150x13	28	96	155	30	71	153	22	96	182	23	96	182	23	96	182	26	86	224
DIMENSIONS(APPROX.)(MM)	H	600			600			670			670			670			870		
	H-BEAM,BOX TYPE DIMENSIONS (APPROX.)(MM)	ax200x100x16	39	146	153	39	146	153	29	146	190	30	146	190	30	146	190	35	136
H-BEAM,BOX TYPE DIMENSIONS (APPROX.)(MM)	ax250x150x19	36	196	156	36	196	156	26	196	193	27	196	193	27	196	193	32	186	233
	ax300x200x22	33	246	159	33	246	159	23	246	196	24	246	196	24	246	196	29	236	236
	ax400x300x25	30	346	162	30	346	162	20	296	199	21	346	199	21	346	199	26	336	239
WEIGHT(APPROX.)(KG)		190			220			375			470			470			770		

※ KL □□□□-N-H□□-W Hoist Name Plate shall be typed as per above coding

※ Other specifications are the same as 43 page.

### Creep




CAPACITY(TON)		1			2			2,8			3			5		
TYPE	HIGH SPEED TRAVERSING	C-KL1-H6-MH			C-KL2-H6-MH			C-KL2,8-H6-MH			C-KL3-H6-MH			C-KL5-H6-MH		
	LOW SPEED TRAVERSING	C-KL1-H6-ML			C-KL2-H6-ML			C-KL2,8-H6-ML			C-KL3-H6-ML			C-KL5-H6-ML		
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(I-BEAM)	S	T	U	S	T	U	S	T	U	S	T	U	S	T	U
	I-200x100x7	38	46	144	33	46	172	-	-	-	-	-	-	-	-	-
	I-250x125x7,5	30	71	153	24	71	182	25	71	182	23	71	182	-	-	-
	I-300x150x13	28	96	155	22	96	182	23	96	182	23	96	182	37	86	224
DIMENSIONS(APPROX.)(MM)	H	600			670			670			670			870		
	H-BEAM,BOX TYPE DIMENSIONS (APPROX.)(MM)	ax200x100x16	39	146	153	29	146	190	30	146	190	30	146	190	35	136
H-BEAM,BOX TYPE DIMENSIONS (APPROX.)(MM)	ax250x150x19	36	196	156	26	196	193	27	196	193	27	196	193	32	186	233
	ax300x200x22	33	246	159	23	246	196	24	246	196	24	246	196	29	236	236
	ax400x300x25	30	346	162	20	296	199	21	346	199	21	346	199	26	336	239
WEIGHT(APPROX.)(KG)		290			460			570			570			805		

※ KL □□□□-C-H□□-W Hoist Name Plate shall be typed as per above coding

※ Other specifications are the same as 48 page.

# WIRE HOIST **Wide-Flange Type**

## Low Head Type – Normal (7.5~10ton)




CAPACITY(TON)		7,5			10			
TYPE	HIGH SPEED TRAVERSING	KL7,5-H6-MH			KL10-H6-MH			
	LOW SPEED TRAVERSING	KL7,5-H6-ML			KL10-H6-ML			
HOIST	MAX. LIFT(M)		6			6		
	HOISTING SPEED (M/MIN)	HIGH SPEED 50/60(Hz)	3,1/3,8			3,7/4,5		
		LOW SPEED 50/60(Hz)	2,3/2,8			2,5/3,0		
	HOISTING MOTOR (KW x P)	HIGH SPEED	5,5x6			9x8		
		LOW SPEED	4,2x8			6x12		
	WIRE ROPE	CONSTRUCTION	6x37			6x37		
DIA OF ROPE		14x4			16x4			
BRAKE		DC MAGNET DISC						
TRAVERSING	TRAVERSING SPEED (M/MIN)	HIGH SPEED 50/60(Hz)	12,5/15			12,5/15		
		LOW SPEED 50/60(Hz)	8,3/10			8,3/10		
	TRAVERSING MOTOR (KWxP)	HIGH SPEED	0,75x4			0,75x4		
		LOW SPEED	0,5x6			0,5x6		
DIMENSIONS(APPROX)(MM)		H	1250			1290		
		A	845			905		
		B	789			885		
		C	720			750		
		D	660			690		
		G	300			300		
		K	375			375		
		E	323			323		
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(I-BEAM)	S	T	U	S	T	U	
	I-450x175x13	32	77	248	37	92	243	
	I-600x190x13	37	92	243	37	92	243	
H-BEAM,BOX TYPE DIMENSIONS (APPROX.)(MM)	ax250x110x25	35	152	260	35	152	260	
	ax300x160x28	32	202	263	32	202	263	
	ax400x260x30	30	302	265	30	302	265	
	ax500x360x35	25	402	270	25	402	270	
WEIGHT(APPROX.)(KG)		860			1160			

※ KL □□□□-N-H□□-W Hoist Name Plate shall be typed as per above coding

# WIRE HOIST Wide-Flange Type


## Low Head Type – Creep (7.5~10ton)



CAPACITY(TON)		7.5			10			
TYPE	HIGH SPEED TRAVERSING	C-KL7,5-H6-MH			C-KL10-H6-MH			
	LOW SPEED TRAVERSING	C-KL7,5-H6-ML			C-KL10-H6-ML			
HOIST	MAX. LIFT(M)		6			6		
	HOISTING SPEED(M/MIN) HIGH/CREEP SPEED		50Hz	3,1/0,31		3,7/0,37		
			60HZ	3,8/0,38		4,5/0,45		
	HOISTING MOTOR (KW x P)		HIGH SPEED	5,5x6		9x8		
			CREEP SPEED	1,0x6		1,1x8		
	WIRE ROPE		CONSTRUCTION	6x37		6x37		
DIA OF ROPE			14x4		16x4			
BRAKE		DC MAGNET DISC						
TRAVERSING	TRAVERSING SPEED (M/MIN)		HIGH SPEED 50/60(Hz)	12,5/15		12,5/15		
			LOW SPEED 50/60(Hz)	8,3/10		8,3/10		
	TRAVERSING MOTOR (KWxP)		HIGH SPEED	0,75x4		0,75x4		
			LOW SPEED	0,5x6		0,5x6		
DIMENSIONS(APPROX)(MM)		H	1250		1290			
		A	1099		1205			
		B	789		885			
		C	720		750			
		D	660		690			
		G	300		300			
		K	375		375			
		E	323		323			
F	800		985					
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)		axbxt(I-BEAM)	S	T	U	S	T	U
		I-450x175x13	32	77	248	37	92	243
		I-600x190x13	37	92	243	37	92	243
H-BEAM,BOX TYPE DIMENSIONS (APPROX.)(MM)		ax250x110x25	35	152	260	35	152	260
		ax300x160x28	32	202	263	32	202	263
		ax400x260x30	30	302	265	30	302	265
		ax500x360x35	25	402	270	25	402	270
WEIGHT(APPROX.)(KG)		920			1230			


※ KL □□□□-C-H□□-W Hoist Name Plate shall be typed as per above coding

# MEMO



# WIRE HOIST **Special Type**

## Regular Type – Normal (4~10ton)




Capacity(Ton)		4					6					8					10					
Type	Hoisting Speed	High-High	KSN04-H06-MH					KSN06-H06-MH					KSN08-H06-MH					KSN10-H06-MH				
		High-Low	KSN04-H06-ML					KSN06-H06-ML					KSN08-H06-ML					KSN10-H06-ML				
		Low-High	KSN04-L06-MH					KSN06-L06-MH					KSN08-L06-MH					KSN10-L06-MH				
		Low-Low	KSN04-L06-ML					KSN06-L06-ML					KSN08-L06-ML					KSN10-L06-ML				
Hoist	Max. Lift(m)		6(12)					6(12)					6(12)					6(12)				
	Hoisting Speed (m/min)	High Speed 50/60(Hz)	4,2/5,0					3,8/4,5					2,3/2,8					2,3/2,8				
		Low Speed 50/60(Hz)	2,1/2,5					2,0/2,3					1,8/2,1					1,8/2,1				
	Hoisting Motor (Kw x P)	High Speed	3,7x4					5,5x4					5,5x6					5,5x6				
		Low Speed	1,8x8					2,8x8					4,2x8					4,2x8				
	Wire Rope	Construction	6x37					6x37					6x37					6x37				
Dia.(min)x no. of Ropes		Ø10x4 Falls					Ø12,5x4 Falls					Ø14x4 Falls					Ø16x4 Falls					
Brake		DC Magnet Disc Brake																				
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24					20/24					20/24					20/24				
		Low Speed 50/60(Hz)	13/16					13/16					13/16					13/16				
	Traversing Motor (Kw x P)	High Speed	0,75x4					0,75x4					0,75x4					0,75x4				
		Low Speed	0,5x6					0,5x6					0,5x6					0,5x6				
Brake		DC Magnet Disc Brake																				
Dimensions(approx)(mm)	H	1050					1050					1390					1390					
	A	504(701)					564(771)					580(772)					606(821)					
	B	588(785)					598(805)					685(877)					711(926)					
	D	425					475					540					560					
	G	520(920)					550(960)					530(910)					580(1010)					
	M	260					260					275					275					
	N	225					225					275					275					
	L	67(186)					67(274)					65(203)					55(270)					
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(I-BEAM)	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	
	I-300x150x19t~	515	267	24	96	182	515	267	23	96	122	-	-	-	-	-	-	-	-	-	-	
	I-450x175x26t~	528	267	22	121	127	528	267	21	121	127	535	351	34	111	228	535	351	34	111	228	
	I-600x190x25t~	-	-	-	-	-	-	-	-	-	-	543	351	32	118	230	543	351	32	118	230	
H-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(H-BEAM)	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	
	H-Hx150x20t~	515	267	24	96	184	515	267	21	121	182	-	-	-	-	-	-	-	-	-	-	
	H-Hx200x26t~	540	267	21	146	191	540	267	15	171	191	535	351	31	111	232	560	351	34	128	231	
	H-Hx300x30t~	-	-	-	-	-	-	-	-	-	-	560	351	27	211	236	610	351	28	228	235	
Min.Radius of curvature(m)		For Straight Only(Curvature Hinge Type Option)																				
Weight(approx)(kg)		334(374)					404(480)					658(720)					678(740)					

※ KSN □□□□-N-H□□-W Hoist Name Plate shall be typed as per above coding



# WIRE HOIST **Special Type**

## Double Low Head Type – Normal (4~10ton)




Capacity(Ton)		4	6	8	10	
Type	Hoisting Speed	High-High	KSD04-H12-MH	KSD06-H12-MH	KSD08-H12-MH	KSD10-H12-MH
		High-Low	KSD04-H12-ML	KSD06-H12-ML	KSD08-H12-ML	KSD10-H12-ML
		Low-High	KSD04-L12-MH	KSD06-L12-MH	KSD08-L12-MH	KSD10-L12-MH
		Low-Low	KSD04-L12-ML	KSD06-L12-ML	KSD08-L12-ML	KSD10-L12-ML
Hoist	Max. Lift(m)		12	12	12	12
	Hoisting Speed (m/min)	High Speed 50/60(Hz)	4,2/5,0	3,8/4,5	2,3/2,8	2,3/2,8
		Low Speed 50/60(Hz)	2,1/2,5	2,0/2,3	1,8/2,1	1,8/2,1
	Hoisting Motor (Kw x P)	High Speed	3,7x4	5,5x4	5,5x6	5,5x6
		Low Speed	1,8x8	2,8x8	4,2x8	4,2x8
	Wire Rope	Construction	6x37	6x37	6x37	6x37
Dia.(min)x no. of Ropes		Ø10x4 Falls	Ø12,5x4 Falls	Ø14x4 Falls	Ø16x4 Falls	
Brake		DC Magnet Disc Brake				
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24	20/24	20/24	20/24
		Low Speed 50/60(Hz)	13/16	13/16	13/16	13/16
	Traversing Motor (Kw x P)	High Speed	0,75x4	0,75x4	0,75x4	0,75x4
		Low Speed	0,5x6	0,5x6	0,5x6	0,5x6
Brake		DC Magnet Disc Brake				
Dimensions(approx.)(mm)	H	510	510	755	755	
	R	1150	1150	1150	1150	
	A	560	560	705	705	
	B	560	560	705	705	
	C	430	430	615	615	
	G	786	830	874	926	
	K	702	746	769	821	
	W	850	850	1070	1070	
	D	47	47	58	58	
	L	767	798	732	824	
	M	135	135	170	170	
	N	135	135	170	170	
	P	Ø165	Ø165	Ø165	Ø165	
	Q	Ø195	Ø165	Ø195	Ø195	
T	334	334	374	382		
S	519	536	472	537		
Weight(approx.)(kg)		490	590	910	925	
Rail(kg/m)		15 Kg/M	15 Kg/M	15 Kg/M	15 Kg/M	

※ KSD □□□□-N-H□□-W Hoist Name Plate shall be typed as per above coding

# WIRE HOIST **Special Type**

## Low Head Type – Normal (4~10ton)




Capacity(Ton)		4		6		8		10													
Type	Hoisting Speed	High-High	KSL04-H06-MH		KSL06-H06-MH		KSL08-H06-MH		KSL10-H06-MH												
		High-Low	KSL04-H06-ML		KSL06-H06-ML		KSL08-H06-ML		KSL10-H06-ML												
		Low-High	KSL04-L06-MH		KSL06-L06-MH		KSL08-L06-MH		KSL10-L06-MH												
		Low-Low	KSL04-L06-ML		KSL06-L06-ML		KSL08-L06-ML		KSL10-L06-ML												
Hoist	Max. Lift(m)		6(12)		6(12)		6(12)		6(12)												
	Hoisting Speed (m/min)	High Speed 50/60(Hz)	4,2/5,0		3,8/4,5		2,3/2,8		2,3/2,8												
		Low Speed 50/60(Hz)	2,1/2,5		2,0/2,3		1,8/2,1		1,8/2,1												
	Hoisting Motor (Kw x P)	High Speed	3,7x4		5,5x4		5,5x6		5,5x6												
		Low Speed	1,8x8		2,8x8		4,2x8		4,2x8												
	Wire Rope	Construction	6x37		6x37		6x37		6x37												
Dia.(min)x no. of Ropes		Ø10x4 Falls		Ø12,5x4 Falls		Ø14x4 Falls		Ø16x4 Falls													
Brake		DC Magnet Disc Brake																			
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24		20/24		20/24		20/24												
		Low Speed 50/60(Hz)	13/16		13/16		13/16		13/16												
	Traversing Motor (Kw x P)	High Speed	0,75x4		0,75x4		0,75x4		0,75x4												
		Low Speed	0,5x6		0,5x6		0,5x6		0,5x6												
Brake		DC Magnet Disc Brake																			
Dimensions(approx)(mm)	H	600		600		800		800													
	A	534(731)		594(801)		610(802)		636(851)													
	B	588(785)		598(805)		685(877)		711(926)													
	G	770(1170)		790(1200)		770(1160)		830(1260)													
	M	203(200)		203(205)		300(297)		296(296)													
	N	149(146)		199(201)		225(222)		221(221)													
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(I-BEAM)	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U
	I-300x150x19t~	565	585	25	68	266	565	585	25	68	266	-	-	-	-	-	-	-	-	-	-
	I-450x175x26t~	578	598	18	93	273	578	598	18	93	273	683	683	20	93	333	683	683	20	93	333
	I-600x190x25t~	-	-	-	-	-	-	-	-	-	-	691	691	19	108	332	691	691	19	108	332
H-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(H-BEAM)	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U
	H-Hx150x20t~	565	585	25	68	265	565	585	25	68	265	-	-	-	-	-	-	-	-	-	-
	H-Hx200x26t~	590	610	19	118	271	590	610	19	118	271	696	696	20	118	327	696	696	20	118	327
	H-Hx300x30t~	-	-	-	-	-	-	-	-	-	-	746	746	16	218	331	746	746	16	218	331
Min.Radius of curvature(m)		For Straight Only																			
Weight(approx)(kg)		349(389)		419(495)		678(740)		698(760)													

※ KSL □□□□-N-H□□-W Hoist Name Plate shall be typed as per above coding

# WIRE HOIST **Special Type**

## Double Rail Type – Normal (4~10ton)




Capacity(Ton)		4	6	8	10	
Type	Hoisting Speed	High-High	KSD04-H12-MH	KSD06-H12-MH	KSD08-H12-MH	KSD10-H12-MH
		High-Low	KSD04-H12-ML	KSD06-H12-ML	KSD08-H12-ML	KSD10-H12-ML
		Low-High	KSD04-L12-MH	KSD06-L12-MH	KSD08-L12-MH	KSD10-L12-MH
		Low-Low	KSD04-L12-ML	KSD06-L12-ML	KSD08-L12-ML	KSD10-L12-ML
Hoist	Max. Lift(m)		12	12	12	12
	Hoisting Speed (m/min)	High Speed 50/60(Hz)	4,2/5,0	3,8/4,5	2,3/2,8	2,3/2,8
		Low Speed 50/60(Hz)	2,1/2,5	2,0/2,3	1,8/2,1	1,8/2,1
	Hoisting Motor (Kw x P)	High Speed	3,7x4	5,5x4	5,5x6	5,5x6
		Low Speed	1,8x8	2,8x8	4,2x8	4,2x8
	Wire Rope	Construction	6x37	6x37	6x37	6x37
Dia.(min)x no. of Ropes		Ø10x4 Falls	Ø12,5x4 Falls	Ø14x4 Falls	Ø16x4 Falls	
Brake		DC Magnet Disc Brake				
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24	20/24	20/24	20/24
		Low Speed 50/60(Hz)	13/16	13/16	13/16	13/16
	Traversing Motor (Kw x P)	High Speed	0,75x4	0,75x4	0,75x4	0,75x4
		Low Speed	0,5x6	0,5x6	0,5x6	0,5x6
Brake		DC Magnet Disc Brake				
Dimensions(approx)(mm)	H	350	350	580	580	
	R	1150	1150	1150	1150	
	A	544	544	654	654	
	B	528	528	638	638	
	C	580	620	750	750	
	G	786	830	874	926	
	K	702	746	769	821	
	W	850	850	1050	1050	
	D	47	47	58	58	
	L	767	798	732	824	
	M	119	119	129	129	
	N	103	103	113	113	
	P	Ø165	Ø165	Ø165	Ø165	
	Q	Ø195	Ø165	Ø195	Ø195	
T	334	334	374	382		
S	519	536	472	537		
Weight(approx.)(kg)		550	560	980	1010	
Rail(kg/m)		15 Kg/M	15 Kg/M	15 Kg/M	15 Kg/M	

※ KSD □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST Special Type

## Regular Type – Creep (4~10ton)




Capacity(Ton)		4					6					8					10					
Type	Hoisting Speed	High-HIGH	C-KSN04-H06-MH					C-KSN06-H06-MH					C-KSN08-H06-MH					C-KSN10-H06-MH				
		High-Low	C-KSN04-H06-ML					C-KSN06-H06-ML					C-KSN08-H06-ML					C-KSN10-H06-ML				
Hoist	Max. Lift(m)		6(12)					6(12)					6(12)					6(12)				
	Hoisting Speed(m/min) High/Creep	50Hz	4,2/0,42					3,8/0,38					2,3/0,23					2,3/0,23				
		60Hz	5,0/0,5					4,5/0,45					2,8/0,28					2,8/0,28				
	Hoisting Motor (Kw x P)	High Speed	3,7x4					5,5x4					5,5x6					5,5x6				
		Creep Speed	0,4x4					1,1x4					1,0x6					1,0x6				
Wire Rope	Construction	6x37					6x37					6x37					6x37					
	Dia.(min)x no. of Ropes	Ø10x4 Falls					Ø12,5x4 Falls					Ø14x4 Falls					Ø16x4 Falls					
Brake		DC Magnet Disc Brake																				
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24					20/24					20/24					20/24				
		Low Speed 50/60(Hz)	13/16					13/16					13/16					13/16				
	Traversing Motor (Kw x P)	High Speed	0,75x4					0,75x4					0,75x4					0,75x4				
		Low Speed	0,5x6					0,5x6					0,5x6					0,5x6				
Brake		DC Magnet Disc Brake																				
Dimensions(approx)(mm)	H	1050					1050					1390					1390					
	A	504(701)					564(771)					580(772)					606(821)					
	B	753(950)					833(1040)					920(1112)					946(1161)					
	D	425					475					540					560					
	G	520(920)					550(960)					530(910)					580(1010)					
	M	260					260					275					275					
	N	225					225					275					275					
	L	67(186)					67(274)					225(222)					55(270)					
E	375					555					655					655						
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(I-BEAM)	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	
	I-300x150x19t~	515	267	24	96	182	515	267	23	96	122	-	-	-	-	-	-	-	-	-	-	
	I-450x175x26t~	528	267	22	121	127	528	267	21	121	127	535	351	34	111	228	535	351	34	111	228	
	I-600x190x25t~	-	-	-	-	-	-	-	-	-	-	543	351	32	118	230	543	351	32	118	230	
H-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(H-BEAM)	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	
	H-Hx150x20t~	515	267	24	96	184	515	267	21	121	182	-	-	-	-	-	-	-	-	-	-	
	H-Hx200x26t~	540	267	21	146	191	540	267	15	171	191	535	351	31	111	232	560	351	34	128	231	
	H-Hx300x30t~	-	-	-	-	-	-	-	-	-	-	560	351	27	211	236	610	351	28	228	235	
Min.Radius of curvature(m)		For Straight Only(Curvature Hinge Type Option)																				
Weight(approx)(kg)		374(404)					444(520)					708(770)					728(790)					

※ KSN □□□□-C-H□□-W Hoist Name Plate shall be typed as per above coding

# WIRE HOIST Special Type

## Double Low Head Type – Creep (4~10ton)




Capacity(Ton)		4	6	8	10	
Type	Hoisting Speed	High-HIGH	C-KSP04-H12-MH	C-KSP06-H12-MH	C-KSP08-H12-MH	C-KSP10-H12-MH
		High-Low	C-KSP04-H12-ML	C-KSP06-H12-ML	C-KSP08-H12-ML	C-KSP10-H12-ML
Hoist	Max. Lift(m)		12	12	12	12
	Hoisting Speed(m/min) High/Creep	50Hz	4,2/0,42	3,8/0,38	2,3/0,23	2,3/0,23
		60Hz	5,0/0,5	4,5/0,45	2,8/0,28	2,8/0,28
	Hoisting Motor (Kw x P)	High Speed	3,7x4	5,5x4	5,5x6	5,5x6
		Creep Speed	0,4x4	1,1x4	1,0x6	1,0x6
Wire Rope	Construction	6x37	6x37	6x37	6x37	
	Dia.(min)x no. of Ropes	Ø10x4 Falls	Ø12,5x4 Falls	Ø14x4 Falls	Ø16x4 Falls	
Brake		DC Magnet Disc Brake				
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24	20/24	20/24	20/24
		Low Speed 50/60(Hz)	13/16	13/16	13/16	13/16
	Traversing Motor (Kw x P)	High Speed	0,75x4	0,75x4	0,75x4	0,75x4
		Low Speed	0,5x6	0,5x6	0,5x6	0,5x6
Brake		DC Magnet Disc Brake				
Dimensions(approx)(mm)	H	510	510	755	755	
	R	1150	1150	1150	1150	
	A	560	560	705	705	
	B	560	560	705	705	
	C	430	430	615	615	
	G	950	1040	1112	1161	
	K	702	746	769	821	
	W	850	850	1070	1070	
	D	47	47	58	58	
	L	767	798	732	824	
	M	135	135	170	170	
	N	135	135	170	170	
	P	Ø165	Ø165	Ø165	Ø165	
	Q	Ø195	Ø165	Ø195	Ø195	
E	375	375	425	425		
T	334	334	374	382		
S	519	536	472	537		
Weight(approx.)(kg)		530	540	960	975	
Rail(kg/m)		15 Kg/M	15 Kg/M	15 Kg/M	15 Kg/M	

※ KSP □□□□-C-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST Special Type

## Low Head Type – Creep (4~10ton)




Capacity(Ton)		4		6		8		10													
Type	Hoisting Speed	High-HIGH	C-KSL04-H06-MH		C-KSL06-H06-MH		C-KSL08-H06-MH		C-KSL10-H06-MH												
		High-Low	C-KSL04-H06-ML		C-KSL06-H06-ML		C-KSL08-H06-ML		C-KSL10-H06-ML												
Hoist	Max. Lift(m)		6(12)		6(12)		6(12)		6(12)												
	Hoisting Speed(m/min) High/Creep	50Hz	4,2/0,42		3,8/0,38		2,3/0,23		2,3/0,23												
		60Hz	5,0/0,5		4,5/0,45		2,8/0,28		2,8/0,28												
	Hoisting Motor (Kw x P)	High Speed	3,7x4		5,5x4		5,5x6		5,5x6												
		Creep Speed	0,4x4		1,1x4		1,0x6		1,0x6												
Wire Rope	Construction	6x37		6x37		6x37		6x37													
	Dia.(min)x no. of Ropes	Ø10x4 Falls		Ø12,5x4 Falls		Ø14x4 Falls		Ø16x4 Falls													
Brake		DC Magnet Disc Brake																			
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24		20/24		20/24		20/24												
		Low Speed 50/60(Hz)	13/16		13/16		13/16		13/16												
	Traversing Motor (Kw x P)	High Speed	0,75x4		0,75x4		0,75x4		0,75x4												
		Low Speed	0,5x6		0,5x6		0,5x6		0,5x6												
Brake		DC Magnet Disc Brake																			
Dimensions(approx)(mm)	H	600		600		800		800													
	A	534(731)		594(801)		610(802)		636(851)													
	B	753(950)		833(1040)		920(1112)		946(1161)													
	G	770(1170)		790(1200)		770(1160)		830(1260)													
	M	203(200)		203(205)		300(297)		296(296)													
	N	149(146)		199(201)		225(222)		221(221)													
	L	67(186)		67(274)		65(203)		55(270)													
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(I-BEAM)	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U
	I-300x150x19t~	565	585	25	68	266	565	585	25	68	266	-	-	-	-	-	-	-	-	-	-
	I-450x175x26t~	578	598	18	93	273	578	598	18	93	273	683	683	20	93	333	683	683	20	93	333
	I-600x190x25t~	-	-	-	-	-	-	-	-	-	-	691	691	19	108	332	691	691	19	108	332
H-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(H-BEAM)	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U
	H-Hx150x20t~	565	585	25	68	265	565	585	25	68	265	-	-	-	-	-	-	-	-	-	-
	H-Hx200x26t~	590	610	19	118	271	590	610	19	118	271	696	696	20	118	327	696	696	20	118	327
	H-Hx300x30t~	-	-	-	-	-	-	-	-	-	-	746	746	16	218	331	746	746	16	218	331
Min. Radius of curvature(m)		For Straight Only																			
Weight(approx)(kg)		389(429)		459(535)		728(790)		748(800)													

※ KSL □□□□-C-H□□-W Hoist Name Plate shall be typed as per above coding

# WIRE HOIST Special Type

## Double Rail Type – Creep (4~10ton)



VIEW from X  
(Creep Side)

Capacity(Ton)		4	6	8	10	
Type	Hoisting Speed	High-HIGH	C-KSD04-H12-MH	C-KSD06-H12-MH	C-KSD08-H12-MH	C-KSD10-H12-MH
		High-Low	C-KSD04-H12-ML	C-KSD06-H12-ML	C-KSD08-H12-ML	C-KSD10-H12-ML
Hoist	Max. Lift(m)		12	12	12	12
	Hoisting Speed(m/min) High/Creep	50Hz	4,2/0,42	3,8/0,38	2,3/0,23	2,3/0,23
		60Hz	5,0/0,5	4,5/0,45	2,8/0,28	2,8/0,28
	Hoisting Motor (Kw x P)	High Speed	3,7x4	5,5x4	5,5x6	5,5x6
		Creep Speed	0,4x4	1,1x4	1,0x6	1,0x6
Wire Rope	Construction	6x37	6x37	6x37	6x37	
	Dia.(min)x no. of Ropes	Ø10x4 Falls	Ø12,5x4 Falls	Ø14x4 Falls	Ø16x4 Falls	
Brake		DC Magnet Disc Brake				
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24	20/24	20/24	20/24
		Low Speed 50/60(Hz)	13/16	13/16	13/16	13/16
	Traversing Motor (Kw x P)	High Speed	0,75x4	0,75x4	0,75x4	0,75x4
		Low Speed	0,5x6	0,5x6	0,5x6	0,5x6
Brake		DC Magnet Disc Brake				
Dimensions(approx)(mm)	H	350	350	580	580	
	R	1150	1150	1150	1150	
	A	544	544	654	654	
	B	528	528	638	638	
	C	580	620	750	750	
	G	950	1040	1112	1161	
	K	702	746	769	821	
	W	850	850	1050	1050	
	D	47	47	58	58	
	L	767	798	732	824	
	M	119	119	129	129	
	N	103	103	113	113	
	P	Ø165	Ø165	Ø165	Ø165	
	Q	Ø195	Ø165	Ø195	Ø195	
E	375	375	425	425		
T	334	334	374	382		
S	519	536	472	537		
Weight(approx.)(kg)		590	600	1030	1060	
Rail(kg/m)		15 Kg/M	15 Kg/M	15 Kg/M	15 Kg/M	

※ KSD □□□□-C-H□□ Hoist Name Plate shall be typed as per above coding



# WIRE HOIST Explosion Proof Type

## How is an explosion avoided?

The easiest way, of course, is by following the “first rule of explosion protection”: avoid the creation of an explosive atmosphere. For example, by providing adequate ventilation or confining work processes to closed systems which prevent the occurrence of dangerous gases.

If this is not possible, there are basically two possibilities:

- Either, prevent the explosive atmosphere from igniting. To do this the equipment must have a limited surface temperature and the creation of sparks or sources of ignition must be avoided.
- Or the effects of an explosion must be reduced to a negligible level. This is done by isolating the ignition source, e.g. by mounting the equipment in flameproof enclosures.

## What explodes, with what force and when?

The various inflammable gases and vapours are divided into *explosion groups*. These express the ignition transmission capacity or explosive energy. *Group 1* applies to gases for *explosion protection in mines*. *Groups IIA, IIB and IIC* apply to general explosion protection. In addition, gases are divided into *temperature classes T1 to T6*. This expresses their ignition quality.

Explosion group	Temperature class					
	T 1	T 2	T 3	T 4	T 5	T 6
II A	acetone acetic ammoniac benzol(pure) carbon oxide ethane ethyl acetate ethyl chloride methane methyl chloride propane toluol	i-amyl acetate n-butane n-butyl alcohol ethylene chloride sym. cyclo- heaxanon	benzine n-hexane  diesel fuel jet fuel heating oils hydrogen sulphide	acetaldehyde ethyl ether		
II B	town gas	ethylene ethyl oxide				
II C	hydrogen	acetylene				carbon disulphide

## Types of protection


The ignition protection modes increased safety “e” and flameproof enclosure “d” are relevant for explosion protection for hoists and cranes.

Increased safety “e” designates measures which prevent *inadmissible temperatures* and *the creation of sparks and electric arcs* in this electric equipment.

In the case of flameproof enclosures “d”, all the affected parts of electrical equipment, e.g. a hoist, are *installed in an housing*. This covers all components which are a direct source of ignition (e.g. switching sparks in contactors) as well as those which could theoretically become a source of ignition though overheating (e.g. brakes, motor windings, transformers). The enclosure is capable of withstanding the pressure of an internal explosion without igniting an explosive environment.

EXPLOSION PROOF CONSTRUCTIONS AND EXPLOSION GROUP					
Description	Korea	Japan	Germany	U.S.A	Ignition Point(°C)
	KS	JIS,RIIS	IEC	NEC, UL	
Temperature Class	T <sub>1</sub>	G <sub>1</sub>	T <sub>1</sub>	T <sub>1</sub>	Over 450
	T <sub>2</sub>	G <sub>2</sub>	T <sub>2</sub>	T <sub>2</sub>	300~450
	T <sub>3</sub>	G <sub>3</sub>	T <sub>3</sub>	T <sub>3</sub>	200~300
	T <sub>4</sub>	G <sub>4</sub>	T <sub>4</sub>	T <sub>4</sub>	135~200
	T <sub>5</sub>	G <sub>5</sub>	T <sub>5</sub>	T <sub>5</sub>	100~135
	T <sub>6</sub>	G <sub>6</sub>	T <sub>6</sub>	T <sub>6</sub>	85~100
Explosion Group	d <sub>1</sub>	1	II <sub>A</sub>	D	
	d <sub>2</sub>	2	II <sub>B</sub>	C	
	d <sub>3</sub>	3	II <sub>C</sub>	B	

## Marking

Within the European Community, the norms mentioned above stipulate that a type test must be performed by a recognized and authorized testing authority. The test is documented by a *certificate of conformity* which is recognized throughout the EEC. Approved equipment is entitled to bear the  label. Test authorities in the Federal Republic of Germany are the Physikalisch-Technische Bundesanstalt in Braunschweig and the Bergbauversuchsstrecke (Mining Test Centre) in Dortmund.

The marking of explosion-proof equipment is specified as mandatory in the European Norms, irrespective of whether the equipment is for use inside or outside the EEC.

The European Norms prescribe the marking of explosion-proof electrical equipment independent of whether the equipment will be traded within the European Community or outside it.




Marking of equipment

 EEx de II B T3

**Example of marking:**  
in which




- Symbol for apparatus certified by an EC testing authority,
- Symbol for apparatus constructed in accordance with European Norms,
- Flameproof enclosure
- Explosion group
- Temperature class

## Scope of Application



## Component Arrangement



Application (classified by ignition grade and explosion degree of explosive gases)

Ignition grade (G)	Explosion degree (d)	Application (classified by ignition grade and explosion degree of explosive gases)		
		1	2	3
G1 Above 450°C (320 deg.)				
G2 Above 300°C and below 450°C (200 deg.)		Acetone, ammonium, carbon monoxide, ethane, acetic acid, ethyl acetate, toluene, propane, benzene, methanol and methane	Coal gas	Wager gas Hydrogen
G3 Above 200°C and below 300°C (120 deg.)		Ethanol, isoamyl acetate, 1-butanol butane and acetic anhydride	Ethylene and ethylene oxide	Acetylene
G4 Above 135°C and below 200°C (70 deg.)		Gasoline and hexane		
G5 Above 100°C and below 135°C (40 deg.)		Acetaldehyde and ethyl ether		
				Carbon disulfide

(Note) Temperature in ignition grade column shows flash point.  
Temperature in parentheses indicates upper limit for temperature rise of casing.

# WIRE HOIST Explosion Proof Type

## Regular Type – Normal (0.5~5ton)





Capacity(Ton)		0.5		1		2		2.8		3		5																			
Type	Hoisting and Traversing Speed	High-High	E-KN0,5-H06(12)-MH		E-KN1-H06(12)-MH		E-KN2-H06(12)-MH		E-KN2,8-H06(12)-MH		E-KN3-H06(12)-MH		E-KN5-H06(12)-MH																		
		High-Low	E-KN0,5-H06(12)-ML		E-KN1-H06(12)-ML		E-KN2-H06(12)-ML		E-KN2,8-H06(12)-ML		E-KN3-H06(12)-ML		E-KN5-H06(12)-ML																		
		Low-High	E-KN0,5-L06(12)-MH		E-KN1-L06(12)-MH		E-KN2-L06(12)-MH		E-KN2,8-L06(12)-MH		E-KN3-L06(12)-MH		E-KN5-L06(12)-MH																		
		Low-Low	E-KN0,5-L06(12)-ML		E-KN1-L06(12)-ML		E-KN2-L06(12)-ML		E-KN2,8-L06(12)-ML		E-KN3-L06(12)-ML		E-KN5-L06(12)-ML																		
Hoist	Max. Lift(m)		6(12)		6(12)		6(12)		6(12)		6(12)		6(12)																		
	Hoisting Speed (m/min)	High Speed 50/60(Hz)	10/12		10/12		8,4/10		7,5/9		7,5/9		4,7/5,6																		
		Low Speed 50/60(Hz)	5/6		5/6		4,2/5		3,7/4,5		3,7/4,5		3,5/4,2																		
	Hoisting Motor (Kw x P)	High Speed	1,2x4		2,4x4		3,7x4		4,8x4		5,5x4		5,5x6																		
		Low Speed	0,6x8		1,2x8		1,8x8		2,4x8		2,8x8		4,2x8																		
	Wire Rope	Construction	6x19		6x19		6x37		6x37		6x37		6x37																		
Dia.(min)x no. of Ropes		Ø6x2 Falls		Ø8x2 Falls		Ø10x2 Falls		Ø12,5x2 Falls		Ø12,5x2 Falls		Ø16x2 Falls																			
Brake		DC Magnet Disc Brake																													
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24		20/24		20/24		20/24		20/24		20/24																		
		Low Speed 50/60(Hz)	13/16		13/16		13/16		13/16		13/16		13/16																		
	Traversing Motor (Kw x P)	High Speed	0,4x4		0,4x4		0,75x4		0,75x4		0,75x4		0,75x4																		
		Low Speed	0,2x6		0,2x6		0,5x6		0,5x6		0,5x6		0,5x6																		
Brake		DC Magnet Disc Brake																													
Dimensions(approx)(mm)	H	705		815		980		1115		1115		1325																			
	A	420(475)		455(525)		515(570)		570(620)		570(620)		655(755)																			
	B	430(575)		515(655)		515(665)		535(685)		535(685)		630(730)																			
	D	300		355		360		360		360		400																			
	G	255		255		260		260		260		275																			
	K	200		200		225		225		225		275																			
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(I-BEAM)	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U
	I-200x100x7t~	505	450	38	48	144	505	450	38	48	144	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	I-250x125x7,5t~	518	460	30	71	153	518	460	30	71	153	610	555	23	71	182	610	555	23	71	182	610	555	23	71	182	645	575	39	61	222
	I-300x150x10t~	530	475	28	96	155	530	475	28	96	155	625	568	23	96	182	625	568	23	96	182	625	568	23	96	182	660	585	37	86	224
	I-450x175x13t~	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	675	600	34	111	228
Min.Radius of curvature(m)		1,5		1,5		1,8		1,8		1,8		2,3																			
Weight(approx)(kg)		197(207)		240(268)		328(364)		424(468)		424(468)		627(692)																			

※ EX-KN □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST Explosion Proof Type

## Regular Type – Normal (7.5~20ton)




Capacity(Ton)		7,5	10	15	20																	
Type	Hoisting and Traversing Speed	High-High	E-KN7,5-H12-MH	E-KN10-H12-MH	E-KN15-H12-MH	E-KN20-H12-MH																
		High-Low	E-KN7,5-H12-ML	E-KN10-H12-ML	E-KN15-H12-ML	E-KN20-H12-ML																
		Low-High	E-KN7,5-L12-MH	E-KN10-L12-MH	E-KN15-L12-MH	E-KN20-L12-MH																
		Low-Low	E-KN7,5-L12-ML	E-KN10-L12-ML	E-KN15-L12-ML	E-KN20-L12-ML																
Hoist	Max. Lift(m)		12	12	12	12																
	Hoisting Speed (m/min)	High Speed 50/60(Hz)	3,1/3,8	3,7/4,5	3,7/4,5	3,5/4,2																
		Low Speed 50/60(Hz)	2,3/2,8	2,5/3	2,5/3	2,3/2,8																
	Hoisting Motor (Kw x P)	High Speed	5,5x6	9x8	13x8	17x8																
		Low Speed	4,2x8	6x12	8,5x12	11,5x12																
	Wire Rope	Construction	6x37	6x37	6x37	6x37																
Dia,(min)x no. of Ropes		Ø14x4 Falls	Ø16x4 Falls	Ø20x4 Falls	Ø22,4x4 Falls																	
Brake		DC Magnet Disc Brake																				
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	12,5/15	12,5/15	12,5/15	12,5/15																
		Low Speed 50/60(Hz)	8,3/10	8,3/10	8,3/10	8,3/10																
	Traversing Motor (Kw x P)	High Speed	0,75x4	0,75x4	1,5x4	1,5x4																
		Low Speed	0,5x6	0,5x6	1x6	1x6																
Brake		DC Magnet Disc Brake																				
Dimensions(approx)(mm)	H	1460	1520	1875	2115																	
	A	975	1025	1025	1215																	
	B	945	1135	1140	1285																	
	D	710	780	720	740																	
	G	800	800	800	850																	
	K	276	276	300	300																	
	M	276	276	300	300																	
I-BEAM TYPE DIMENSIONS (APPROX,)(MM)	axbxt(I-BEAM)	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	
	I-300x150x10t~	592	450	35	68	224	592	480	35	68	224	-	-	-	-	-	-	-	-	-	-	-
	I-450x175x13t~	605	450	30	93	228	605	480	30	98	228	715	520	32	77	248	715	550	32	77	248	
	I-600x190x13t~	613	450	25	118	232	613	480	25	118	232	723	520	32	92	248	715	550	32	92	248	
Min.Radius of curvature(m)		For straight rails only																				
Weight(approx)(kg)		960					1260					2080					2480					

※ EX-KN □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST Explosion Proof Type

## Low Head Type – Normal (0.5~5ton)




Capacity(Ton)		0.5			1			2			2,8			3			5			
Type	Hoisting and Traversing Speed	High-High	E-KL0,5-H06-MH			E-KL1-H06-MH			E-KL2-H06-MH			E-KL2,8-H06-MH			E-KL3-H06-MH			E-KL5-H06-MH		
		High-Low	E-KL0,5-H06-ML			E-KL1-H06-ML			E-KL2-H06-ML			E-KL2,8-H06-ML			E-KL3-H06-ML			E-KL5-H06-ML		
		Low-High	E-KL0,5-L06-MH			E-KL1-L06-MH			E-KL2-L06-MH			E-KL2,8-L06-MH			E-KL3-L06-MH			E-KL5-L06-MH		
		Low-Low	E-KL0,5-L06-ML			E-KL1-L06-ML			E-KL2-L06-ML			E-KL2,8-L06-ML			E-KL3-L06-ML			E-KL5-L06-ML		
Hoist	Max. Lift(m)	6			6			6			6			6			6			
		Hoisting Speed (m/min)	High Speed 50/60(Hz)	10/12			10/12			8,4/10			7,5/9			7,5/9			4,7/5,6	
	Low Speed 50/60(Hz)		5/6			5/6			4,2/5			3,7/4,5			3,7/4,5			3,7/4,2		
	Hoisting Motor (Kw x P)	High Speed	1,2x4			2,4x4			3,7x4			4,8x4			5,5x4			5,5x6		
		Low Speed	0,6x8			1,2x8			1,8x8			2,4x8			2,8x8			4,2x8		
	Wire Rope	Construction	7x19			6x19			6x19			6x37			6x37			6x37		
Dia.(min)x no. of Ropes		Ø4x4 Falls			Ø6x4 Falls			Ø8x4 Falls			Ø9x4 Falls			Ø9x4 Falls			Ø11,2x4 Falls			
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)			20/24			20/24			20/24			20/24			20/24			
		Low Speed 50/60(Hz)			13/16			13/16			13/16			13/16			13/16			
	Traversing Motor (Kw x P)	High Speed			0,4x4			0,4x4			0,75x4			0,75x4			0,75x4			
		Low Speed			0,2x6			0,2x6			0,5x6			0,5x6			0,5x6			
Brake		DC Magnet Disc Brake																		
Dimensions(approx)(mm)	H	550			550			620			620			620			800			
	A	515			555			640			660			660			755			
	B	675			765			785			780			780			880			
	C	635			635			665			740			740			815			
	D	245			290			385			395			395			465			
	G	255			255			260			260			260			275			
	K	200			200			225			225			225			275			
	F	525			615			635			630			630			730			
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbx(I-BEAM)	S	T	U	S	T	U	S	T	U	S	T	U	S	T	U	S	T	U	
	I-200x100x7t~	38	46	144	38	46	144	-	-	-	-	-	-	-	-	-	-	-	-	
	I-250x125x7,5t~	30	71	153	30	71	153	22	71	182	23	71	182	23	71	182	-	-	-	
	I-300x150x10t~	28	96	155	28	96	155	22	96	182	23	96	182	23	96	182	26	86	224	
I-450x175x13t~	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	23	111	228		
Min.Radius of curvature(m)	1,5			1,5			1,8			1,8			1,8			2,3				
Weight(approx)(kg)	225			250			400			490			490			780				

※ EX-KL □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST Explosion Proof Type

## Double Rail Type – Normal (2~5ton)





Capacity(Ton)		2	2,8	3	5	
Type	Hoisting and Traversing Speed	High-High	E-KD02-H12-MH	E-KD2,8-H12-MH	E-KD03-H12-MH	E-KD05-H12-MH
		High-Low	E-KD02-H12-ML	E-KD2,8-H12-ML	E-KD03-H12-ML	E-KD05-H12-ML
		Low-High	E-KD02-L12-MH	E-KD2,8-L12-MH	E-KD03-L12-MH	E-KD05-L12-MH
		Low-Low	E-KD02-L12-ML	E-KD2,8-L12-ML	E-KD03-L12-ML	E-KD05-L12-ML
Hoist	Max. Lift(m)		12	12	12	12
	Hoisting Speed (m/min)	High Speed 50/60(Hz)	8,4/10	7,5/9	7,5/9	4,7/5,6
		Low Speed 50/60(Hz)	4,2/5	3,7/4,5	3,7/4,5	3,5/4,2
	Hoisting Motor (Kw x P)	High Speed	3,7x4	4,8x4	5,5x4	5,5x6
		Low Speed	1,8x8	2,4x8	2,8x8	4,2x8
	Wire Rope	Construction	6x37	6x37	6x37	6x37
Dia,(min)x no. of Ropes		Ø8x4 Falls	Ø9x4 Falls	Ø9x4 Falls	Ø12,5x4 Falls	
Traversing	Brake		DC Magnet Disc Brake			
	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24	20/24	20/24	20/24
		Low Speed 50/60(Hz)	13/16	13/16	13/16	13/16
	Traversing Motor (Kw x P)	High Speed	0,75x4	0,75x4	0,75x4	0,75x4
		Low Speed	0,5x6	0,5x6	0,5x6	0,5x6
	Brake		DC Magnet Disc Brake			
Dimensions(approx)(mm)	H	415	420	420	510	
	R	950	950	950	1150	
	A	465	465	465	510	
	B	390	390	390	470	
	C	630	730	730	760	
	G	790	835	835	985	
	K	790	795	795	960	
	W	650	650	650	760	
	D	47	47	47	47	
	L	680	690	690	890	
	M	115	115	115	125	
	N	90	90	90	110	
P	Ø140	Ø140	Ø140	Ø165		
Q	Ø170	Ø170	Ø170	Ø190		
Weight(approx.)(kg)		500	600	600	900	
Rail(kg/m)		15 Kg/M	15 Kg/M	15 Kg/M	15 Kg/M	

※ EX-KD □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST **Explosion Proof Type**

## Double Rail Type – Normal (7.5~30ton)





Capacity(Ton)		7.5	10	15	20	30	
Type	Hoisting and Traversing Speed	High-High	E-KD7,5-H12-MH	E-KD10-H12-MH	E-KD15-H12-MH	E-KD20-H12-MH	E-KD30-H12-MH
		High-Low	E-KD7,5-H12-ML	E-KD10-H12-ML	E-KD15-H12-ML	E-KD20-H12-ML	E-KD30-H12-ML
		Low-High	E-KD7,5-L12-MH	E-KD10-L12-MH	E-KD15-L12-MH	E-KD20-L12-MH	E-KD30-L12-MH
		Low-Low	E-KD7,5-L12-ML	E-KD10-L12-ML	E-KD15-L12-ML	E-KD20-L12-ML	E-KD30-L12-ML
Hoist	Max. Lift(m)		12	12	12	12	12
	Hoisting Speed (m/min)	High Speed 50/60(Hz)	3,1/3,8	3,7/4,5	3,7/3,5	3,7/4,3	2,3/2,8
		Low Speed 50/60(Hz)	2,3/2,8	2,5/3	2,5/3	2,5/2,8	1,5/1,8
	Hoisting Motor (Kw x P)	High Speed	5,5x6	9x8	13x8	17x8	17x8
		Low Speed	4,2x8	6x12	8,5x12	11,5x12	11,5x12
	Wire Rope	Construction	6x37	6x37	6x37	6x37	6x37
Dia,(min)x no. of Ropes		Ø14x4 Falls	Ø16x4 Falls	Ø20x4 Falls	Ø22,4x4 Falls	Ø22,4x6 Falls	
Brake		DC Magnet Disc Brake					
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	12,5/15	12,5/15	12,5/15	12,5/15	12,5/15
		Low Speed 50/60(Hz)	8,3/10	8,3/10	8,3/10	8,3/10	8,3/10
	Traversing Motor (Kw x P)	High Speed	0,75x4	0,75x4	1,5x4	1,5x4	1,5x4x2
		Low Speed	0,5x6	0,5x6	1x6	1x6	1x6x2
Brake		DC Magnet Disc Brake					
Dimensions(approx)(mm)	H	730	775	995	1175	2480	
	R	1150	1150	1200	1300	1800	
	A	525	565	625	670	940	
	B	480	510	555	610	940	
	C	775	965	960	1000	1080	
	G	995	1045	1145	1235	1495	
	K	1045	1135	1135	1285	1555	
	W	800	865	920	1000	1540	
	D	58	58	58	58	70	
	L	852	851	872	934	1418	
	M	120	120	130	140	180	
	N	95	100	130	140	160	
	P	Ø165	Ø165	Ø180	Ø220	Ø250	
Q	Ø195	Ø195	Ø210	Ø250	Ø280		
Weight(approx.)(kg)		980	1280	1390	2380	3530	
Rail(kg/m)		15 Kg/M	15 Kg/M	22 Kg/M	22 Kg/M	30 Kg/M	

※ EX-KD □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding



# WIRE HOIST **Explosion Proof Type**

## Double Rail Type – Normal (35~70ton)





Capacity(Ton)		35	50	60	70	
Type	Hoisting and Traversing Speed	High-High	E-KD35-H12-MH	E-KD50-H12-MH	E-KD60-H12-MH	E-KD70-H12-MH
		High-Low	E-KD35-H12-ML	E-KD50-H12-ML	E-KD60-H12-ML	E-KD70-H12-ML
Hoist	Max. Lift(m)		12	12	12	12
	Hoisting Speed (m/min)	High Speed 50/60(Hz)	4/4,8	2,7/3,2	2/2,4	2/2,4
	Hoisting Motor (Kw x P)	High Speed	33x6	33x6	33x6	33x6
	Wire Rope	Construction	6xFi(250)	6xFi(25)	6xFi(25)	6xFi(25)
		Dia.(min)x no. of Ropes	Ø28x4 Falls	Ø28x6 Falls	Ø28x8 Falls	Ø28x8 Falls
Brake		DC Magnet Disc Brake				
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	12,5/15	12,5/15	12,5/15	12,5/15
		Low Speed 50/60(Hz)	8,3/10	8,3/10	8,3/10	8,3/10
	Traversing Motor (Kw x P)	High Speed	2,2x4	2,2x4x2	2,2x4x2	3,7x4x2
		Low Speed	1,5x6	1,5x6x2	1,5x6x2	2,2x6x2
Brake		DC Magnet Disc Brake				
Dimensions(approx)(mm)	H	1490	1680	1780	1780	
	R	1150	1150	1150	1150	
	A	1600	2300	2800	2800	
	B	1025	1432	1525	1525	
	C	1192	1400	1400	1400	
	G	1555	1880	2130	2130	
	K	1460	1815	2065	2065	
	W	1550	2125	2125	2075	
	D	70	80	80	80	
	L	1044	1430	1930	1930	
	M	215	275	275	300	
	N	215	275	275	300	
P	Ø355	Ø450	Ø450	Ø500		
Q	Ø395	Ø490	Ø490	Ø540		
Weight(approx.)(kg)		5320	7120	8620	9120	
Rail(kg/m)		37 Kg/M	50 Kg/M	50 Kg/M	50 Kg/M	

※ EX-KD □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST Explosion Proof Type

## Regular Type – Creep (0.5~5ton)





Capacity(Ton)		1		2		2.8		3		5												
Type	Hoisting and Traversing Speed	High-HIGH	E-CKN1-H06(12)-MH		E-CKN2-H06(12)-MH		E-CKN2,8-H06(12)-MH		E-CKN3-H06(12)-MH		E-CKN5-H06(12)-MH											
		High-Low	E-CKN1-H06(12)-ML		E-CKN2-H06(12)-ML		E-CKN2,8-H06(12)-ML		E-CKN3-H06(12)-ML		E-CKN5-H06(12)-ML											
Hoist	Max. Lift(m)		6(12)		6(12)		6(12)		6(12)		6(12)											
	Hoisting Speed(m/min) High/Creep	50Hz	10/1		8,4/0,84		7,5/0,75		7,5/0,75		4,7/0,47											
		60Hz	12/1,2		10/1		9/0,9		9/0,9		5,6/0,56											
	Hoisting Motor (Kw x P)	High Speed	2,4/0,4x4		3,7/0,4x4		4,8/1,1x4		5,5/1,1x4		5,5/1,1x6											
		Creep Speed	0,4x4		1,1x4		1,0x6		1,0x6		1,0x6											
	Wire Rope	Construction	6x19		6x37		6x37		6x37		6x37											
Dia,(min)x no. of Ropes		Ø8x2 Falls		Ø10x2 Falls		Ø12,5x2 Falls		Ø12,5x2 Falls		Ø16x4 Falls												
Brake		DC Magnet Disc Brake																				
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24		20/24		20/24		20/24		20/24											
		Low Speed 50/60(Hz)	13/16		13/16		13/16		13/16		13/16											
	Traversing Motor (Kw x P)	High Speed	0,4x4		0,75x4		0,75x4		0,75x4		0,75x4											
		Low Speed	0,2x6		0,5x6		0,5x6		0,5x6		0,5x6											
Brake		DC Magnet Disc Brake																				
Dimensions(approx)(mm)	H	815		980		1115		1115		1325												
	A	660(720)		700(750)		830(875)		820(860)		900(1000)												
	B	515(655)		515(665)		535(685)		535(685)		630(730)												
	D	420		400		465		455		505												
	F	450		555		555		555		585												
	G	255		260		260		260		275												
	K	200		225		225		225		275												
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(I-BEAM)	C	S	T	U	C	S	T	U	C	S	T	U	C	S	T	U	C	S	T	U	
	I-200x100x7t~	505	38	46	144	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	I-250x125x7,5t~	518	30	71	153	540	26	71	182	610	25	71	182	610	25	71	182	645	37	61	222	
	I-300x150x10t~	530	28	96	155	555	24	96	182	625	23	96	182	625	23	96	182	660	32	86	224	
	I-450x175x13t~	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	675	32	111	228
Min.Radius of curvature(m)		1,5		1,8		1,8		1,8		2,3												
Weight(approx)(kg)		305(425)		400(515)		495(540)		495(540)		715(780)												

※ EX-KN □□□□-C-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST Explosion Proof Type

## Regular Type – Creep (7.5~20ton)




Capacity(Ton)		7,5		10		15		20										
Type	Hoisting and Traversing Speed	High-HIGH	E-CKN7,5-H12-MH		E-CKN10-H12-MH		E-CKN15-H12-MH		E-CKN20-H12-MH									
		High-Low	E-CKN7,5-H12-ML		E-CKN10-H12-ML		E-CKN15-H12-ML		E-CKN20-H12-ML									
Hoist	Max. Lift(m)		12		12		12		12									
	Hoisting Speed(m/min) High/Creep	50Hz	3,1/0,31		3,7/0,37		3,7/0,37		3,5/0,35									
		60Hz	3,8/0,38		4,5/0,45		4,5/0,45		4,2/0,42									
	Hoisting Motor (Kw x P)	High Speed	5,5x6		9x8		13x8		17x8									
		Creep Speed	1x6		1,1x8		1,8x8		1,8x8									
	Wire Rope	Construction	6x37		6x37		6x37		6x37									
Dia,(min)x no. of Ropes		Ø14x4 Falls		Ø16x4 Falls		Ø20x4 Falls		Ø22,4x4 Falls										
Brake		DC Magnet Disc Brake																
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	12,5/15		12,5/15		12,5/15		12,5/15									
		Low Speed 50/60(Hz)	8,3/10		8,3/10		8,3/10		/,3/10									
	Traversing Motor (Kw x P)	High Speed	0,75x4(2units)		0,75x4(2units)		1,5x4(2units)		1,5x4(2units)									
		Low Speed	0,5x6(2units)		0,5x6(2units)		1x6(2units)		1x6(2units)									
Brake		DC Magnet Disc Brake																
Dimensions(approx)(mm)		H	1460		1565		1875		2115									
		A	1235		1325		1435		1530									
		B	745		1135		1140		1285									
		D	710		780		720		740									
		F	650		680		720		750									
		L	850		850		870		935									
		G	800		800		800		850									
		M	276		276		300		300									
		K	276		276		300		300									
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)		axbxt(I-BEAM)	C	S	T	U	C	S	T	U	C	S	T	U	C	S	T	U
		I-300x150x10t~	592	35	68	224	592	35	68	224	-	-	-	-	-	-	-	-
		I-450x175x13t~	605	30	93	228	605	30	93	228	715	32	77	248	715	32	77	248
		I-600x190x13t~	613	32	118	227	613	32	118	227	723	37	92	243	723	37	92	243
Min,Radius of curvature(m)		Straight line																
Weight(approx)(kg)		1050		1350		2250		2600										

※ EX-KN □□□□-C-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST **Explosion Proof Type**

## Low Head Type – Creep (0.5~5ton)




Capacity(Ton)		1		2		2.8		3		5						
Type	Hoisting and Traversing Speed	High-HIGH	E-CKL1-H06-MH		E-CKL2-H06-MH		E-CKL2,8-H06-MH		E-CKL3-H06-MH		E-CKL5-H06-MH					
		High-LOW	E-CKL1-H06-ML		E-CKL2-H06-ML		E-CKL2,8-H06-ML		E-CKL3-H06-ML		E-CKL5-H06-ML					
Hoist	Max. Lift(m)		6		6		6		6		6					
	Hoisting Speed(m/min) High/Creep	50Hz	10/1		8,4/0,84		7,5/0,75		7,5/0,75		4,7/0,47					
		60Hz	12/1,2		10/1		9/0,9		9/0,9		5,6/0,56					
	Hoisting Motor (Kw x P)	High Speed	2,4x4		3,7x4		4,8x4		5,5x4		5,5x6					
		Creep Speed	0,4x4		0,4x4		1,1x4		1,1x4		1x6					
	Wire Rope	Construction	6x19		6x19		6x37		6x37		6x37					
Dia.(min)x no. of Ropes		Ø6x4 Falls		Ø8x4 Falls		Ø9x4 Falls		Ø9x4 Falls		Ø11,2x4 Falls						
Brake		DC Magnet Disc Brake														
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24		20/24		20/24		20/24		20/24					
		Low Speed 50/60(Hz)	13/16		13/16		13/16		13/16		13/16					
	Traversing Motor (Kw x P)	High Speed	0,4x4		0,75x4		0,75x4		0,75x4		0,75x4					
		Low Speed	0,2x6		0,5x6		0,5x6		0,5x6		0,5x6					
Brake		DC Magnet Disc Brake														
Dimensions(approx)(mm)	H	550		620		620		620		800						
	A	760		825		920		920		1000						
	B	765		785		780		780		980						
	C	635		665		740		740		815						
	D	290		385		565		565		635						
	G	255		260		260		260		275						
	K	200		225		225		225		275						
	E	330		375		375		375		425						
F	615		635		630		630		730							
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(I-BEAM)	S	T	U	S	T	U	S	T	U	S	T	U	S	T	U
	I-200x100x7t~	38	46	144	33	46	172	-	-	-	-	-	-	-	-	-
	I-250x125x7,5t~	30	71	153	24	71	182	25	71	182	23	71	182	-	-	-
	I-300x150x10t~	28	96	155	22	96	182	23	96	182	23	96	182	37	86	224
I-450x175x13t~	-	-	-	-	-	-	-	-	-	-	-	-	34	111	228	
Min.Radius of curvature(m)		1,5		1,8		1,8		1,8		2,3						
Weight(approx)(kg)		355		520		625		625		855						

※ EX-KL □□□□-C-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST **Explosion Proof Type**

## Double Rail Type – Creep (2~5ton)




Capacity(Ton)		2	2,8	3	5	
Type	Hoisting and Traversing Speed	High-HIGH	E-CKD02-H12-MH	E-CKD2,8-H12-MH	E-CKD03-H12-MH	E-CKD05-H12-MH
		High-Low	E-CKD02-H12-ML	E-CKD2,8-H12-ML	E-CKD03-H12-ML	E-CKD05-H12-ML
Hoist	Max. Lift(m)		12	12	12	12
	Hoisting Speed(m/min) High/Creep	50Hz	8,4/0,84	7,5/0,75	4,7/0,47	3,1/0,31
		60Hz	10/1	9/0,9	9/0,9	5,6/0,56
	Hoisting Motor (Kw x P)	High Speed	3,7x4	4,8x4	5,5x4	5,5x6
		Creep Speed	0,4x4	1,1x4	1,0x6	1,0x6
	Wire Rope	Construction	6x37	6x37	6x37	6x37
Dia,(min)x no. of Ropes		Ø8x4 Falls	Ø9x4 Falls	Ø9x4 Falls	Ø12,5x4 Falls	
Brake		DC Magnet Disc Brake				
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24	20/24	20/24	20/24
		Low Speed 50/60(Hz)	13/16	13/16	13/16	13/16
	Traversing Motor (Kw x P)	High Speed	0,75x4	0,75x4	0,75x4	0,75x4
		Low Speed	0,5x6	0,5x6	0,5x6	0,5x6
Brake		DC Magnet Disc Brake				
Dimensions(approx)(mm)	H	415	420	420	510	
	R	950	950	950	1150	
	A	465	465	465	510	
	B	390	390	390	470	
	C	630	730	730	760	
	G	955	1070	1070	1220	
	K	890	896	896	960	
	W	650	650	650	760	
	S	45	45	45	42	
	D	47	47	47	47	
	L	680	690	690	890	
	M	115	115	115	125	
	N	90	90	90	110	
P	Ø140	Ø140	Ø140	Ø165		
Q	Ø170	Ø170	Ø170	Ø190		
Weight(approx.)(kg)		570	570	570	980	
Rail(kg/m)		15 Kg/M	15 Kg/M	15 Kg/M	15 Kg/M	

※ EX-KD □□□□-C-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST **Explosion Proof Type**

## Double Rail Type – Creep (7.5~30ton)



Capacity(Ton)		7.5	10	15	20	30	
Type	Hoisting and Traversing Speed	High-HIGH	E-CKD7.5-H12-MH	E-CKD10-H12-MH	E-CKD15-H12-MH	E-CKD20-H12-MH	E-CKD30-H12-MH
		High-Low	E-CKD7.5-H12-ML	E-CKD10-H12-ML	E-CKD15-H12-ML	E-CKD20-H12-ML	E-CKD30-H12-ML
Hoist	Max. Lift(m)		12	12	12	12	12
	Hoisting Speed(m/min) High/Creep	50Hz	3,1/0,31	3,7/0,37	3,7/0,37	3,5/0,35	2,3/0,23
		60Hz	3,8/0,38	4,5/0,45	4,5/0,45	4,2/0,42	2,8/0,28
	Hoisting Motor (Kw x P)	High Speed	5,5x6	9x8	13x8	17x8	17x8
		Creep Speed	1x6	1,1x8	1,8x8	1,8x8	1,8x8
	Wire Rope	Construction	6x37	6x37	6x37	6x37	6x37
Dia,(min)x no. of Ropes		Ø14x4 Falls	Ø16x4 Falls	Ø20x4 Falls	Ø22,4x4 Falls	Ø22,4x6 Falls	
Brake		DC Magnet Disc Brake					
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	12,5/15	12,5/15	12,5/15	12,5/15	12,5/15
		Low Speed 50/60(Hz)	8,3/10	8,3/10	8,3/10	8,3/10	8,3/10
	Traversing Motor (Kw x P)	High Speed	0,75x4	0,75x4	1,5x4	1,5x4	1,5x4x2
		Low Speed	0,5x6	0,5x6	1x6	1x6	1x6x2
Brake		DC Magnet Disc Brake					
Dimensions(approx)(mm)		H	730	775	995	1175	1480
		R	1150	1150	1200	1300	1800
		A	525	565	625	670	940
		B	480	510	555	610	940
		C	775	965	960	1000	1080
		G	1255	1345	1455	1550	1810
		K	945	1135	1140	1285	1545
		W	800	865	920	1000	1540
		D	58	58	58	58	70
		L	850	850	870	935	1420
		M	120	120	130	140	180
		N	95	100	130	140	180
		P	Ø165	Ø165	Ø180	Ø220	Ø250
Q	Ø195	Ø195	Ø210	Ø250	Ø280		
Weight(approx.)(kg)		1065	1375	2030	2495	3646	
Rail(kg/m)		15 Kg/M	15 Kg/M	22 Kg/M	22 Kg/M	30 Kg/M	

※ EX-KD □□□□-C-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST **Explosion Proof Type**

## Double Rail Type – Creep (35~70ton)




Capacity(Ton)			35	50	60	70
Type	Hoisting and Traversing Speed	High-HIGH	E-CKD35-H12-MH	E-CKD50-H12-MH	E-CKD60-H12-MH	E-CKD70-H12-MH
		High-Low	E-CKD35-H12-ML	E-CKD50-H12-ML	E-CKD60-H12-ML	E-CKD70-H12-ML
Hoist	Max. Lift(m)		12	12	12	12
	Hoisting Speed(m/min) High/Creep	50Hz	4/0,4	2,7/0,27	2/0,2	2/0,2
		60Hz	4,8/0,48	3,2/0,32	2,4/0,24	2,4/0,24
	Hoisting Motor (Kw x P)	High Speed	33x6	33x6	33x6	33x6
		Creep Speed	3,7x4	3,7x4	3,7x4	3,7x4
	Wire Rope	Construction	6xFI(25)	6xFI(25)	6xFI(25)	6xFI(25)
Dia.(min)x no. of Ropes		Ø28x4 Falls	Ø28x6 Falls	Ø28x8 Falls	Ø28x8 Falls	
Brake			DC Magnet Disc Brake			
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	12,5/15	12,5/15	12,5/15	12,5/15
		Low Speed 50/60(Hz)	8,3/10	8,3/10	8,3/10	8,3/10
	Traversing Motor (Kw x P)	High Speed	2,2x4	2,2x4x2	2,2x4x2	3,7x4x2
		Low Speed	1,5x6	1,5x6x2	1,5x6x2	2,2x6x2
Brake			DC Magnet Disc Brake			
Dimensions(approx)(mm)	H		1490	1680	1780	1780
	R		1600	2300	2800	2800
	A		1025	1432	1525	1525
	B		955	1243	1150	1150
	C		1292	1400	1400	1400
	G		1835	2160	2410	2410
	K		1460	1815	2065	2065
	W		1550	2125	2125	2075
	D		70	80	80	80
	L		1044	1430	1930	1930
	M		215	275	275	300
	N		215	275	275	300
P		Ø355	Ø450	Ø450	Ø500	
Q		Ø395	Ø490	Ø490	Ø540	
Weight(approx.)(kg)			5550	7350	9200	9350
Rail(kg/m)			37 Kg/M	50 Kg/M	50 Kg/M	50 Kg/M

※ EX-KD □□□□-C-H□□ Hoist Name Plate shall be typed as per above coding




# WIRE HOIST **Explosion Proof Type for Special** Regular Type – Normal (4~10ton)



Capacity(Ton)		4		6		8		10													
Type	Hoisting Speed	High-High	E-KSN04-H06-MH		E-KSN06-H06-MH		E-KSN08-H06-MH		E-KSN10-H06-MH												
		High-Low	E-KSN04-H06-ML		E-KSN06-H06-ML		E-KSN08-H06-ML		E-KSN10-H06-ML												
		Low-High	E-KSN04-L06-MH		E-KSN06-L06-MH		E-KSN08-L06-MH		E-KSN10-L06-MH												
		Low-Low	E-KSN04-L06-ML		E-KSN06-L06-ML		E-KSN08-L06-ML		E-KSN10-L06-ML												
Hoist	Max. Lift(m)		6(12)		6(12)		6(12)		6(12)												
	Hoisting Speed (m/min)	High Speed 50/60(Hz)	4,2/5,0		3,8/4,5		2,3/2,8		2,3/2,8												
		Low Speed 50/60(Hz)	2,1/2,5		2,0/2,3		1,8/2,1		1,8/2,1												
	Hoisting Motor (Kw x P)	High Speed	3,7x4		5,5x4		5,5x6		5,5x6												
		Low Speed	1,8x8		2,8x8		4,2x8		4,2x8												
	Wire Rope	Construction	6x37		6x37		6x37		6x37												
Dia.(min)x no. of Ropes		Ø10x4 Falls		Ø12,5x4 Falls		Ø14x4 Falls		Ø16x4 Falls													
Brake		DC Magnet Disc Brake																			
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24		20/24		20/24		20/24												
		Low Speed 50/60(Hz)	13/16		13/16		13/16		13/16												
	Traversing Motor (Kw x P)	High Speed	0,75x4		0,75x4		0,75x4		0,75x4												
		Low Speed	0,5x6		0,5x6		0,5x6		0,5x6												
Brake		DC Magnet Disc Brake																			
Dimensions(approx)(mm)	H	1050		1050		1390		1390													
	A	579(776)		639(846)		655(847)		681(896)													
	B	638(835)		648(855)		735(927)		761(976)													
	D	415		465		530		550													
	G	520(920)		550(960)		530(910)		580(1010)													
	M	260		260		275		275													
	N	225		225		275		275													
L	67(186)		67(274)		65(203)		55(270)														
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(I-BEAM)	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U
	I-300x150x19t~	665	332	24	96	182	665	332	23	96	122	-	-	-	-	-	-	-	-	-	-
	I-450x175x26t~	678	332	22	121	127	678	332	21	121	127	685	416	34	111	228	685	416	34	111	228
	I-600x190x25t~	-	-	-	-	-	-	-	-	-	-	693	416	32	118	230	693	416	32	118	230
H-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(H-BEAM)	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U
	H-Hx150x20t~	665	332	24	96	184	665	332	21	121	182	-	-	-	-	-	-	-	-	-	-
	H-Hx200x26t~	690	332	21	146	191	695	332	15	171	191	685	416	31	111	232	710	416	34	128	231
	H-Hx300x30t~	-	-	-	-	-	-	-	-	-	-	710	416	27	211	236	760	416	28	228	235
Min.Radius of curvature(m)		For Straight Only(Curvature Hinge Type Option)																			
Weight(approx)(kg)		384(424)		454(530)		708(770)		728(790)													

※ EX-KSN □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding


# WIRE HOIST **Explosion Proof Type for Special** Low Head Type – Normal (4~10ton)



Capacity(Ton)		4					6					8					10					
Type	Hoisting Speed	High-High	E-KSL04-H06-MH					E-KSL06-H06-MH					E-KSL08-H06-MH					E-KSL10-H06-MH				
		High-Low	E-KSL04-H06-ML					E-KSL06-H06-ML					E-KSL08-H06-ML					E-KSL10-H06-ML				
		Low-High	E-KSL04-L06-MH					E-KSL06-L06-MH					E-KSL08-L06-MH					E-KSL10-L06-MH				
		Low-Low	E-KSL04-L06-ML					E-KSL06-L06-ML					E-KSL08-L06-ML					E-KSL10-L06-ML				
Hoist	Max. Lift(m)		6(12)					6(12)					6(12)					6(12)				
	Hoisting Speed (m/min)	High Speed 50/60(Hz)	4,2/5,0					3,8/4,5					2,3/2,8					2,3/2,8				
		Low Speed 50/60(Hz)	2,1/2,5					2,0/2,3					1,8/2,1					1,8/2,1				
	Hoisting Motor (Kw x P)	High Speed	3,7x4					5,5x4					5,5x6					5,5x6				
		Low Speed	1,8x8					2,8x8					4,2x8					4,2x8				
	Wire Rope	Construction	6x37					6x37					6x37					6x37				
Dia.(min)x no. of Ropes		Ø10x4 Falls					Ø12,5x4 Falls					Ø14x4 Falls					Ø16x4 Falls					
Brake		DC Magnet Disc Brake																				
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24					20/24					20/24					20/24				
		Low Speed 50/60(Hz)	13/16					13/16					13/16					13/16				
	Traversing Motor (Kw x P)	High Speed	0,75x4					0,75x4					0,75x4					0,75x4				
		Low Speed	0,5x6					0,5x6					0,5x6					0,5x6				
Brake		DC Magnet Disc Brake																				
Dimensions(approx)(mm)	H	600					600					800					800					
	A	609(806)					669(877)					680(877)					711(926)					
	B	638(835)					648(855)					735(927)					761(976)					
	G	770(1170)					790(1200)					770(1160)					830(1260)					
	M	203(200)					203(205)					300(297)					296(296)					
	N	149(146)					199(201)					225(222)					221(221)					
	L	67(186)					67(274)					65(203)					55(270)					
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(I-BEAM)	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	
	I-300x150x19t~	565	705	25	68	266	565	705	25	68	266	-	-	-	-	-	-	-	-	-	-	
	I-450x175x26t~	578	718	18	93	273	578	718	18	93	273	683	803	20	93	333	683	803	20	93	333	
	I-600x190x25t~	-	-	-	-	-	-	-	-	-	-	691	811	19	108	332	691	811	19	108	332	
H-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(H-BEAM)	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	
	H-Hx150x20t~	565	705	25	68	265	565	705	25	68	265	-	-	-	-	-	-	-	-	-	-	
	H-Hx200x26t~	590	718	19	118	271	590	730	19	118	271	696	816	20	118	327	696	816	20	118	327	
	H-Hx300x30t~	-	-	-	-	-	-	-	-	-	-	746	866	16	218	331	746	866	16	218	331	
Min.Radius of curvature(m)		For Straight Only																				
Weight(approx)(kg)		399(439)					469(545)					728(790)					748(810)					

※ EX-KSL □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding


# WIRE HOIST **Explosion Proof Type for Special** Double Low Head Type – Normal (4~10ton)



Capacity(Ton)		4	6	8	10	
Type	Hoisting Speed	High-High	E-KSP04-H12-MH	E-KSP06-H12-MH	E-KSP08-H12-MH	E-KSP10-H12-MH
		High-Low	E-KSP04-H12-ML	E-KSP06-H12-ML	E-KSP08-H12-ML	E-KSP10-H12-ML
		Low-High	E-KSP04-L12-MH	E-KSP06-L12-MH	E-KSP08-L12-MH	E-KSP10-L12-MH
		Low-Low	E-KSP04-L12-ML	E-KSP06-L12-ML	E-KSP08-L12-ML	E-KSP10-L12-ML
Hoist	Max. Lift(m)		12	12	12	12
	Hoisting Speed (m/min)	High Speed 50/60(Hz)	4,2/5,0	3,8/4,5	2,3/2,8	2,3/2,8
		Low Speed 50/60(Hz)	2,1/2,5	2,0/2,3	1,8/2,1	1,8/2,1
	Hoisting Motor (Kw x P)	High Speed	3,7x4	5,5x4	5,5x6	5,5x6
		Low Speed	1,8x8	2,8x8	4,2x8	4,2x8
	Wire Rope	Construction	6x37	6x37	6x37	6x37
Dia.(min)x no. of Ropes		Ø10x4 Falls	Ø12,5x4 Falls	Ø14x4 Falls	Ø16x4 Falls	
Brake		DC Magnet Disc Brake				
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24	20/24	20/24	20/24
		Low Speed 50/60(Hz)	13/16	13/16	13/16	13/16
	Traversing Motor (Kw x P)	High Speed	0,75x4	0,75x4	0,75x4	0,75x4
		Low Speed	0,5x6	0,5x6	0,5x6	0,5x6
Brake		DC Magnet Disc Brake				
Dimensions(approx)(mm)	H	510	510	755	755	
	R	1150	1150	1150	1150	
	A	560	560	705	705	
	B	560	560	705	705	
	C	760	760	945	945	
	G	836	880	924	976	
	K	777	821	844	896	
	W	850	850	1070	1070	
	D	47	47	58	58	
	L	767	798	732	824	
	M	135	135	170	170	
	N	135	135	170	170	
	P	Ø165	Ø165	Ø165	Ø165	
	Q	Ø195	Ø165	Ø195	Ø195	
T	334	334	374	382		
S	519	536	472	537		
Weight(approx.)(kg)		540	540	960	975	
Rail(kg/m)		15 Kg/M	15 Kg/M	15 Kg/M	15 Kg/M	

※ EX-KSP □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding


# WIRE HOIST Explosion Proof Type for Special Double Rail Type – Normal (4~10ton)



Capacity(Ton)		4	6	8	10	
Type	Hoisting Speed	High-High	E-KSD04-H12-MH	E-KSD06-H12-MH	E-KSD08-H12-MH	E-KSD10-H12-MH
		High-Low	E-KSD04-H12-ML	E-KSD06-H12-ML	E-KSD08-H12-ML	E-KSD10-H12-ML
		Low-High	E-KSD04-L12-MH	E-KSD06-L12-MH	E-KSD08-L12-MH	E-KSD10-L12-MH
		Low-Low	E-KSD04-L12-ML	E-KSD06-L12-ML	E-KSD08-L12-ML	E-KSD10-L12-ML
Hoist	Max. Lift(m)		12	12	12	12
	Hoisting Speed (m/min)	High Speed 50/60(Hz)	4,2/5,0	3,8/4,5	2,3/2,8	2,3/2,8
		Low Speed 50/60(Hz)	2,1/2,5	2,0/2,3	1,8/2,1	1,8/2,1
	Hoisting Motor (Kw x P)	High Speed	3,7x4	5,5x4	5,5x6	5,5x6
		Low Speed	1,8x8	2,8x8	4,2x8	4,2x8
	Wire Rope	Construction	6x37	6x37	6x37	6x37
Dia.(min)x no. of Ropes		Ø10x4 Falls	Ø12,5x4 Falls	Ø14x4 Falls	Ø16x4 Falls	
Brake		DC Magnet Disc Brake				
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24	20/24	20/24	20/24
		Low Speed 50/60(Hz)	13/16	13/16	13/16	13/16
	Traversing Motor (Kw x P)	High Speed	0,75x4	0,75x4	0,75x4	0,75x4
		Low Speed	0,5x6	0,5x6	0,5x6	0,5x6
Brake		DC Magnet Disc Brake				
Dimensions(approx)(mm)	H	350	350	580	580	
	R	1150	1150	1150	1150	
	A	544	544	654	654	
	B	528	528	638	638	
	C	910	950	1080	1080	
	G	836	880	924	976	
	K	777	821	844	896	
	W	850	850	1050	1050	
	D	47	47	58	58	
	L	767	798	732	824	
	M	119	119	129	129	
	N	103	103	113	113	
	P	Ø165	Ø165	Ø165	Ø165	
	Q	Ø195	Ø165	Ø195	Ø195	
T	334	334	374	382		
S	519	536	472	537		
Weight(approx.)(kg)		600	610	1030	1060	
Rail(kg/m)		15 Kg/M	15 Kg/M	15 Kg/M	15 Kg/M	

※ EX-KSD □□□□-N-H□□ Hoist Name Plate shall be typed as per above coding


# WIRE HOIST Explosion Proof Type for Special Regular Type – Creep (4~10ton)



Capacity(Ton)		4		6		8		10													
Type	Hoisting Speed	High-HIGH	E-CKSN04-H06-MH		E-CKSN06-H06-MH		E-CKSN08-H06-MH		E-CKSN10-H06-MH												
		High-Low	E-CKSN04-H06-ML		E-CKSN06-H06-ML		E-CKSN08-H06-ML		E-CKSN10-H06-ML												
Hoist	Max. Lift(m)		6(12)		6(12)		6(12)		6(12)												
	Hoisting Speed(m/min) High/Creep	50Hz	4,2/0,42		3,8/0,38		2,3/0,23		2,3/0,23												
		60Hz	5,0/0,5		4,5/0,45		2,8/0,28		2,8/0,28												
	Hoisting Motor (Kw x P)	High Speed	3,7x4		5,5x4		5,5x6		5,5x6												
		Creep Speed	0,4x4		1,1x4		1,0x6		1,0x6												
Wire Rope	Construction	6x37		6x37		6x37		6x37													
	Dia.(min)x no. of Ropes	Ø10x4 Falls		Ø12,5x4 Falls		Ø14x4 Falls		Ø16x4 Falls													
Brake		DC Magnet Disc Brake																			
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24		20/24		20/24		20/24												
		Low Speed 50/60(Hz)	13/16		13/16		13/16		13/16												
	Traversing Motor (Kw x P)	High Speed	0,75x4		0,75x4		0,75x4		0,75x4												
		Low Speed	0,5x6		0,5x6		0,5x6		0,5x6												
Brake		DC Magnet Disc Brake																			
Dimensions(approx)(mm)	H	1050		1050		1390		1390													
	A	579(776)		639(846)		655(847)		681(896)													
	B	803(1000)		883(1090)		970(1162)		996(1211)													
	D	415		565		530		550													
	G	520(920)		550(960)		530(910)		580(1010)													
	M	260		260		275		275													
	N	225		225		275		275													
	L	67(186)		67(274)		225(222)		55(270)													
E	375		555		655		655														
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(I-BEAM)	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U
	I-300x150x19t~	665	332	24	96	182	665	332	23	96	122	-	-	-	-	-	-	-	-	-	-
	I-450x175x26t~	678	332	22	121	127	678	332	21	121	127	685	416	34	111	228	685	416	34	111	228
	I-600x190x25t~	-	-	-	-	-	-	-	-	-	-	693	416	32	118	230	693	416	32	118	230
H-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(H-BEAM)	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U
	H-Hx150x20t~	665	332	24	96	184	665	332	21	121	182	-	-	-	-	-	-	-	-	-	-
	H-Hx200x26t~	690	332	21	146	191	690	332	15	171	191	685	416	31	111	232	710	416	34	128	231
	H-Hx300x30t~	-	-	-	-	-	-	-	-	-	-	710	416	27	211	236	760	416	28	228	235
Min.Radius of curvature(m)		For Straight Only(Curvature Hinge Type Option)																			
Weight(approx)(kg)		454(484)		524(600)		788(850)		808(870)													

※ EX-KSN □□□□-C-H□□ Hoist Name Plate shall be typed as per above coding


# WIRE HOIST Explosion Proof Type for Special Low Head Type – Creep (4~10ton)



Capacity(Ton)		4					6					8					10					
Type	Hoisting Speed	High-HIGH	E-CKSL04-H06-MH					E-CKSL06-H06-MH					E-CKSL08-H06-MH					E-CKSL10-H06-MH				
		High-Low	E-CKSL04-H06-ML					E-CKSL06-H06-ML					E-CKSL08-H06-ML					E-CKSL10-H06-ML				
Hoist	Max. Lift(m)		6(12)					6(12)					6(12)					6(12)				
	Hoisting Speed(m/min) High/Creep	50Hz	4,2/0,42					3,8/0,38					2,3/0,23					2,3/0,23				
		60Hz	5,0/0,5					4,5/0,45					2,8/0,28					2,8/0,28				
	Hoisting Motor (Kw x P)	High Speed	3,7x4					5,5x4					5,5x6					5,5x6				
		Creep Speed	0,4x4					1,1x4					1,0x6					1,0x6				
Wire Rope	Construction	6x37					6x37					6x37					6x37					
	Dia.(min)x no. of Ropes	Ø10x4 Falls					Ø12,5x4 Falls					Ø14x4 Falls					Ø16x4 Falls					
Brake		DC Magnet Disc Brake																				
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24					20/24					20/24					20/24				
		Low Speed 50/60(Hz)	13/16					13/16					13/16					13/16				
	Traversing Motor (Kw x P)	High Speed	0,75x4					0,75x4					0,75x4					0,75x4				
		Low Speed	0,5x6					0,5x6					0,5x6					0,5x6				
Brake		DC Magnet Disc Brake																				
Dimensions(approx)(mm)	H	600					600					800					800					
	A	609(806)					669(876)					685(877)					711(926)					
	B	803(1000)					883(1090)					970(1162)					996(1211)					
	G	770(1170)					790(1200)					770(1160)					830(1260)					
	M	203(200)					203(205)					300(297)					296(296)					
	N	149(146)					199(201)					225(222)					221(221)					
	L	67(186)					67(274)					65(203)					55(270)					
E	375					555					655					655						
I-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(I-BEAM)	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	
	I-300x150x19t~	565	705	25	68	266	565	705	25	68	266	-	-	-	-	-	-	-	-	-	-	
	I-450x175x26t~	578	718	18	93	273	578	718	18	93	273	683	803	20	93	333	683	803	20	93	333	
	I-600x190x25t~	-	-	-	-	-	-	-	-	-	-	691	811	19	108	332	691	811	19	108	332	
H-BEAM TYPE DIMENSIONS (APPROX.)(MM)	axbxt(H-BEAM)	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	C	F	S	T	U	
	H-Hx150x20t~	565	705	25	68	265	565	705	25	68	265	-	-	-	-	-	-	-	-	-	-	
	H-Hx200x26t~	590	730	19	118	271	590	730	19	118	271	696	816	20	118	327	696	816	20	118	327	
	H-Hx300x30t~	-	-	-	-	-	-	-	-	-	-	746	866	16	218	331	746	866	16	218	331	
Min.Radius of curvature(m)		For Straight Only																				
Weight(approx)(kg)		469(509)					539(615)					808(870)					828(880)					

※ EX-KSL □□□□-C-H□□ Hoist Name Plate shall be typed as per above coding

# WIRE HOIST **Explosion Proof Type for Special** Double Rail Type – Creep (4~10ton)




VIEW from X  
(Creep Side)

Capacity(Ton)		4	6	8	10	
Type	Hoisting Speed	High-HIGH	E-CKSP04-H12-MH	E-CKSP06-H12-MH	E-CKSP08-H12-MH	E-CKSP10-H12-MH
		High-Low	E-CKSP04-H12-ML	E-CKSP06-H12-ML	E-CKSP08-H12-ML	E-CKSP10-H12-ML
Hoist	Max. Lift(m)		12	12	12	12
	Hoisting Speed(m/min) High/Creep	50Hz	4,2/0,42	3,8/0,38	2,3/0,23	2,3/0,23
		60Hz	5,0/0,5	4,5/0,45	2,8/0,28	2,8/0,28
	Hoisting Motor (Kw x P)	High Speed	3,7x4	5,5x4	5,5x6	5,5x6
		Creep Speed	0,4x4	1,1x4	1,0x6	1,0x6
Wire Rope	Construction	6x37	6x37	6x37	6x37	
	Dia.(min)x no. of Ropes	Ø10x4 Falls	Ø12,5x4 Falls	Ø14x4 Falls	Ø16x4 Falls	
Brake		DC Magnet Disc Brake				
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24	20/24	20/24	20/24
		Low Speed 50/60(Hz)	13/16	13/16	13/16	13/16
	Traversing Motor (Kw x P)	High Speed	0,75x4	0,75x4	0,75x4	0,75x4
		Low Speed	0,5x6	0,5x6	0,5x6	0,5x6
Brake		DC Magnet Disc Brake				
Dimensions(approx)(mm)	H	510	510	755	755	
	R	1150	1150	1150	1150	
	A	560	560	705	705	
	B	560	560	705	705	
	C	760	760	945	945	
	G	1000	1090	1162	1162	
	K	777	821	844	896	
	W	850	850	1070	1070	
	D	47	47	58	58	
	L	767	798	732	824	
	M	135	135	170	170	
	N	135	135	170	170	
	P	Ø165	Ø165	Ø165	Ø165	
	Q	Ø195	Ø165	Ø195	Ø195	
E	375	375	425	425		
T	334	334	374	382		
S	519	536	472	537		
Weight(approx.)(kg)		610	620	1040	1055	
Rail(kg/m)		15 Kg/M	15 Kg/M	15 Kg/M	15 Kg/M	

※ EX-KSP □□□□-C-H□□ Hoist Name Plate shall be typed as per above coding



# WIRE HOIST Explosion Proof Type for Special Double Rail Type – Creep (4~10ton)



Capacity(Ton)		4	6	8	10	
Type	Hoisting Speed	High-HIGH	E-CKSD04-H12-MH	E-CKSD06-H12-MH	E-CKSD08-H12-MH	E-CKSD10-H12-MH
		High-Low	E-CKSD04-H12-ML	E-CKSD06-H12-ML	E-CKSD08-H12-ML	E-CKSD10-H12-ML
Hoist	Max. Lift(m)		12	12	12	12
	Hoisting Speed(m/min) High/Creep	50Hz	4,2/0,42	3,8/0,38	2,3/0,23	2,3/0,23
		60Hz	5,0/0,5	4,5/0,45	2,8/0,28	2,8/0,28
	Hoisting Motor (Kw x P)	High Speed	3,7x4	5,5x4	5,5x6	5,5x6
		Creep Speed	0,4x4	1,1x4	1,0x6	1,0x6
Wire Rope	Construction	6x37	6x37	6x37	6x37	
	Dia.(min)x no. of Ropes	Ø10x4 Falls	Ø12,5x4 Falls	Ø14x4 Falls	Ø16x4 Falls	
Brake		DC Magnet Disc Brake				
Traversing	Traversing Speed (m/min)	High Speed 50/60(Hz)	20/24	20/24	20/24	20/24
		Low Speed 50/60(Hz)	13/16	13/16	13/16	13/16
	Traversing Motor (Kw x P)	High Speed	0,75x4	0,75x4	0,75x4	0,75x4
		Low Speed	0,5x6	0,5x6	0,5x6	0,5x6
Brake		DC Magnet Disc Brake				
Dimensions(approx)(mm)	H	350	350	580	580	
	R	1150	1150	1150	1150	
	A	544	544	654	654	
	B	528	528	638	638	
	C	910	950	1080	1080	
	G	1000	1090	1162	1211	
	K	777	821	844	896	
	W	850	850	1050	1050	
	D	47	47	58	58	
	L	767	798	732	824	
	M	119	119	129	129	
	N	103	103	113	113	
	P	Ø165	Ø165	Ø165	Ø165	
	Q	Ø195	Ø165	Ø195	Ø195	
E	375	375	425	425		
T	334	334	374	382		
S	519	536	472	537		
Weight(approx.)(kg)		670	680	1110	1140	
Rail(kg/m)		15 Kg/M	15 Kg/M	15 Kg/M	15 Kg/M	


※ EX-KSD □□□□-C-H□□ Hoist Name Plate shall be typed as per above coding

# LS HOIST (only for LScrane)



## ■ Construction cost saving crane

This is good for factory who needs larger space due to big sized production. This is also good for municipal apartment factory whose roof is low and whose work is precision assembly. In order to meet such requirement, we reduced absolute dimension. When compared with same grade single girder crane, we reduced crane self height by 2m from 3.6m to 1.6m.





■ MHO 20 tons Span 20m




■ DHO 20 tons Span 20m



## ■ Extraordinary crane girder size

This crane has single girder size while suffices double girder crane hook height. This means self weight has decreased by 44% compared with same grade double girder crane.





Redline is Bending part,  
Blueline is Welding part



### ■ New Concept Saddle

As there is no extruding gear, lifetime is very long.  
It prevents environment contamination.  
It also keeps working area clean.

### ■ VVVF Inverter Control

As there is no vibration, noise and slip,  
even unskilled worker can use easily and  
this will enables safe and precise handling.

### ■ Clean Crane

This is environment friendly crane that has low noise and  
low vibration that is good for a work place where vibration  
and noise affect to the production.




### ■ Innovative Hook Height

This crane will suffices incredible  
hook height from normal single girder .  
It satisfies the hook height of  
double girder crane or even above.



# LS HOIST Only for LScrane


2 ~ 10 ton



Model		LS 200			LS 300			LS 400			LS 500			LS 600			LS 800			LS 1000		
Capacity(ton)		2			3			4			5			6			8			10		
Hoist	lift(m)	12	18	24	12	18	24	6	9	12	12	18	24	6	9	12	12	18	24	12	18	24
	Speed(m/min)	5	10		4,5	9		2,5	5		4,2	5,6		2,3	4,5		2,8	3,8		4,5		
	Motor(kwXP)	1,8x8	3,7x4		2,8x8	5,5x4		1,8x8	3,7x4		4,2x8	3,5x6		2,8x8	5,5x4		4,5x8	6,0x6		9x8		
	Wire Rope (Dia(φ)×No.of Ropes)	8x4			9x4			8x8			12,5x4			9x8			14x4			16x4		
Traversing	Speed(m/min)	10	16		10	16		10	16		12	19		12	19		12	19		12	19	
	Motor(kwXP)	0,5x6	0,75x4		0,5x6	0,75x4		0,5x6	0,75x4		0,5x6	0,75x4		0,5x6	0,75x4		0,5x6	0,75x4		0,5x6	0,75x4	
	Wheel(φ)	140			140			140			160			160			160			160		
	Rail(kg/m)	15			15			15			15			15			15			15		
Dimension (mm)	A	816	1116	1296	816	1116	1416	816	1116	1296	1011	1511	1861	818	1118	1418	989	1489	1839	989	1489	1839
	B	750	900	990	750	900	1050	750	900	990	847	1097	1272	706	856	1006	836	1086	1261	953	1203	1378
	C	808	958	1048	808	958	1108	808	958	1048	938	1188	1363	809	959	1109	927	1177	1352	999	1249	1424
	D	614			614			614			664			614			734			734		
	E	751			751			751			751			751			751			751		
	F	215			215			215			215			245			235			235		
	G	220			250			270			280			261			300			325		
	H	550			600			750			825			915			900			1015		
Weight (kg)	450	620	790	550	750	950	550	720	890	950	1160	1220	750	950	1150	1000	1280	1400	1365	1550	1690	


# LS HOIST Only for LScrane

15 ~ 40 ton



Model		LS 1500			LS 2000			LS 3000			LS 4000		
Capacity(ton)		15			20			30			40		
Hoist	lift(m)	12	18	24	12	18	24	8	12	16	6	9	12
	Speed(m/min)	4.5			4.2			2.8			2.1		
	Motor(kwXP)	13x8			17x8			17x8			17x8		
	Wire Rope (Dia(φ)×No.of Ropes)	20x4			22.4x4			22.4x6			22.4x8		
Traversing	Speed(m/min)	16	24		16	24		19	30		16	24	
	Motor(kwXP)	1,0x6	1,5x4		1,0x6	1,5x4		1,0x6 (2Units)	1,5x4 (2Units)		1,5x6 (2Units)	2,2x4 (2Units)	
	Wheel(φ)	200			200			250			315		
	Rail(kg/m)	22			22			30			37		
Dimension (mm)	A	1032	1482	2032	1113	1613	2013	1110	1610	2010	1108	1608	2008
	B	1006	1231	1506	1217	1467	1667	1216	1466	1666	1215	1465	1665
	C	1079	1304	1579	1164	1414	1614	1163	1413	1613	1162	1412	1612
	D	950			1005			1150			1250		
	E	950			950			950			950		
	F	370			375			400			450		
	G	390			430			520			600		
H	1080			1240			1480			1700			
Weight	(kg)	2070	2400	2570	2600	2895	3070	3500	4000	4500	5500	6000	6500

# CHAIN HOIST



1. Electrical equipment cover
2. Electrical Components
3. Gearbox
4. Slipping clutch
5. Top hook
6. Center frame
7. Load sheave
8. Motor frame
9. Rotor
10. Stator
11. Brake Cover
12. Brake
13. Bottom hook
14. Chain bucket
15. Push button

## EXPLANATION OF HOIST DESIGNATION

**KG T - S 1000 - AF**

\*Other  
 SP = Single Phase  
 AF = A Frame  
 BF = B Frame  
 CF = C Frame

\*Hoist capacity (KG)  
 1000KG, 2000KG...

\*Hoisting speed  
 S = Single Speed  
 D = Dual speed

\*Travesing method  
 O = Ordinary type  
 T = Motor Driven Trolley  
 L = Low head type

KG CRANES

# MAIN PRODUCTS

## Electric Chain Hoist



Suspension Type  
1/2ton~20ton



Motor Trolley Type  
1/2ton~20ton



Low-Head Type  
1/2ton~5ton



Single Phase Hoist  
1/2ton~2ton

## Crane & Components of Crane



Crane



Saddle



Geared Motor



Soft Starter

# SELECTION CRITERIA

**You can use CHAIN HOIST for a long time without any trouble if you select it properly according**

KG Cranes Chain Hoists are allocated to mechanism groups in accordance with the following regulations. Under the allowance of the following mechanism groups, the hoist should be operated and should not exceed the nominal values. On each identification plate The following is indicated.

Hook suspension chain hoist : FEM 9.511 (Hoist = FEM 2m 40% ED)

Motor trolley mounted series : FEM 9.511 (Hoist/Trolley + FEM 2m 1Am 40 / 25% ED)

Starting frequency = 240 time/Hr.

### FEM Mechanism Group 9.511


(Rules for Design of Serial Lifting Equipment : Classification of Mechanism)

Mechanism group	1Bm	1Am	2m	3m	4m	5m
Load group	Average operating period per day (h)					
Light $k < 0.50$	<2	2-4	4-8	8-16	>16	-
Medium $0.50 < k < 0.63$	<1	1-2	2-4	4-8	8-16	>16
Heavy $0.30 < k < 0.80$	<0.5	0.5-1	1-2	2-4	4-8	8-16
Very Heavy $0.80 < k < 1.00$	<0.25	<0.5	0.5-1	1-2	2-4	4-8




# CHAIN HOIST


## Suspension Type




A-Frame 250~500kg




B-Frame 1000~3000kg [2falls]




C-Frame 3000kg



C-Frame 5000kg



C-Frame 7500kg




C-Frame 10000kg

Frame	Model	Capacity (KG)	Hoisting Motor-Single				Hoisting Motor-Dual				Load Chain (mm*Falls)	Net.Weight (kgs)	Dimension					
			Power(kw)		Speed(m/min)		Power(kw)		Speed(m/min)				Single			Dual		
			50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz			A	B	C	D	E	A
A	KGO-S250	250	0,21*8P	0,25*8P	3,5	4,2	-	-	-	-	Ø5x1	32	245	238	150	180	430	-
			0,42*4P	0,5*4P	7	8,4	-	-	-	-								
	KGO-S490	490	0,42*4P	0,5*4P	3,5	4,2	-	-	-	-	Ø5x2	37	245	238	150	180	430	-
	KGO-S500	500	0,92*4P	1,1*4P	7	8,4	-	-	-	-	Ø5x1	-	-	-	-	-	-	-
B	KGO-S(D)500	500	1,25*4P	1,5*4P	9	10,8	1,25/0,63*4/8P	1,5/0,75*4/8P	9,0/4,5	10,8/5,4	Ø7,1x1	65	295	245	145	210	495	325
			1,25*4P	1,5*4P	5,8	7	1,25/0,63*4/8P	1,5/0,75*4/8P	5,8/2,9	7,0/3,5								
	KGO-S(D)1000	1000	1,25*4P	1,5*4P	6,4	7,7	1,25/0,63*4/8P	1,5/0,75*4/8P	6,4/3,2	7,7/3,9	Ø7,1 x1	65	295	245	145	210	495	325
			1,7*4P	2,0*4P	5,8	7	1,7/0,85*4/8P	2,0/1,0*4/8P	5,8/2,9	7,0/3,5								
	KGO-S(D)1250	1250	1,7*4P	2,0*4P	6,4	7,7	1,7/0,85*4/8P	2,0/1,0*4/8P	6,4/3,2	7,7/3,9	Ø7,1x1	65	295	245	145	210	495	325
			2,1*4P	2,5*4P	6,7	8	2,1/1,05*4/8P	2,5/1,25*4/8P	6,7/3,3	8,0/4,0								
	KGO-S(D)1500	1500	2,1*4P	2,5*4P	7,3	8,8	2,1/1,05*4/8P	2,5/1,25*4/8P	7,3/3,7	8,8/4,4	Ø8,0x1	75	325	245	170	240	525	355
			1,25*4P	1,5*4P	2,9	3,5	1,25/0,63*4/8P	1,5/0,75*4/8P	2,9/1,5	3,5/1,8								
	KGO-S(D)1800	1800	1,25*4P	1,5*4P	2,9	3,5	1,25/0,63*4/8P	1,5/0,75*4/8P	3,2/1,6	3,9/1,9	Ø7,1x2	80	295	245	145	210	575	325
			1,7*4P	2,0*4P	2,9	3,5	1,7/0,85*4/8P	2,0/1,0*4/8P	2,9/1,5	3,5/1,8								
KGO-S(D)2000	2000	1,25*4P	1,5*4P	2,9	3,5	1,25/0,63*4/8P	1,5/0,75*4/8P	3,2/1,6	3,9/1,9	Ø7,1x2	80	295	245	145	210	575	325	
		1,7*4P	2,0*4P	3,2	3,9	1,7/0,85*4/8P	2,0/1,0*4/8P	3,2/1,6	3,9/2,0									
KGO-S(D)2500	2500	1,7*4P	2,0*4P	3,2	3,9	1,7/0,85*4/8P	2,0/1,0*4/8P	3,2/1,6	3,9/2,0	Ø7,1x2	80	295	245	145	210	575	325	
		2,1*4P	2,5*4P	3,3	4	2,1/1,05*4/8P	2,5/1,25*4/8P	3,3/1,7	4,0/2,0									
KGO-S(D)3000	3000	2,1*4P	2,5*4P	3,7	4,4	2,1/1,05*4/8P	2,5/1,25*4/8P	3,7/1,8	4,4/2,2	Ø8,0 x2	85	325	245	170	240	645	355	
		2,9*4P	3,5*4P	5	6	2,9/1,45*4/8P	3,5/1,75*4/8P	5,0/2,5	6,0/3,0									
C	KGO-S(D)3000	3000	2,9*4P	3,5*4P	5	6	2,9/1,45*4/8P	3,5/1,75*4/8P	5,0/2,5	6,0/3,0	Ø11,2x1	120	350	315	195	285	830	390
	KGO-S(D)5000	5000	2,9*4P	3,5*4P	2,5	3	2,9/1,45*4/8P	3,5/1,75*4/8P	2,5/1,3	3,0/1,5	Ø11,2x2	220	350	315	125	350	1190	390
	KGO-S(D)7500	7500	2,9*4P	3,5*4P	1,7	2	2,9/1,45*4/8P	3,5/1,75*4/8P	1,7/0,8	2,0/1,0	Ø11,2x3	390	385	325	190	430	1550	390
	KGO-S(D)10000	10000	2,9*4P	3,5*4P	1,3	1,5	2,9/1,45*4/8P	3,5/1,75*4/8P	1,3/0,6	1,5/0,8	Ø11,2x4	550	385	385	465	465	1550	390


standard

# CHAIN HOIST


## Motor Trolley Type




A-Frame 250~500kg




B-Frame 1000~3000kg [2falls]




C-Frame 3000kg



C-Frame 5000kg



C-Frame 7500kg



C-Frame 10000kg

Frame	Model	Capacity (KG)	Hoisting Motor—Single				Hoisting Motor—Dual				Traversing Motor				Load Chain (mm* Falls)	Net Weight (kgs)	I-Beam Width (mm)	Min. Radius For Curve (mm)	Dimension					
			Power(kw)		Speed(m/min)		Power(kw)		Speed(m/min)		Power(kw)		Speed(m/min)						Single			Dual		
			50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz					A	B	C	D	E	A
A	KG T-S250	250	0,21*8P	0,25*8P	3,5	4,2	—	—	—	—	0,33*4P	0,4*4P	16,7	20	Ø5x1	58	75~125	1200	245	238	240	320	490	—
			0,42*4P	0,5*4P	7	8,4	—	—	—	—	—	—	—	—	—	—			—	—	—	—	—	—
	KG T-S490	490	0,42*4P	0,5*4P	3,5	4,2	—	—	—	—	—	—	—	—	Ø5x2	60			245	238	240	320	490	—
	KG T-S500	500	0,92*4P	1,1*4P	7	8,4	—	—	—	—	—	—	—	—	Ø5x1	60	245	238	240	320	490	—		
B	KG T-S(D)500	500	1,25*4P	1,5*4P	9	10,8	1,25/0,63*4/8P	1,5/0,75*4/8P	9,0/4,5	10,8/5,4	0,33*4P	0,4*4P	16,7	20	Ø7,1x1	105	75~125	1200	295	245	240	320	500	325
			1,25*4P	1,5*4P	6,8	7	1,25/0,63*4/8P	1,5/0,75*4/8P	5,8/2,9	7,0/3,5	0,33*4P	0,4*4P	16,7	20	Ø7,1x1	105			295	245	240	320	500	325
	KG T-S(D)1000	1000	1,25*4P	1,5*4P	6,4	7,7	1,25/0,63*4/8P	1,5/0,75*4/8P	6,4/3,2	7,7/3,9	0,33*4P	0,4*4P	16,7	20	Ø7,1x1	105			295	245	240	320	500	325
			1,7*4P	2,0*4P	5,8	7	1,7/0,85*4/8P	2,0/1,0*4/8P	5,8/2,9	7,0/3,5	0,33*4P	0,4*4P	16,7	20	Ø7,1x1	105			295	245	240	320	500	325
	KG T-S(D)1250	1250	1,7*4P	2,0*4P	6,4	7,7	1,7/0,85*4/8P	2,0/1,0*4/8P	6,4/3,2	7,7/3,9	0,33*4P	0,4*4P	16,7	20	Ø7,1x1	105			295	245	240	320	500	325
			2,1*4P	2,5*4P	6,7	8	2,1/1,05*4/8P	2,5/1,25*4/8P	6,7/3,3	8,0/4,0	0,33*4P	0,4*4P	15,8	19	Ø8,0x1	115			325	245	240	320	530	355
	KG T-S(D)1500	1500	2,1*4P	2,5*4P	7,3	8,8	2,1/1,05*4/8P	2,5/1,25*4/8P	7,3/3,7	8,8/4,4	0,33*4P	0,4*4P	15,8	19	Ø8,0x1	115			325	245	240	320	530	355
			1,25*4P	1,5*4P	2,9	3,5	1,25/0,63*4/8P	1,5/0,75*4/8P	2,9/1,5	3,5/1,8	0,33*4P	0,4*4P	15,8	19	Ø7,1x2	115			295	245	240	320	580	325
	KGT-S(D)2000	2000	1,25*4P	1,5*4P	2,9	3,5	1,25/0,63*4/8P	1,5/0,75*4/8P	2,9/1,5	3,5/1,8	0,33*4P	0,4*4P	15,8	19	Ø7,1x2	115			295	245	240	320	580	325
			1,7*4P	2,0*4P	2,9	3,5	1,7/0,85*4/8P	2,0/1,0*4/8P	2,9/1,5	3,5/1,8	0,33*4P	0,4*4P	15,8	19	Ø7,1x2	115			295	245	240	320	580	325
KGT-S(D)2500	2500	1,7*4P	2,0*4P	3,2	3,9	1,7/0,85*4/8P	2,0/1,0*4/8P	3,2/1,6	3,9/2,0	0,33*4P	0,4*4P	15,8	19	Ø7,1x2	115	295	245	240	320	580	325			
		2,1*4P	2,5*4P	3,3	4	2,1/1,05*4/8P	2,5/1,25*4/8P	3,3/1,7	4,0/2,0	0,33*4P	0,4*4P	15,8	19	Ø8,0x2	120	325	245	240	320	650	355			
KGT-S(D)3000	3000	2,1*4P	2,5*4P	3,7	4,4	2,1/1,05*4/8P	2,5/1,25*4/8P	3,7/1,8	4,4/2,2	0,33*4P	0,4*4P	15,8	19	Ø8,0x2	120	325	245	240	320	650	355			
		2,9*4P	3,5*4P	5	6	2,9/1,45*4/8P	3,5/1,75*4/8P	5,0/2,5	6,0/3,0	0,33*4P	0,4*4P	13,3	16	Ø11,2x1	175	350	315	190	350	810	390			
C	KGT-S(D)3000	3000	2,9*4P	3,5*4P	5	6	2,9/1,45*4/8P	3,5/1,75*4/8P	5,0/2,5	6,0/3,0	0,33*4P	0,4*4P	13,3	16	Ø11,2x1	175	350	315	190	350	810	390		
			2,9*4P	3,5*4P	2,5	3	2,9/1,45*4/8P	3,5/1,75*4/8P	2,5/1,3	3,0/1,5	0,33*4P	0,4*4P	13,3	16	Ø11,2x2	275	350	315	200	350	1070	390		
KGT-S(D)5000	5000	5000	2,9*4P	3,5*4P	1,7	2	2,9/1,45*4/8P	3,5/1,75*4/8P	1,7/0,8	2,0/1,0	0,4*6P	0,5*6P	10,8	13	Ø11,2x3	480	465	330	260	430	1280	—		
			2,9*4P	3,5*4P	1,3	1,5	2,9/1,45*4/8P	3,5/1,75*4/8P	1,3/0,6	1,5/0,8	0,83*6P	1,0*6P	10,8	13	Ø11,2x4	640	465	390	465	465	1280	—		

# CHAIN HOIST

Special Type

## SINGLE PHASE HOIST

### Powerful Performance

Excellent performance including when lower voltage lifting up to the weight of 1.25 times heavier than rated weight.

### Enough Working Time

Over 20 minutes of running time as like 3 phase hoist.



Frame	Model	Capacity (KG)	Hoisting Motor				Load Chain (mm*Falls)	Net Weight (kgs)	Dimension				
			Power(kw)		Speed(m/min)				Single				
			50Hz	60Hz	50Hz	60Hz			A	B	C	D	E
A	KGO-S250-SP	250	0,21*8P	0,25*8P	3,5	4,2	Ø5x1	32	245	238	150	180	430
			0,42*4P	0,5*4P	7,0	8,4							
	KGO-S490-SP	490	0,42*4P	0,5*4P	3,5	4,2	Ø5x2	37	245	238	150	180	430
	KGO-S500-SP	500	0,92*4P	1,1*4P	7,0	8,4	Ø5x1						
B	KGO-S1000-SP	1000	1,25*4P	1,5*4P	5,8	7,0	Ø7,1x1	65	295	245	145	210	495
			1,25*4P	1,5*4P	6,4	7,7							
	KGO-S1800-SP	1800	1,25*4P	1,5*4P	2,9	3,5	Ø7,1x2	80	295	245	145	210	575
	KGO-S2000-SP	2000	1,25*4P	1,5*4P	3,2	3,9							

standard

Frame	Model	Capacity (KG)	Hoisting Motor				Traversing Motor				Load Chain (mm* Falls)	Net Weight (kgs)	I-Beam Width (mm)	Min. Radius For Curve (mm)	Dimension				
			Power(kw)		Speed(m/min)		Power(kw)		Speed(m/min)										
			50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz					A	B	C	D	E
A	KGT-S250-SP	250	0,21*8P	0,25*8P	3,5	4,2	0,33*4P	0,4*4P	16,7	20	Ø5x1	58	75~125	1200	245	238	240	320	490
			0,42*4P	0,5*4P	7,0	8,4													
	KGT-S490-SP	490	0,42*4P	0,5*4P	3,5	4,2	0,33*4P	0,4*4P	16,7	20	Ø5x2 Ø5x1	60			245	238	240	320	490
	KGT-S500-SP	500	0,92*4P	1,1*4P	7,0	8,4													
B	KGT-S1000-SP	1000	1,25*4P	1,5*4P	5,8	7,0	0,33*4P	0,4*4P	16,7	20	Ø7,1x1	105	75~125	1200	295	245	240	300	500
			1,25*4P	1,5*4P	6,4	7,7													
	KGT-S1800-SP	1800	1,25*4P	1,5*4P	2,9	3,5	0,33*4P	0,4*4P	15,8	19	Ø7,1x2	115	100~150	1500	295	245	240	300	580
	KGT-S2000-SP	2000	1,25*4P	1,5*4P	3,2	3,9													

standard



# VLC CHAIN HOIST

VLC Chain Host is produced by KG Cranes who has advanced technical skills as a manufacturer of hoist and crane component since 1968. VLC Chain Hoist is capable to handle the capacity up to 250tons by new technology.

High frequency

Competitive Price

Compact Size

Durability


More Safe

Modular Design

Capacity 6.3ton~250ton




## Main Body




## Characteristic

- Next generation chain hoist. Suitable for the work of high frequency, using high frequency and powerful torque motor
- Competitive price more than 40%
- Long life span by using high strength materials
- Easy to assemble and maintain by using progressive technique of modular system
- Up to 250tons capacity
- Saving electric bill (up to 30%) by using KGP (option)

## Variety




Mono-Rail Type (6TON~100TON)



Double-Rail Type



High frequency,  
powerful, Competitive price,  
More light



▶ Various pocket wheel is guaranteed a perfect fit and a smooth, low-wear chain run depends on the applied chain and the chain tolerances

SPROCKET



Load Chain



GEARED MOTOR



**Power Up**


▶ High efficiency, silence, easy to maintain and compact design by using planetary geared box motor

▶ We use various geared motor according to the type of the hoist.

▶ Long life chain which can be used in high capacity lifting devices

# VLC CHAIN HOIST

## Mono-Rail Type Hoist (6.3~50ton)



### Specifications

MODEL	Capa' (Ton)	ISO	Lift (m)	Hoisting				Traversing					
				Speed(m/min)		Motor (kwxp)	Load Chain dia x p	Rev.	Brake	Speed(m/min)		Motor (kwxp)	Brake
LCH0631	6			50Hz	6,3			1/1		50Hz	12,5	0,4 x 4	
				60Hz	7,5					60Hz	15,0		
LCH0632	12			50Hz	3,2			2/1		50Hz	12,5	0,75 x 4	
				60Hz	3,8					60Hz	15,0		
LCH0633	16			50Hz	2,1			3/1		50Hz	12,5	1,5 x 4	DC Magnet Disc Brake
				60Hz	2,5					60Hz	15,0		
LCH0634	25	M5	6	50Hz	1,6	8,5 x 4	16 x 45	4/1	DC Magnet Disc Brake	50Hz	12,5	1,5 x 4	DC Magnet Disc Brake
				60Hz	1,9					60Hz	15,0		
LCH0635	30			50Hz	1,3			5/1		50Hz	12,5	1,5 x 4	DC Magnet Disc Brake
				60Hz	1,5					60Hz	15,0		
LCH0636	35			50Hz	1,0			6/1		50Hz	12,5	1,5 x 4	DC Magnet Disc Brake
				60Hz	1,3					60Hz	15,0		
LCH0638	45			50Hz	0,8			8/1		50Hz	12,5	1,5 x 4	DC Magnet Disc Brake
				60Hz	1,0					60Hz	15,0		

### Dimensions(mm)


MODEL	Capa' (Ton)	T/S Rail Width(w)				Right Plan			Front Plan						Weight (kg)
		300		400		c	d	e	f	g	h	i	j	k	
		a	b	a	b										
LCH0631	6	550	250	600	300	630	550	90	110	300	900	180	330	450	1250
LCH0632	12	600	250	650	300	630	550	110	125	330	1000	200	365	500	1500
LCH0633	16	650	250	700	300	630	550	110	150	380	1300	425	615	800	1700
LCH0634	25	650	250	700	300	630	550	125	150	380	1400	510	700	1000	1900
LCH0635	30	650	250	700	300	630	550	125	150	2250	1500	415	1540	1200	2600
LCH0636	35	650	250	700	300	630	550	140	150	2400	1550	415	1615	1400	2800
LCH0638	45	650	250	700	300	630	550	160	150	2750	1600	415	1790	1750	3200

Note : 1, The transversing dimensions of width h-beam rails on the basis of one standard size.  
2, If Curved Rail Requires, this must be indicated in advance.



# VLC CHAIN HOIST

Mono-Rail Type Hoist (2.5~100ton)



## Specifications

MODEL	Capa <sup>1</sup> (Ton)	ISO	Lift (m)	Hoisting					Traversing				
				Speed(m/min)	Motor (kwxp)	Load Chain dia × p	Rev.	Brake	Speed(m/min)	Motor (kwxp)	Brake		
LCH1251	12	M5	6	50Hz	6,3	17 × 6	22 × 66	1/1	DC Magnet Disc Brake	50Hz	12,5	0,75 × 4	DC Magnet Disc Brake
				60Hz	7,5					60Hz	15,0		
LCH1252	25			2/1	50Hz			3,2		50Hz	12,5		
					60Hz			3,8		60Hz	15,0		
LCH1253	35			3/1	50Hz			2,1		50Hz	12,5		
					60Hz			2,5		60Hz	15,0		
LCH1254	45			4/1	50Hz			1,6		50Hz	12,5		
					60Hz			1,9		60Hz	15,0		
LCH1255	60			5/1	50Hz			1,3		50Hz	12,5		
					60Hz			1,5		60Hz	15,0		
LCH1256	70			6/1	50Hz			1,1		50Hz	12,5		
					60Hz			1,3		60Hz	15,0		
LCH1258	90			8/1	50Hz			0,8		50Hz	12,5		
					60Hz			1,0		60Hz	15,0		


## Dimensions(mm)

MODEL	Capa <sup>1</sup> (Ton)	T/S Rail Width(w)				Right Plan			Front Plan						Weight (kg)
		300		400		c	d	e	f	g	h	i	j	k	
		a	b	a	b										
LCH1251	12	600	250	650	300	780	650	110	125	330	1200	200	365	500	1800
LCH1252	25	650	250	700	300	780	650	125	150	380	1400	230	420	600	2300
LCH1253	35	650	250	700	300	780	650	140	150	1300	1750	415	1065	800	3200
LCH1254	45	650	250	700	300	780	650	160	150	1550	1800	415	1190	1350	3500
LCH1255	60	650	250	700	300	780	650	170	150	2300	2300	415	1565	1650	4900
LCH1256	70	650	250	700	300	780	650	190	150	2550	2400	415	1690	1800	5200
LCH1258	90	650	250	700	300	780	650	210	150	3300	2500	415	2065	2450	5800

Note : 1. The transversing dimensions of width h-beam rails on the basis of one standard size.  
2. If Curved Rail Requires, this must be indicated in advance.

# VLC CHAIN HOIST

## Mono-Rail & Double Rail Type Hoist (25~250ton)



### Specifications

MODEL	Capa' (Ton)	ISO	Lift (m)	Hoisting				Traversing							
				Speed(m/min)	Motor (kwxp)	Load Chain dia x p	Rev.	Brake	Speed(m/min)	Motor (kwxp)	Brake				
LCH2501	25	M5	6	50Hz	6,5	37 x 6	32 x 90	1/1	DC Magnet Disc Brake	50Hz	12,5	1,5 x 4	DC Magnet Disc Brake		
				60Hz	7,8					60Hz	15,0				
LCH2502	50			50Hz	3,3					2/1	50Hz			12,5	
				60Hz	3,9										60Hz
LCH2503	75			50Hz	2,2					3/1	50Hz			12,5	
				60Hz	2,6										60Hz
LCH2504	100			50Hz	1,7					4/1	50Hz			12,5	
				60Hz	2,0										60Hz
LCH2506	150			50Hz	1,1					6/1	50Hz			12,5	3,7 x 4
				60Hz	1,3										
LCH2508	200	50Hz	0,8	8/1	50Hz	12,5	5,5 x 4								
		60Hz	1,0					60Hz	15,0						
LCH2510	250	50Hz	0,7	10/1	50Hz	12,5									
		60Hz	0,8				60Hz	15,0							

### Mono-Rail Type Dimensions(mm)

MODEL	Capa' (Ton)	T/S Rail Width(w)				Right Plan			Front Plan						Weight (kg)
		300		400		c	d	e	f	g	h	i	j	k	
		a	b	a	b										
LCH2501	25	650	250	700	300	900	850	125	150	380	1500	230	420	650	2800
LCH2502	50	650	250	700	300	900	850	160	150	750	1600	415	790	900	3800
LCH2503	75	650	250	700	300	900	850	190	150	1775	2900	415	1300	1700	5500
LCH2504	100	650	250	700	300	900	850	210	150	2550	3000	415	1690	2150	6400

### Double-Rail Type Dimensions(mm)

MODEL	Capa' (Ton)	T/S Rail Width(w)		a	b	c	d	e	f	g	h	i	Weight (kg)
LCH2506	150	1400	1600	1400	84	160	720	270	1000	1800	1500	800	13000
		1800	2000										
LCH2508	200	1600	1800	1500	84	180	720	300	1000	2200	1750	1000	15000
		2000	2200										
LCH2510	250	1600	1800	1600	84	200	720	330	1000	2500	2000	1300	18000
		2000	2200										

Note : 1. The transversing dimensions of width h-beam rails on the basis of one standard size.  
 2. If Curved Rail Requires, this must be indicated in advance.

### Selection Criteria

#### 1. The group is determined by the load spectrum and operating time.

Load Spectrum	Average operating time per working day in hours			
	2-4	4-8	8-16	over 16
Light	2-4	4-8	8-16	over 16
Medium	1-2	2-4	4-8	8-16
Heavy	0.5-1	1-2	2-4	4-8
Very Heavy	0.25-0.5	0.5-1	1-2	2-4
Mechanism Group, ISO	M4	M	M6	M7

#### 3. Model and capacity table

Model	Reeving	Load(kg)			
		8000	6000	6000	4000
LCH063	1/1	8000	6000	6000	4000
	2/1	15000	12000	10000	8000
	3/1	20000	16000	16000	12000
	4/1	30000	25000	20000	16000
	5/1	35000	30000	25000	20000
	6/1	40000	35000	30000	25000
	8/1	50000	45000	40000	30000
LCH125	1/1	15000	12000	10000	8000
	2/1	30000	25000	20000	16000
	3/1	40000	35000	30000	25000
	4/1	50000	45000	40000	30000
	5/1	70000	60000	50000	40000
	6/1	80000	70000	60000	50000
	8/1	100000	90000	80000	60000
LCH250	1/1	30000	25000	20000	16000
	2/1	60000	50000	40000	35000
	3/1	90000	75000	60000	50000
	4/1	120000	100000	80000	70000
	6/1	180000	150000	125000	100000
	8/1	250000	200000	175000	125000
	10/1	300000	250000	200000	150000

#### 4. Example

LCH250	: 25000kg
Load spectrum	: "Light" form table
Hoist speed	: 6.0m/min
Reeving	: 1/1
Average hook path	: 6m
No. of cycles/hour	: 20
Working time/day	: 8hours

The average operation time per working day is estimated or calculated as follows:

$$\text{Operating time/day} = \frac{2 \cdot \text{average hook path} \cdot \text{no. of cycles/hour} \cdot \text{working time/day}}{60 \cdot \text{hoist speed}} = \frac{2 \cdot 6 \cdot 20 \cdot 8}{60 \cdot 6} = 5.33 \text{ hours}$$


For the light load spectrum and an average daily operating time of 5.33 hours, the table shows group M5. For a load capacity of 25000g and 1/1 rope reeving, the table indicates hoist size LCH250-25000.

#### 2. The load spectrum

(in most cases estimated) can be evaluated in accordance with the following definitions


##### Light

Hoist units which are usually subject to very small loads and in exceptional cases only to maximum loads.




##### Medium

Hoist units which are usually subject to small loads but rather often to maximum loads.




##### Heavy

Hoist units which are usually subject to medium loads but frequently to maximum loads.





##### Very heavy

Hoist units which are usually subject to maximum or almost maximum loads.



# TURNING DEVICE

Easy, Fast and Safe




**Control Range**

- S 250 ~ 600mm
- M 1200 ~ 1800mm
- L 1800 ~ 3000mm


Model	CAPACITY	TYPE	A	B	max.C	D	G	K	L	t	w	SPEED m/min	WEIGHT kg
TD 015-	1,500kg	S	580	595	600	350	700	750	1175	20	110	6,0	195
		M	1180	1195	1800	350	1200	1250	2375	20	110	6,0	400
TD 030-	3,000kg	S	600	625	600	400	700	750	1225	20	110	6,0	240
		M	1200	1225	1800	400	1200	1250	2425	20	110	6,0	550
TD 060-	6,000kg	S	635	690	600	430	700	780	1325	25	110	5,0	400
		M	1235	1290	1800	430	1200	1280	2525	25	110	5,0	850
TD 090-	9,000kg	S	660	740	600	460	900	980	1400	40	120	4,5	600
		M	1260	1340	1800	460	1200	1280	2600	40	120	4,5	1000
		L	1860	1940	3000	460	1800	1880	3800	40	120	4,5	1500
TD 150-	15,000kg	S	1385	1535	1800	500	1200	1300	2920	50	130	3,4	1150
		M	1985	2135	3000	500	1800	1900	4120	50	130	3,4	1700
TD 200-	20,000kg	S	1325	1445	1800	520	1200	1300	2770	50	150	2,3	1500
		M	1925	2045	3000	520	1850	1950	3970	50	150	2,3	2100
TD 300-	30,000kg	S	1475	1495	1800	650	1250	1400	2970	60	150	2,3	1900
		M	2075	2095	3000	650	1850	2000	4170	60	150	2,3	2650

# TURNING DEVICE


Chain Type




## Application




Ship block




Main frame




Concrete block



Truss



Steel Structure



Engine Block



# TURN OVER HOIST

One Hoist doing **Three** Functions!!



Function

### A + B Hoisting

We supply the single hook attachments for option



Function

### A or B Single turning


Slow turning and safe turning



Function


### A ⇄ B Dual turning

High speed turning and keeping the weight balance




According as the target products, we supply the special hanging jig.


### Application




Ship block





Concrete block



Circular cone



# TURN OVER HOIST



※ Value of S,L,M,N will be decide by Value a,b,c,d,e


※ For example

$$e = 20,000 \quad a=b=c=d=1,000$$

$$S = 30,000 \quad L=1,000 \quad M = b+a+d+300 = 3,300 \quad N = c+d+300 = 2,300$$




# TURN OVER HOIST




Model		Capacity (ton)	TO 4 (2+2)	TO 6 (3+3)	TO 10 (5+5)	TO 15 (7.5+7.5)	TO 20 (10+10)	TO 30 (15+15)
Hoist	Max. lift(m)		12	12	12	12	12	12
	Hoisting Speed (m/min)	High Speed	10	9.0	5.6	3.8	4.5	4.5
		Low Speed	5	4.5	4.2	2.8	3.0	3.0
	Hoisting Motor 2 X (Kw X P)	High Speed	3.7 X 4	5.5 X 4	5.5 X 6	5.5 X 6	9 X 8	13 X 8
		Low Speed	1.8 X 8	2.8 X 8	4.2 X 8	4.2 X 8	6 X 12	8.5 X 12
	Wire Rope	Construction	6 X Fi(25)	6 X Fi(25)	6 X Fi(25)	6 X Fi(25)	6 X Fi(25)	6 X Fi(25)
Dia(mm) X No.of Ropes		8 X 4	9 X 4	12.5 X 4	14 X 4	16 X 4	20 X 4	
		Brake	DC Magnet Disc Brake					
Traversing	Traversing Speed (m/min)	High Speed	24	15	15	15	15	15
		Low Speed	16	10	10	10	10	10
	Traversing Motor (Kw X P)	High Speed	0.75 X 4	0.75 X 4	0.75 X 4	1.5 X 4	1.5 X 4	1.5 X 4 (2units)
		Low Speed	0.5 X 6	0.5 X 6	0.5 X 6	1.0 X 6	1.0 X 6	1.0 X 6 (2units)
Dimensions (approx.) (mm)	H		450	450	550	750	800	1100
	R		1150	1150	1150	1200	1300	1800
	A		790	790	837	852	892	1100
	B		765	765	845	855	885	950
	C		630	645	695	860	900	980
	G		800	800	950	950	1040	1200
	K		800	800	950	950	1040	1200
	W		1300	1300	1350	1400	1490	1650
	D		47	58	58	58	58	70
	P		165	165	165	180	220	250
Q		195	195	195	210	250	280	
Weight(approx.) (kg)			800	1000	1450	1700	2400	3500
Traversing Rail			15kg/m	15kg/m	15kg/m	22kg/m	22kg/m	30kg/m

# TURN OVER HOIST



Model		Capacity (ton)	TO 40 (20+20)	TO 60 (30+30)	TO 80 (40+40)	TO 100 (50+50)	TO 120 (60+60)	TO 160 (80+80)
Hoist	Max. lift(m)		12	12	12	12	12	12
	Hoisting Speed (m/min)	High Speed	4.2	2.8	4.2	2.8	2.8	2.1
		Low Speed	2.8	1.8				
	Hoisting Motor 2 X (Kw X P)	High Speed	17 X 8	17 X 8	37 X 6	37 X 6	37 X 6	37 X 6
		Low Speed	11.5 X 12	11.5 X 12				
	Wire Rope	Construction	6 X Fi(25)	6 X Fi(25)	6 X Fi(25)	6 X Fi(25)	6 X Fi(25)	6 X Fi(25)
Dia(mm) X No.of Ropes		22.4 X 4	22.4 X 6	28 X 6	28 X 6	28 X 6	28 X 8	
Brake		DC Magnet Disc Brake						
Traversing	Traversing Speed (m/min)	High Speed	15	15	15	15	15	15
		Low Speed	10	10	10	10	10	10
	Traversing Motor (Kw X P)	High Speed	2.2 X 4 (2units)	2.2 X 4 (2units)	3.7 X 4 (2units)	3.7 X 4 (2units)	3.7 X 4 (2units)	5.5 X 4 (2units)
		Low Speed	1.5 X 6 (2units)	1.5 X 6 (2units)	2.2 X 6 (2units)	2.2 X 6 (2units)	2.2 X 6 (2units)	3.7 X 6 (2units)
Dimensions (approx.) (mm)	H	1300	1600	1600	1800	1900	1900	
	R	2300	2800	2800	3000	3000	3000	
	A	1300	1550	1750	2000	2000	2000	
	B	1150	1350	1550	1550	1550	1550	
	C	1220	1220	1220	1800	1800	1800	
	G	1350	1600	1600	1850	2150	2150	
	K	1350	1600	1600	1850	2150	2150	
	W	1900	2300	2400	3000	3000	3000	
	D	80	80	80	120	120	120	
	P	450	450	500	400	500	600	
Q	490	490	540	540	540	540		
Weight(approx.) (kg)		5500	8000	9700	13000	16000	19000	
Traversing Rail		37kg/m	37kg/m	37kg/m	73kg/m	73kg/m	73kg/m	

# MEMO



# KG CRANE *New* PRODUCT SELECTION


## DB Crab

### Gear Box & DC MG Brake

- Modular Design
- Variable Speed
- Variety Type of Brakes

### Reference

- Hyundai heavy industry and others : 20,000ton / year
- POSCO steel mill and others : 30,000ton / year
- Samsung shipyard and others : 50,000ton / year
- American Shipyard : 5,000ton / year
- Middle east Steel mill : 10,000ton / year



### Wheel Block & TS Geared Motor

- Single Case Block
- Compact Design
- BBS Design
- Easy Maintenance

### Main Frame


- 10Kinds Modular Design
- Package Type

### Inverter Panel

- VVVF Control
- Usage Memory Function

**40% More Light**  
**40% Smaller**  
**40% Saving Cost**


## Turn Over Hoist




### One Hoist doing Three Functions!!

- Function **A + B Hoisting**  
We supply the single hook attachments for option
- Function **A or B Single turning**  
Slow turning and safe turning
- Function **A ⇄ B Dual turning**  
High speed turning and keeping the weight balance


### Application



Ship block



Concrete block




Truss


## Turning Device




**Turn it Easy**




### Application



Truss



Steel Structure




Engine Block

## Low Space Crane

### Save the Building Construction

If you compare with single girder crans\*, LSCrane reduce the crane height from 3.6meter to 1.6meter. It means that you don't need to raise the building height for the hook approach.  
 (\*MHO 20 ton Span 20m)



**Amazing Crane Girder Size**  
 LSCrane is a same size with single girder crane\* even satisfy the diube girder crane hook approach. It means that LSCrane save the 44% self weight.

### VVVF Control

VVVF(Variable Voltage Variable Frequency)  
 Control : Inverter  
 Safe and exact working are guaranteed.

### Hook Approach Innovation


Hook approach innovation LSCrane hook approach is the highest than any other crane.

### Reference


- Doosan heavy industry and others : 8,000ton / year
- POSCO steel and others : 6,000ton / year

**KG Crane is the manufacturer of hoist and crane component since 1968**  
**From Pinion gears to 600ton Goliath cranes. Please visit [www.kgcrane.com](http://www.kgcrane.com)**

• Tel : +82-32-583-6671 Fax : +82-32-583-6674 •



- Construction Cost Save (30%)
- Extraordinary Crane Girder Size
- Clean Crane (Low Noise & Low Vibration)
- Innovative Hook Height



**KGCranes**  
www.kgcrane.com

482-1, Kajua-dong, Seo-gu, Incheon-city 404-817, KOREA  
 Tel : +82-32-583-6671  
 Fax : +82-32-583-6674  
 E-mail : kgcrane@kgcrane.com  
 overseas@kgcrane.com

KGCranes reserves the right to alter or amend the above information without notice. This document and the information contained herein, is the exclusive property of KGCranes and represents a non-public, confidential and proprietary trade secret that may not be reproduced, disclosed to third parties, altered or otherwise employed in any manner whatsoever without the express written consent of KGCranes. Copyright © (2011) KGCranes, All rights reserved.

The specification of catalogue could be changed without any previous notice.

Ver. #: TG201101001