

re_reporter-IP/SE+

Omnibrid Business Surveillance System



Product information

The re_reporter-IP/SE+ is a pure digital network recorder supporting multiple compression algorithms and digital matrix functionalities for up to 32 IP camera channels (license). The system is based on TCP/IP (1Gbit onboard Ethernet) providing a sole IP solution. IP-cameras of various brands can be integrated into the system for recording and playback purposes via license. H264CCTV, H.264 and MJPEG formats are supported with free configurable resolutions. In addition, it provides 16 sabotage controlled binary inputs and 8 relay outputs.

- | Pure IP network recorder with digital video matrix functionality based on TCP/IP
- | Up to 32 network cameras of selected brands can be attached to the system via license
- | Omnibrid technology supporting multi standard video compression
- | Up to 4 hard disk drives for database (internal)
- | iSCSI support for external storage
- | Video management functionality based on internal programmable logic controller (GeViPLC)
- | Dynamic user interface adaptations triggered by events or user profiles
- | Integration of unlimited systems via network (LAN/WAN) using TCP/IP

GEUTEBRÜCK
Competence in Video Security

Technical data		re_reporter-IP/SE+
Video & audio sources		
Digital (IP)	Compression algorithms	M-JPEG, H.264 (multimedia), H264CCTV, MPEG4CCTV, MPEG4CCTV/MP
	Supported resolutions	D1, CIF, QCIF, Megapixel, HD
	Supported network cameras	re_reporter-IP/SE+ supports direct recording and playback of network cameras from: GEUTEBRÜCK TopLine, GEUTEBRÜCK TopLine, GEUTEBRÜCK VIPCAM, GEUTEBRÜCK EcoLine, JVC, AXIS, ARECONTVISION, Basler, FLIR, Hikvision, Hitron, IQInVision, Pelco, RIVA, RTSP-Universal, Samsung, Sony, Sanyo, Bosch, Acti, CNB, Panasonic and Mobotix. The ONVIF standard is supported. Detailed and current information on supported IP cameras can be found on our website at: Products/useful information
	Recording rate	The recording rate strongly depends on the type of network camera and the compression algorithm used.
	Recording formats	All resolutions supported by the network camera can be recorded and displayed in the corresponding format.
	Number of IP sources	An unlimited number of video sources (TopLine, CAM2IP, VIPCAM) can be connected license free. The overall number of IP cameras are limited by the available network bandwidth. IP cameras from other manufacturers can be integrated via license
Analog	Analog sources can be connected using CAM2IP. For more information, please see the corresponding technical data sheets.	
	Audio inputs	1 x mono (system audio) ISO/IEC 11172-2 Layer II, sampling rates: 32 kHz, 44.1 kHz and 48 kHz, 16-bit
Video & audio (output)		
Video outputs for live and stored images		DVI-I output (QXGA, 16.7 million colors) Display Port (WQXGA, 16,7 million colors) Resolution depending on the connector monitor up to 2048 x 1536 pixels @ 75 Hz (Dual DVI) or up to 2560 x 1600 @ 60 Hz (Display Port).
Audio outputs		1 x stereo (line out, jack, 3.5 mm)
Interfaces		
Control inputs		16 internal floating input contacts, tamper-monitored (switchable)
Relay outputs		8 internal relay outputs, 24 V DC, 1 A
Serial		1 x serial interface (RS-232) expandable with additional card to 4 x RS-232 (e.g., for remote camera control)
USB		8 USB 2.0 interfaces, 2 on the front, 6 on the back
Ethernet		1 x Ethernet 10/100/1000 base-TX interface, expandable with additional card
PC keyboard, mouse		USB ports on the back of the unit
Recording & transmission		
Database throughput		28-30 MB/s with internal storage (max. 4 SATA hard drives)40-50 MB/s for external storage (e.g. iSCSI RAID System, G-VRaid)
Playback throughput		Depending on the compression format, up to 20 live channels. MPEG4CCTV: Up to 1200 fps, M-JPEG: Up to 800 fps, H.264 (multimedia): Up to 400 fps (sum of all GSC/view windows on a separate evaluation computer, e.g. GSCSpeedView with built-in quad-VGA graphics card)
Software matrix		Real „live transmission“ with up to 25/30 fps per each available video channel (analog sources) Network cameras are transmitted with the frame rate you support (digital sources)
Latency times M-JPEG, H.264 (multimedia)		Depending on the specific IP camera
Functions for data reduction for network and storage	FLTM*	Fading Long Term Memory – automatic (adjustable) reduction of the frame rates in the older database streams
	* Based on the principle, not for H.264 (multimedia)	

Image processing		
Video analysis (may require license*)	Basic AD	License-free integrated Basic Activity Detection for the entire image area.
	Advanced AD*	Advanced Activity Detection – 42 x 34 configurable detection cells, reaction time: 160 ms
	G-Tect/MoP*	Motion Privacy (Picture blurring function for moving objects)
	CPZ	Client Privacy Zones (Picture blurring function for predefined areas)
	ANPR*, ANPR-4ChMux*	Number plate recognition for moving vehicles, and for fleet monitoring
	VCA4IP	Video Content Analysis for IP – ability to use the above video analysis methods and IP sources
Diagnostics	Synchronous signal surveillance (analog sources), contrast surveillance, angle monitoring (CPA), GSCDiagnostics	
Compression settings MPEG4CCTV, H264CCTV	Variable GOP length VGL Variable frame rate VFR Variable bit rate VBR Constant picture quality CPQ	
Cutlist	Ability to easily create a cutting list for a compact data export.	
Data export	Export of image data available in the following formats: GBF* (GEUTEBRÜCK Backup File), MPEG2* (mpg), MPEG4CCTV (m2v), H.264 (h264), Video-DVD* (vob), JPG (3 Qualitäts-Level), BMP All data media under Windows are supported as well as a direct export to CD/DVD. * Export including audio possible	
Storage media		
Internal	Standard disk holder Max. 4 SATA hard drives for the multimedia database	
External	Optional external RAID system using iSCSI-based products (e.g. G-VRaid), other storage media and storage concepts on request	
General		
Operating system	Windows 7 embedded 64Bit	
Processor	INTEL Pentium Dual Core G850 2,9 GHz inside or better	
Main memory	2 x 2 GB RAM (optionalally upgradeable to 4 x 2 GB RAM)	
Voltage supply	Power supply unit: 110 - 240 V AC / 60 - 50 Hz ±10%, 300 W	
Power consumption	Approx. 200 W fully equipped (4 x HDD)/approx. 140 W (1x HDD)	
Power input	IEC connector according to IEC 320 C13	
Ambient temperature	0 °C to +35 °C	
Dimensions in mm: as 19" installation unit as a desktop unit	3 U x 415 mm (depth) 443 x 135 x 415 (W x H x D)	
Weight	Approx. 11.6 kg net (2x HDD)	
Order no.	0.35114	

compe tence

re_porter_IP/SE+_PI_EN 15.10.2012

Technical alterations reserved

GEUTEBRÜCK GmbH

Im Nassen 7-9 | D-53578 Windhagen | Tel. +49 (0)2645 137-0 | Fax-999 E-mail: info@geutebrueck.com | Web: www.geutebrueck.com